

# **OVERVIEW**





1. Optical drive *	9. Line-out (3.5mm)
2. Power button	10. Flex IO *
3. Microphone (3.5mm)	11. HDMI 2.1 TMDS
4. Card reader *	12. 2x DisplayPort 1.4
5. Headphone / microphone combo jack (3.5mm)	13. 4x USB 2.0
6. USB-C 3.2 Gen 1	14. 2x PS/2 ports (keyboard / mouse) *
7. 2x USB 3.2 Gen 1	15. Ethernet (RJ-45)
8. 2x USB 3.2 Gen 2	16. Optional ports on expansion cards *

Notes:

- Ports with \* are only available on selected models
- More ports are available through the optional expansion cards (not shown on the sample product above)

## ThinkCentre M70s Gen 3

## PERFORMANCE

## **Processor**

### **Processor Family**

Intel® Pentium®, or 12th Generation Intel Core™ i3 / i5 / i7 / i9 Processor

### Processor

Processor Name	Cores	Threads	Base Frequency	Max Frequency	Cache	Processor Graphics
Core i5-12400	6 (6 P-core + 0 E- core)	12	P-core 2.5GHz	P-core 4.4GHz	18MB	Intel UHD Graphics 730
Core i5- 12400F	6 (6 P-core + 0 E- core)	12	P-core 2.5GHz	P-core 4.4GHz	18MB	-
Core i5-12500	6 (6 P-core + 0 E- core)	12	P-core 3.0GHz	P-core 4.6GHz	18MB	Intel UHD Graphics 770
Core i7-12700	12 (8 P-core + 4 E-core)	20	P-core 2.1GHz / E-core 1.6GHz	P-core 4.8GHz / E-core 3.6GHz	25MB	Intel UHD Graphics 770
Core i7- 12700F	12 (8 P-core + 4 E-core)	20	P-core 2.1GHz / E-core 1.6GHz	P-core 4.8GHz / E-core 3.6GHz	25MB	-
Core i9-12900	16 (8 P-core + 8 E-core)	24	P-core 2.4GHz / E-core 1.8GHz	P-core 5.0GHz / E-core 3.8GHz	30MB	Intel UHD Graphics 770
Core i9- 12900F	16 (8 P-core + 8 E-core)	24	P-core 2.4GHz / E-core 1.8GHz	P-core 5.0GHz / E-core 3.8GHz	30MB	-

## **Operating System**

### **Operating System**

- Windows® 11 Pro 64
- Windows 11 Home 64
- Windows 11 DG Windows 10 Pro 64
- Windows 10 IoT Enterprise LTSC 2021
- Ubuntu Linux
- No operating system

## Graphics

### **Graphics**<sup>[1]</sup>

Graphics	Туре	De Memory Connector Max Resolution		Key Features	Remark	
Intel UHD graphics 730	Integrated	Shared	2x DP 1.4 HBR2, 1x HDMI® 2.1 TMDS, 1x Flex IO (VGA / DP 1.2 / HDMI 2.1 TMDS / USB- C)	4096x2304@60hz(DP), 4096x2160@60Hz[HDMI / Flex IO(HDMI)], 3840x2160@60Hz[Flex IO(USB-C / DP)], 2048x1536@50Hz[Flex IO(VGA)]	DirectX® 12	-
Intel UHD graphics 770	Integrated	Shared	2x DP 1.4 HBR2, 1x HDMI 2.1 TMDS, 1x Flex IO (VGA / DP 1.2 / HDMI 2.1 TMDS / USB- C)	4096x2304@60hz(DP), 4096x2160@60Hz[HDMI / Flex IO(HDMI)], 3840x2160@60Hz[Flex IO(USB-C / DP)], 2048x1536@50Hz[Flex IO(VGA)]	DirectX 12	-

Notes:

1. The information of integrated graphics are not applicable for the models without integrated graphics (for the details, please refer to processor section)

## **Monitor Support**

### Monitor Support<sup>[1]</sup>

Supports up to 4 independent displays via onboard ports (2x DP, 1x HDMI, and 1x optional Flex IO), more displays support via discrete graphics

Notes:

1. Onboard video ports are only available for the models with integrated graphics

## Chipset

### Chipset

Intel Q670 Chipset

## Memory

### Max Memory<sup>[1]</sup>

Up to 128GB DDR4-3200

### **Memory Slots**

Four DDR4 DIMM slots, dual-channel capable

### **Memory Type**

DDR4-3200

Notes:

1. The max memory is based on the test results with current Lenovo® memory offerings. The system may support more memory as the technology develops.

## Storage

### Storage Support<sup>[1][2]</sup>

- Up to three drives, 1x 2.5"/3.5" HDD + 1x 2.5" HDD + 1x M.2 SSD
- 2.5" HDD up to 1TB each
- 3.5" HDD up to 2TB
- M.2 SSD up to 2TB

### Storage Type

Disk Type	Interface	RPM	Offering	Security
2.5" SATA HDD	SATA 6Gb/s	7.2K	-	-
3.5" SATA HDD	SATA 6Gb/s	7.2K	-	-
M.2 2242 SSD	PCIe® NVMe®, PCIe 3.0 x4	-	-	-
M.2 2280 SSD	PCIe NVMe, PCIe 3.0 x4	-	-	Opal
M.2 2280 SSD	PCIe NVMe, PCIe 4.0 x4 Performance	-	-	Opal2
M.2 2280 SSD	PCIe NVMe, PCIe 4.0 x4 Value	-	-	Opal2

### RAID

No support

Notes:

- 1. The storage capacity supported is based on the test results with current Lenovo storage offerings. The system may support larger storage as the technology develops.
- 2. The max capacity of SSD/HDD is based on the test results with current Lenovo SSD/HDD offerings. The system may support more capacity as the technology develops.

## Removable Storage

### Optical

- DVD-ROM, SATA connector, slim (9.0mm)
- DVD burner (DVD±RW), SATA connector, slim (9.0mm)
- None

### Card Reader

- 3-in-1 card reader (SD, SDHC, SDXC)
- No card reader

## Multi-Media

### Audio Chip

High Definition (HD) Audio, Realtek® ALC897Q-CG codec

### Speakers

Single speaker, 1W x1

## **Power Supply**

### Power Supply

Power	Туре	Efficiency	Key Features
180W	Fixed	85%	100V - 240V
260W	Fixed	90%	100-240V, 50-60Hz
310W	Fixed	92%	100-240V, 50-60Hz
380W	Fixed	92%	100-240V, 50-60Hz

## DESIGN

## Input Device

### Keyboard

- Lenovo Calliope Keyboard (USB connector), black
- Lenovo Calliope Wireless Keyboard (2.4GHz via USB receiver), black
- Lenovo Traditional Keyboard (USB connector), black
- No keyboard

### Mouse

- Lenovo Calliope Mouse (USB connector), black
- Lenovo Calliope Wireless Mouse (2.4GHz via USB receiver), black
- Lenovo Mouse (PS/2 connector), black (only available via special bid)
- Lenovo Fingerprint Mouse (USB connector), Windows Hello support, black
- No mouse

## Mechanical

### **Form Factor**

SFF (8.2L)

### Dimensions (WxDxH)

93 x 298 x 340 mm (3.6 x 11.7 x 13.4 inches)

### Weight<sup>[1]</sup>

5.3 kg (11.7 lbs)

### Case Color

Black

## Bays<sup>[2]</sup>

- 1x 2.5" disk bay
- 1x 3.5" disk bay
- 1x slim ODD bay

### **Expansion Slots**

- One PCIe 4.0 x16, low-profie
- Two PCIe 3.0 x1, low-profile
- Two M.2 slots (one for WLAN, one for SSD)

### EOU

Toolless cover, disk, optical, extension card assembly / removal

### Stand

- Vertical stand
- No stand

#### Others

- (Optional) Dust filter
- Supports Smart Power On

#### Notes:

2. 2.5" HDD tray is optional, or comes with 2.5 HDD. 3.5" bay supports 2.5" / 3.5" HDD, 3.5" to 2.5 converter comes with 2nd 2.5" HDD.

<sup>1.</sup> Weight may vary by configuration.

# CONNECTIVITY

## Network

### **Onboard Ethernet**

Gigabit Ethernet, Intel Ethernet Connection I219-LM, 1x RJ-45, supports Wake-on-LAN

### **Optional Ethernet**

- Gigabit Ethernet, Bitland BN8E88, 1x RJ-45, PCIe x1
- 2.5 Gigabit Ethernet, Realtek RTL8125BGS, 1x RJ-45, PCIe x1
- No optional Ethernet

### WLAN + Bluetooth®

- Realtek RTL8822CE, 802.11ac Dual Band 2x2 Wi-Fi® + Bluetooth 5.0, M.2 card
- Realtek RTL8852BE, Wi-Fi 6, 802.11ax Dual Band 2x2 Wi-Fi + Bluetooth 5.2, M.2 card
- Intel Wireless-AC 9560, 802.11ac Dual Band 2x2 Wi-Fi + Bluetooth 5.0, M.2 card
- Intel Wi-Fi 6 AX201, 802.11ax 2x2 Wi-Fi + Bluetooth 5.2, M.2 Card
- No WLAN and Bluetooth

### Ports<sup>III</sup>

### Front Ports

- 2x USB 3.2 Gen 1
- 2x USB 3.2 Gen 2
- 1x USB-C 3.2 Gen 1 (15W charging)
- 1x headphone / microphone combo jack (3.5mm)
- 1x microphone (3.5mm)

### **Optional Front Ports**

### 1x card reader

### Rear Ports<sup>[2]</sup>

- 4x USB 2.0
- 1x HDMI 2.1 TMDS
- 2x DisplayPort<sup>™</sup> 1.4
- 1x Ethernet (RJ-45)
- 1x line-out (3.5mm)

### Optional Rear Ports

- 1x USB-C 3.2 Gen 1 with DisplayPort function and 5V@3A charging (Flex IO)
- 1x HDMI 2.1 TMDS (Flex IO)
- 1x VGA (Flex IO)
- 1x DP 1.2 (Flex IO)
- 2x USB 3.2 Gen 1 (via 2-port USB expansion card, PCIe x1)
- 1x serial
- 1x 2nd serial
- 4x serial (via 4-port serial expansion card, PCIe x1)
- 1x parallel
- 2x PS/2

Notes:

- 1. The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed. USB 2.0: 480 Mbit/s:
- USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;
- USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;
- USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;
- Thunderbolt™ 3/4: 40 Gbit/s;
- FireWire 400: 400 Mbit/s;
- FireWire 800: 800 Mbit/s
- 2. For video ports on discrete graphics, please see graphics section

## **Monitor Cable**

#### **Monitor Cable**

- DP to dual DP dongle
- DP to DVI-D dongle
- DP to HDMI 1.4 dongle

- DP to VGA cable (1.5M)
- DP to VGA dongle
- HDMI to VGA dongle
- No monitor cable

# **SECURITY & PRIVACY**

## Security

### **Security Chip**

Discrete TPM 2.0, TCG certified

### Physical Locks

- (Optional) E-lock
- (Optional) Smart Cable Clip
- Kensington<sup>®</sup> Security Slot
- Padlock Loop

### Chassis Intrusion Switch

- Chassis intrusion switch
- No chassis intrusion switch

### Fingerprint Reader

- Touch style fingerprint reader on mouse
- No fingerprint reader

### BIOS Security

- Administrator password
- Power-on password
- Hard disk password
- Boot sequence control
- Boot without keyboard and mouse
- Self-healing BIOS (Level 2)
- Smart USB protection (allows keyboard / mouse only, blocks all storage devices)
- Individual USB port disablement

## MANAGEABILITY

## System Management

### System Management<sup>[1]</sup>

- Intel vPro Essentials
- Non-vPro

Notes:

1. Intel vPro offers a superset of DASH's defined capabilities.

# SERVICE

## Warranty

### Base Warranty<sup>[1]</sup>

- 1-year depot service
- 1-year limited onsite service
- 3-year limited onsite service
- No base warranty

Notes:

1. More information of warranty policy, please access https://pcsupport.lenovo.com/warranty

## **ENVIRONMENTAL**

## **Operating Environment**

Lenovo

### Temperature

- Operating: 5°C (41°F) to 35°C (95°F)
- Storage: -40°C (-40°F) to 60°C (140°F)

### Humidity

- Operating: 20% to 80%
- Storage: 10% to 90%

### Altitude

- Operating: 0 m (0 ft) to 3048 m (10,000 ft)
- Storage: 0 m (0 ft) to 12192 m (40,000 ft)

# CERTIFICATIONS

## **Green Certifications**

### Green Certifications

- (Optional) EPEAT<sup>™</sup> Gold
- (Optional) EPEAT Silver
- (Optional) ENERGY STAR<sup>®</sup> 8.0
- ErP Lot 3
- TCO Certified 9.0
- RoHS compliant

## **Other Certifications**

### **Other Certifications**

- (Optional) TÜV Rheinland<sup>®</sup> Low Noise
- (Optional) TÜV Rheinland Ultra Low Noise

### Mil-Spec Test

MIL-STD-810H military test passed (Low Pressure [Altitude], High Temperature, Low Temperature, Temperature Shock, Humidity, Sand and Dust, Vibration, Shock, Fungus, Solar Radiation, Contamination by Fluids, Salt Fog)

- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS," WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.



intel



intel



intel



intel.



intel



intel