

## Key **Features**

- AMD FreeSync™ Premium Pro for smooth and ultra-low-latency playback
- Mini-LED w/1152 zone display and full-array local dimming for peak visual performance
- VESA DisplayHDR 1400 for mind-blowing colors and contrasts
- Refresh rate overclockable to 200Hz for hyper-responsive visuals
- HDMI 2.1 Connection for console gaming compatibility



## Product **Description**

Experience a new level of visual performance and upgrade your gameplay on the XG341C-2K, featuring Mini LED technology that redefines expectations. Curved 34-inch UWQHD monitor delivers a highly immersive gaming experience teleporting you straight into the middle of the action. Engineered with quantum dot technology, the resolution renders every detail with incredible brightness on VESA certified DisplayHDR<sup>™</sup> 1400 panel. Rapid 200Hz (OC) refresh rate guarantees ultrasmooth gameplay, and a blazing fast 1ms (MPRT) response time to reduce in-game ghosting. Geared with AMD FreeSync<sup>™</sup> Premium Pro technology, you'll handle even the most intense action scenes.

Visit Us www.viewsonic.com

DICDI AV	https://www.view	INDUT CICALAL	51100t/X00410-21X
Display Size (in ):	24	INPUT SIGNAL	30 - 320KH-
Display Size (in.):	34	Frequency Vertical:	30 ~ 320KHz
Viewable Area (in.):	34	Frequency Vertical:	48 ~ 200Hz
Panel Type:	VA Technology	VIDEO INPUT	TMDS - HDMI (v2.1), PCI-E -
Resolution:	3440 x 1440	Digital Sync:	DisplayPort (v1.4), Micro-Packet -
Resolution Type:	UWQHD (UltraWide QHD)	ERGONOMICS	Type C
Static Contrast Ratio:  Dynamic Contrast Ratio:	3,000:1 (typ)	Height Adjust (mm):	120
Light Source:	120M:1 mini LED	Swivel:	50°
•	720; 1400 (w/ HDR+local dimming	Tilt (Forward/Back):	-5° / 23°
Brightness:	Peak (Min))	WEIGHT (IMPERIAL)	
Colors:	16.7M	Net (lbs):	25
Color Space Support:	8 bit true	Net Without Stand (lbs):	18.7
Aspect Ratio:	21:9	Gross (lbs):	40.3
Response Time (MPRT):	1ms	WEIGHT (METRIC)	
Viewing Angles:	178º horizontal, 178º vertical	Net (kg):	11.4
Backlight Life (Hours):	30000 Hrs (Min)	Net Without Stand (kg):	8.5
Curvature:	1500R	Gross (kg):	18.3
Refresh Rate (Hz):	200	DIMENSIONS (IMPERIAL) (W	/XHXD)
Adaptive Sync:	FreeSync Premium Pro	Packaging (in.):	37.9 x 20.4 x 13.8
Blue Light Filter:	Yes	Physical (in.):	31.8 x 18.94~23.67 x 15.1
Flicker-Free:	Yes	Physical Without Stand (in.):	31.8 x 14.3 x 5.2
Color Gamut:	DCI-P3: 97% coverage (Typ) NTSC: 99% size (Typ) sRGB: 140% size / 99% coverage (Typ)	DIMENSIONS (METRIC) (WX	HXD)
		Packaging (mm):	963 x 518 x 351
Pixel Size:	0.232 mm (H) x 0.232 mm (V)	Physical (mm):	807 x 481.11~601.11 x 384
Surface Treatment:	Anti-Glare, Hard Coating (3H)	Physical Without Stand (mm):	807 x 363 x 132
COMPATIBILITY	, and Grains, mana Graining (City)	GENERAL	
PC Resolution (max):	3440x1440	Regulations:	cTUVus, FCC-B, ICES003, CEC, MX- CoC, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, UKCA, CCC, China
Mac® Resolution (max):	3440x1440		
PC Operating System:	Windows 10/11 certified; macOS		RoHS, China Energy Label
	tested	PACKAGE CONTENTS:	XG341C-2K x1, 3-pin Plug (IEC C13, CEE22) x1, HDMI Cable (v2.1; Male- Male) x1, DisplayPort Cable (v1.4; Male-Male) x1, USB Type-C Gen2 Cable (Male-Male) x1, USB A/B Cable (v3.2; Male-Male) x1, Quick
Mac® Resolution (min):	3440x1440		
CONNECTOR			
USB 3.2 Type A Down Stream:	3		Start Guide x1
USB 3.2 Type B Up Stream:	1	Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
USB 3.2 Type C Up Stream; DisplayPort Alt mode :	1	Warranty:	*Warranty offered may differ from
3.5mm Audio Out:	1	wananty.	market to market
HDMI 2.1:	2		
DisplayPort:	1		
Power in:	3-pin Socket (IEC C14 / CEE22)		
AUDIO			
Internal Speakers:	5Watts x2		
POWER			
Eco Mode (Conserve):	45W		
Eco Mode (optimized):	53W		
Consumption (typical):	57W		
Consumption (max):	60W		
Voltage:	AC 100-240V		
Stand-by:	0.5W		
Power Supply:	Internal Power Supply		
ADDITIONAL HARDWARE	1		
Kensington Lock Slot:	Yes		
Cable Organization: CONTROLS	100		
Physical Controls:	Up, Right, Down, Left, Power		
On Screen Display:	Game Modes, Display, Input Select, ViewMode, Audio Adjust, Setup Menu		
OPERATING CONDITIONS	was rajust, octup monu		
Temperature:	32°F to 104°F (0°C to 40°C)		
Humidity (non-condensing):	20% to 90%		
WALL MOUNT			
VESA Compatible:	100 x 100 mm		

Copyright © ViewSonic Corporation 2000-2022. All rights reserved.