

**Philips Signage Solutions 37BDL3050S/00 Signage Display 94 cm (37") 700 cd/m<sup>2</sup> Full HD Black Built-in processor Android 8.0 24/7**



**Brand :** Philips

**Product family:** Signage Solutions

**Product code:** 37BDL3050S/00

**Product name :**  
37BDL3050S/00

Philips Signage Solutions 37BDL3050S/00. Display diagonal: 94 cm (37"), Display resolution: 1920 x 540 pixels, Display brightness: 700 cd/m<sup>2</sup>, HD type: Full HD. Operating hours (hours/days): 24/7. Operating system installed: Android 8.0. Product colour: Black

Display		Performance	
Display diagonal *	94 cm (37")	Operating hours (hours/days)	24/7
Display resolution *	1920 x 540 pixels	Mean time between failures (MTBF)	50000 h
Display brightness *	700 cd/m <sup>2</sup>	Power	
HD type *	Full HD	Power consumption (typical) *	70 W
Native aspect ratio	32:9	Power consumption (standby) *	0.5 W
Response time	8 ms	Input voltage	100/240 V
Contrast ratio (typical)	4000:1	AC input voltage	100/240 V
Viewing angle, horizontal	178°	AC input frequency	50/60 Hz
Viewing angle, vertical	178°	Computer system	
Pixel pitch	0.47 x 0.47 mm	Built-in processor *	✓
Ports & interfaces		Internal memory	2 GB
HDMI ports quantity *	2	On-board graphics card model	ARM Mali-G51
HDMI version	2.0	Internal storage capacity	8 GB
HDMI input ports quantity	1	Operating system installed	Android 8.0
HDMI output ports quantity	1	Weight & dimensions	
VGA (D-Sub) input ports	1	Display height	282.3 mm
USB port *	✓	Width	928.5 mm
USB ports quantity	1	Depth	48.7 mm
USB version	2.0	Height	282.3 mm
USB connector type	USB Type-A	Weight	7.76 kg
Ethernet LAN *	✓	Packaging content	
Ethernet LAN (RJ-45) ports	1	Remote control included	✓
PC Audio in	✓	Batteries included	✓
RS-232 interface	✓	Cables included	AC, HDMI, IR sensor, RS-232
Remote (IR) input	1	Mounting kit	✓
Remote (IR) output	1	Operational conditions	
Design		Operating temperature (T-T)	0 - 40 °C
Placement supported *	Indoor	Operating relative humidity (H-H)	20 - 80%
Orientation	Horizontal	Storage temperature (T-T)	-20 - 60 °C
Product colour *	Black	Storage relative humidity (H-H)	5 - 95%
VESA mounting *	✓	Certificates	
Panel mounting interface	400 x 200 mm	Certification	THIS FCC Class A CB
Performance			
On Screen Display (OSD) languages	Arabic, Simplified Chinese, Traditional Chinese, Czech, Danish, German, Dutch, English, Spanish, French, Italian, Japanese, Norwegian, Polish, Portuguese, Russian, Swedish, Turkish		



8712581799489

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 21-MAR-2023. Prints or copies of Information are only valid on the printed Publication date