

LG 43UH5J-H Signage Display Interactive flat panel 109.2 cm (43") Wi-Fi 500 cd/m 2 4K Ultra HD Black 24/7

Brand: LG Product code: 43UH5J-H


Product name: 43UH5J-H

43" (3840 2160) UHD, 500 cd/m², 200x200, 120W, 11.8Kg

LG 43UH5J-H. Product design: Interactive flat panel. Display diagonal: 109.2 cm (43"), Display resolution: 3840 x 2160 pixels, Display brightness: 500 cd/m^2 , HD type: 4K Ultra HD. Wi-Fi. Operating hours

(hours/days): 24/7. Product colour: Black







Display		Design	
Panel type	IPS	Panel mounting interface	200 x 200 mm
LED backlighting type Display diagonal * 109.2 cm (43") Display resolution * 3840 x 2160 pixels Display brightness * 500 cd/m² HD type * 4K Ultra HD Touchscreen * Native aspect ratio Response time Edge-LED 448") 109.2 cm (43") 440 x 2160 pixels 440 x 2160 pixels 500 cd/m² 450 Litra HD 500 cd/m² 460 Litra HD 500 cd/m² 470 Litra HD 500 cd/m² 8 ms	Edge-LED	Performance	
	Purpose * On Screen Display (OSD) Operating hours (hours/days) HDCP International Protection (IP) code HDCP version	Universal ✓ 24/7 ✓ IP5X 1.4	
Contrast ratio (typical)	1200:1	Power	
Contrast ratio (dynamic) Viewing angle, horizontal Viewing angle, vertical Display number of colours Panel life Native refresh rate Haze rate Ports & interfaces HDMI ports quantity * DVI port * DisplayPorts quantity * USB ports quantity USB version	dynamic) 1000000:1 horizontal 178° vertical 178° r of colours 1.07 billion colours 50000 h rate 60 Hz 25% faces antity * 3 Juantity * 1	Power consumption (typical) * Power consumption (standby) * Power consumption (off) Power consumption (max) Energy efficiency class (SDR) Energy consumption (SDR) per 100 hours AC input voltage AC input frequency Energy efficiency scale Weight & dimensions Width (with stand) Depth (with stand) Height (with stand) Weight (with stand)	80 W 0.5 W 0.5 W 120 W G 68 kWh 100 - 240 V 50 - 60 Hz A to G 962.5 mm 290 mm 613.1 mm 11.8 kg
Ethernet LAN * Wi-Fi *	1	Packaging data	11.0 Ng
DC-in jack	· •	Package width	1060 mm
Audio		Package depth	152 mm
Built-in speaker(s) *	✓	Package height	660 mm
Design		Package weight	13.7 kg
Product design * Placement supported * Product colour * Screen shape	Interactive flat panel Indoor Black Flat	Operational conditions Operating temperature (T-T) Operating relative humidity (H-H)	0 - 40 °C 10 - 80%

Design	
VESA mounting *	✓





8806091657053

0195174033777



195174033777

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.