

Fujitsu PRIMERGY RX2540 M6 server Rack (2U) Intel Xeon Silver 4309Y 2.8 GHz 16 GB DDR4-SDRAM 900 W

Brand : Fujitsu **Product family:** PRIMERGY **Product code:** VFY:R2546SC300IN

Product name: RX2540 M6

- No OS
- Intel Xeon Silver 4309Y (12MB Cache, 2.8GHz)
- 16GB (3200MHz) DDR4-SDRAM (1 x 16)

Intel Xeon Silver 4309Y (12MB Cache, 2.8GHz), 16GB DDR4-SDRAM (3200MHz), 900W, No OS Fujitsu PRIMERGY RX2540 M6. Processor family: Intel Xeon Silver, Processor frequency: 2.8 GHz, Processor model: 4309Y. Internal memory: 16 GB, Internal memory type: DDR4-SDRAM, Memory layout (slots x size): 1 x 16 GB. Power supply: 900 W. Chassis type: Rack (2U)





Processor manufacturer * Intel Ethernet LAN (RJ-45) ports * 1 Processor family * Intel Xeon Silver USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity ports quantity
Processor family * Intel Xeon Silver 3rd Generation Intel® Xeon® Scalable VGA (D-Sub) ports quantity 1 Processor model * 4309Y Processor frequency * 2.8 GHz Chassis type * Rack (2U) Rack mounting Verocessor cores 8 Trusted Platform Module (TPM) Version Processor cache 12 MB Trusted Platform Module (TPM) version Version VGA (D-Sub) ports quantity 1 USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity 1 Design Chassis type * Rack (2U) Rack mounting Version Versio
Processor generation Scalable Processor model * 4309Y Processor frequency * Processor boost frequency Efficient-core base frequency Performance-core base frequency Processor cores 8 Trusted Platform Module (TPM) Processor cache 12 MB Trusted Platform Module (TPM) Version Software Internal memory * 16 GB DDR4-SDRAM Ports quantity VGA (D-Sub) ports quantity 1 Pesign Chassis type * Rack (2U) Rack mounting Trusted Platform Module (TPM) Version Software Operating system installed * X Operating system installed * X And Design Chassis type * Rack (2U) And Chassis type * Rack mounting And Chassis type * Rack (2U) And Chassis type * Rack m
Processor generation Scalable VGA (D-Sub) ports quantity Processor model * 4309Y Processor frequency * 2.8 GHz Processor boost frequency 3.6 GHz Performance-core base frequency Performance-core base frequency Performance-core base frequency Processor cores 8 Trusted Platform Module (TPM) Processor cache 12 MB Trusted Platform Module (TPM) Version Memory Internal memory * 16 GB DDR4-SDRAM VGA (D-Sub) ports quantity 1 Pasign Chassis type * Rack (2U) Processor type * Rack mounting Trusted Platform Module (TPM) Version Software Operating system installed * VGA (D-Sub) ports quantity 1 Posign Chassis type * Rack (2U) Value Rack mounting V Sack mounting V Performance Processor cores Software Operating system installed *
Processor frequency * 2.8 GHz Processor boost frequency 3.6 GHz Efficient-core base frequency 0.0028 GHz Performance-core base frequency 2.8 GHz Performance-core base frequency 2.8 GHz Processor cores 8 Trusted Platform Module (TPM) ✓ Processor cache 12 MB Memory Internal memory * 16 GB Internal memory type * DDR4-SDRAM
Processor boost frequency Processor boost frequency 3.6 GHz Rack mounting Performance-core base frequency Processor cores 8 Trusted Platform Module (TPM) Processor cache 12 MB Trusted Platform Module (TPM) Version Memory Internal memory * 16 GB DDR4-SDRAM Chassis type * Rack (2U) Pack mounting Trusted Platform Module (TPM) Version Software Operating system installed * Note That is the pack of the
Processor boost frequency Efficient-core base frequency Performance-core base frequency Performance-core base frequency Processor cores 8 Trusted Platform Module (TPM) Processor cache 12 MB Trusted Platform Module (TPM) version Memory Internal memory * 16 GB DDR4-SDRAM Rack mounting Parformance Trusted Platform Module (TPM) version Software Operating system installed * ** ** ** ** ** ** ** ** **
Efficient-core base frequency 0.0028 GHz Performance-core base frequency 2.8 GHz Processor cores 8 Trusted Platform Module (TPM) ✓ Processor cache 12 MB Trusted Platform Module (TPM) version 2.0 Memory Internal memory * 16 GB Internal memory type * DDR4-SDRAM Operating system installed * ★
Processor cores 8 Trusted Platform Module (TPM) Processor cache 12 MB Trusted Platform Module (TPM) version Memory Internal memory * 16 GB Internal memory type * DDR4-SDRAM DDR4-SDRAM Trusted Platform Module (TPM) 2.0 Software Operating system installed * X
Processor cache 12 MB Trusted Platform Module (TPM) version 2.0 Memory Internal memory * 16 GB Internal memory type * DDR4-SDRAM DDR4-SDRAM Trusted Platform Module (TPM) version 2.0 Version Operating system installed *
version Version Software Internal memory * DDR4-SDRAM Version Version Operating system installed * X
Internal memory * 16 GB Internal memory type * DDR4-SDRAM Software Operating system installed * X
Internal memory * 16 GB Internal memory type * DDR4-SDRAM Operating system installed * X
internal memory type * DDN4-3DNAM * 3 2
Windows Comen 2010 Debrander
Memory slots 32x DIMM Windows Server 2019 Datacenter Windows Server 2019 Standard
Windows Server 2019 Essentials
Memory clock speed 3200 MHz Hyper-V Server 2016 Windows Server 2016 Datacenter Windows
Memory layout (slots x size) 1 x 16 GB Compatible operating systems * Server 2016 Standard Windows
Maximum internal memory * 12 TB Server 2016 Essentials Windows
Storage Storag
Number of HDDs supported 16 Enterprise Linux 7 Oracle® Linux 7
Supported HDD sizes 2.5" Power
RAID support * Power supply * 900 W
Optical drive type * Weight & dimensions
Width 482.5 mm
Depth 800 mm
Height 86.9 mm
Weight 32 kg



4065221858928

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.