

StarTech.com 2-Port USB 3.0 Extender over OM3 Multimode Fiber - LC/LC - 2x 5Gbps USB-A Hub - 350m (1150ft) Range - Durable USB Fiber Optic Extender - Optical USB Extender

Brand : StarTech.com

Product code: F35023-USB-EXTENDER

Product name : 2-Port USB 3.0 Extender over OM3 Multimode Fiber - LC/LC - 2x 5Gbps USB-A Hub - 350m (1150ft) Range - Durable USB Fiber Optic Extender - Optical USB Extender

StarTech.com 2-Port USB 3.0 Extender over OM3 Multimode Fiber - LC/LC - 2x 5Gbps USB-A Hub - 350m (1150ft) Range - Durable USB Fiber Optic Extender - Optical USB Extender (F35023-USB-EXTENDER)
 StarTech.com 2-Port USB 3.0 Extender over OM3 Multimode Fiber - LC/LC - 2x 5Gbps USB-A Hub - 350m (1150ft) Range - Durable USB Fiber Optic Extender - Optical USB Extender. Width: 93 mm, Depth: 57 mm, Height: 28 mm. Cables included: USB Type-A to Micro-USB Type-B. Power source type: DC, Power consumption (typical): 15 W, Input voltage: 100 - 240 V. Master (outer) case width: 323 mm, Master (outer) case length: 370 mm, Master (outer) case height: 282 mm



Technical details		Operational conditions	
Type *	Console transmitter & receiver	Storage temperature (T-T)	-20 - 70 °C
Data transfer rate	5000 Mbit/s	Operating relative humidity (H-H)	20 - 80%
Maximum transfer distance	350 m	Storage relative humidity (H-H)	10 - 90%
Housing material	Aluminium	Packaging content	
LED indicators	✓	Cables included	USB Type-A to Micro-USB Type-B
Sustainability compliance	✓	Quick start guide	✓
Sustainability certificates	CE	AC adapter included	✓
Certification	FCC	Power	
Ports & interfaces		Power source type	DC
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	2	Power consumption (typical)	15 W
DC-in jack	✓	Input voltage	100 - 240 V
Weight & dimensions		Input current	0.48 A
Width	93 mm	Output voltage	5 V
Depth	57 mm	Output current	3 A
Height	28 mm	Power plug type	Type H
Weight	271 g	Logistics data	
Package width	115 mm	Master (outer) case width	323 mm
Package depth	155 mm	Master (outer) case length	370 mm
Package height	125 mm	Master (outer) case height	282 mm
Package weight	700 g	Products per master (outer) case	12 pc(s)
Operational conditions			
Operating temperature (T-T)	0 - 50 °C		



0065030897389



065030897389

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.