Viewsonic TD2465 Signage Display Interactive flat panel 61 cm (24") LED 250 cd/m² Full HD Black Touchscreen

Brand : Viewsonic Product code: TD2465

Product name: TD2465

- Touch function for wet hands and multiple types of glove
- Pen clicks & Palm rejection technology
- 4-sides frameless design and optional stand for flexibility
- Friendly touch mode setting
- Intuitive touch OSD with ViewSonic Touch Controller

24", 1920 x 1080p, FHD, 3000:1, LED, 250cd/m2, 16:9, 60Hz, HDMI 1.4, DisplayPort, USB 3.2 Type-A x2, USB 3.2 Type-B, VGA

Viewsonic TD2465. Product design: Interactive flat panel. Display diagonal: 61 cm (24"), Display technology: LED, Display resolution: 1920×1080 pixels, Display brightness: 250 cd/m^2 , HD type: Full HD, Touchscreen. Product colour: Black





Diantar		Danima	
Display		Design	
LED backlighting type Display diagonal * 61 cm (24") Display technology * LED Display resolution * 1920 x 1080 pixels Display brightness * 250 cd/m²	61 cm (24") LED	Product design * Product colour * VESA mounting * Panel mounting interface	Interactive flat panel Black ✓ 100 x 100 mm
	250 cd/m²	Performance	
HD type *	Full HD	Purpose *	Commercial
Touchscreen *	ive aspect ratio 16:9 sponse time 7 ms	Power	
Response time Contrast ratio (typical)		Power consumption (typical) * Power consumption (standby) *	24 W 0.5 W
Contrast ratio (dynamic)	20000000:1	AC input voltage	100 - 240 V
Viewing angle, horizontal	178°	Computer system	
Viewing angle, vertical Maximum frame rate	178° 60 fps	Built-in processor *	×
Panel life	30000 h	Weight & dimensions	
Native refresh rate Surface hardness RGB colour space	60 Hz 7H sRGB	Width Depth Height	550 mm 326 mm 49 mm
Ports & interfaces		Weight	4.7 kg
HDMI ports quantity * HDMI version DisplayPorts quantity * USB port *	1 1.4 1	Width (with stand) Depth (with stand) Height (with stand) Weight (with stand)	550 mm 401 mm 198 mm 5.7 kg
USB ports quantity	3	Packaging data	
USB version 3.2 Gen 1 (3.1 Gen 1) USB connector type USB Type-A, USB Type-B Ethernet LAN * Wi-Fi *	Package width Package depth Package height Package weight	647 mm 426 mm 138 mm 7.2 kg	
Audio (L/R) in	1	Packaging content	
Audio (L/R) out Audio	1	Tilt angle Tilt adjustment	20° ✓
Built-in speaker(s) *	✓	Operational conditions	
Number of built-in speakers RMS rated power	2 4 W	Operating temperature (T-T) Operating relative humidity (H-H)	0 - 40 °C 20 - 90%

