PHILIPS

Philips Momentum 32M1C5500VL/00 LED display 80 cm (31.5") 2560 x 1440 pixels Quad HD LCD Black

Product name: 32M1C5500VL/00

Evnia 5000 Quad HD gaming monitor

Philips Momentum 32M1C5500VL/00 LED display 80 cm (31.5") 2560 x 1440 pixels Quad HD LCD Black:

This Philips gaming monitor delivers crystal-clear visuals and smooth gameplay. Sync technology, 165 Hz refresh rate with HDR create a lifelike experience. The slim-frame display with Ultra Wide-Color enhances visual immersion.

Philips Momentum 32M1C5500VL/00. Display diagonal: 80 cm (31.5"), Display resolution: 2560 x 1440 pixels, HD type: Quad HD, Display technology: LCD, Response time: 4 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. VESA mounting. Product colour: Black









Display		Ergonomics	
Display diagonal *	80 cm (31.5")	Cable lock slot *	✓
Display resolution *	2560 x 1440 pixels	Cable lock slot type	Kensington
HD type *	Quad HD	Height adjustment *	×
Native aspect ratio *	16:9	Tilt angle range	-5 - 20°
Display technology *	LCD		Simplified Chinese, Traditional
Panel type *	VA		Chinese, Czech, German, Dutch, English, Spanish, Finnish, French,
Backlight type	W-LED	On Screen Display (OSD) languages	Greek, Hungarian, Italian, Japanese,
Touchscreen *	×		Korean, Polish, Portuguese, Russian,
Display brightness (typical)	250 cd/m ²		Swedish, Turkish, Ukrainian
Response time	4 ms	Plug and Play	✓
Anti-glare screen	✓	LED indicators	Operation, Stand-by
Screen shape *	Curved	Tilt adjustment	✓
Screen curvature rating	1500R	Power	
Contrast ratio (typical) *	3000:1	Energy efficiency class (SDR) *	F
Dynamic contrast ratio marketing name	Mega Infinity DCR	Energy efficiency class (HDR) *	G
Maximum refresh rate *	144 Hz	Energy consumption (SDR) per 1000 hours *	32 kWh
Viewing angle, horizontal	178°	Energy consumption (HDR) per	57.134
Viewing angle, vertical	178°	1000 hours *	57 kWh
Display number of colours *	16.7 million colours	Power consumption (typical) *	45.1 W
Response time (fast)	1 ms	Power consumption (standby) *	0.5 W
Pixel pitch	0.2724 x 0.2724 mm	Power consumption (off)	0.3 W
Pixel density	93.24 ppi	AC input voltage	100 - 240 V
Viewable size, horizontal	69.7 cm	AC input frequency	50 - 60 Hz
Viewable size, vertical	39.2 cm	Power supply type	Internal
Display diagonal (metric)	80 cm	Energy efficiency scale	A to G
High Dynamic Range (HDR) technology	High Dynamic Range 10 (HDR10)	Operational conditions	
DDC/CI	✓	Operating temperature (T-T)	0 - 40 °C
Haze rate	25%	Storage temperature (T-T)	-20 - 60 °C
Surface hardness	3H	Operating relative humidity (H-H)	20 - 80%
Colour depth	8 bit	Operating altitude	0 - 3658 m

Display		Operational conditions	
RGB colour space	sRGB	Non-operating altitude	3658 - 12192 m
sRGB coverage (typical) NTSC coverage (typical) Display sRGB	121.6% 102.1%	Packaging content Stand included	√
Performance	•	Cables included Manual	HDMI, DisplayPort, AC ✓
NVIDIA G-SYNC * AMD FreeSync * VESA Adaptive Sync support Component video sync Flicker-free technology Low Blue Light technology Low input lag Compatible operating systems	X X Separate sync Mac OS X Windows 11 / 10 / 8.1 / 8 / 7	Weight & dimensions Width (with stand) Depth (with stand) Height (with stand) Weight (with stand) Width (without stand) Depth (without stand) Height (without stand) Weight (without stand)	709 mm 239 mm 527 mm 7.83 kg 709 mm 95 mm 423 mm 6.37 kg
Multimedia Built-in speaker(s) * Built-in camera *	×	Packaging data Package width	782 mm
Design Market positioning *	Gaming	Package depth Package height Package weight	227 mm 523 mm 10.4 kg
Product colour * Feet colour	Black Black	Sustainability	
Ports & interfaces Built-in USB hub *	Sustainability compliance Sustainability certificates Doesn't contain European Product Registry for Energy Labelling (EPREL) code	RoHS Mercury, PVC/BFR 1302102	
		Other features Exterior finish type	Textured
Audio output HDCP HDCP version	1.4/2.2	Picture enhancement Recyclable packaging material Regulatory Approvals	SmartImage game 100% CB; CE Mark; FCC Class B; ICES-003; CU-EAC; EAEU ROHS;
Ergonomics VESA mounting * Panel mounting interface	√ 100 x 100 mm	EasyRead mode LowBlue mode Mean time between failures (MTBF)	TUV/ISO9241-307; TUV-BAUART



8712581795962

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.