



## Manhattan USB-C to Micro-USB Cable, 1m, Male to Male, Black, 480 Mbps (USB 2.0), Tangle Resistant Curly Design, Angled Connectors, Ideal for Charging Cabinets/Carts, Hi-Speed USB, Lifetime Warranty, Polybag



**Brand :** Manhattan

**Product code:** 356244

**Product name :** USB-C to Micro-USB Cable, 1m, Male to Male, Black, 480 Mbps (USB 2.0), Tangle Resistant Curly Design, Angled Connectors, Ideal for Charging Cabinets/Carts, Hi-Speed USB, Lifetime Warranty, Polybag

USB-C to Micro-USB Cable, 1m, Male to Male, Black, 480 Mbps (USB 2.0), Tangle Resistant Curly Design, Angled Connectors, Ideal for Charging Cabinets/Carts, Hi-Speed USB, Lifetime Warranty, Polybag

[Manhattan USB-C to Micro-USB Cable, 1m, Male to Male, Black, 480 Mbps \(USB 2.0\), Tangle Resistant Curly Design, Angled Connectors, Ideal for Charging Cabinets/Carts, Hi-Speed USB, Lifetime Warranty, Polybag:](#)

Coiled USB cable - USB C to Micro-B cable - the ideal charging cord to keep car chargers, charging cabinets, and charging carts clutter-free  
Make your charging cable management clutter-free with the coiled, tangle-resistant USB-C to Micro-USB Charging Cable from Manhattan. It flexibly stretches to just the right length you need without tangles and retracts back to a compact format for easy handling and storage. For even more convenience, both plugs are 90° angled for easy connection in places like tight corners or hard-to-reach ports. The reversible USB-C connector will always fit, no matter which way you insert the cable.

Features		Features	
Cable length *	1 m	Certification	CE RoHS UL 20233 REACH
Connector 1 *	USB C	<b>Weight &amp; dimensions</b>	
Connector 2 *	Micro-USB B	Cable diameter	3.5 mm
Connector 1 gender *	Male	Weight	22 g
Connector 2 gender *	Male	<b>Packaging data</b>	
Connector 1 form factor	Angled	Quantity per pack *	1 pc(s)
Connector 2 form factor	Angled	Package weight	24 g
AWG wire size	24/30	Package type	Polybag
Connector contacts plating	Nickel	<b>Operational conditions</b>	
Cable jacket material	Polyvinyl chloride (PVC)	Operating temperature (T-T)	0 - 45 °C
Product colour *	Black	Storage temperature (T-T)	-10 - 70 °C



0766623356244



766623356244

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.