PHILIPS

Philips 6000 series 45B1U6900C 113 cm (44.5") 5120 x 1440 pixels UltraWide Dual Quad HD LED Black

Brand : Philips Product family: 6000 series **Product code:** 45B1U6900C/00

Product name: 45B1U6900C

32:9 SuperWide curved monitor with USB-C

Philips 6000 series 45B1U6900C 113 cm (44.5") 5120 x 1440 pixels UltraWide Dual Quad HD LED Black:

This Philips USB-C multi-purpose monitor offers clutter-free setup. With a single cable you can view smooth, high-resolution video, transfer data and charge your laptop. The headphone holder brings cable management to the next level.

Philips 6000 series 45B1U6900C. Display diagonal: 113 cm (44.5"), Display resolution: 5120×1440 pixels, HD type: UltraWide Dual Quad HD, Display technology: LED, Response time: 4 ms, Native aspect ratio: 32:9, Viewing angle, horizontal: 178° , Viewing angle, vertical: 178° . Built-in speaker(s). Built-in USB hub, USB hub version: 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: Black







Display		Ports & interfaces	
Display diagonal *	113 cm (44.5")	HDCP version	1.4/2.2
Display resolution *	5120 x 1440 pixels	AC (power) in	1
HD type *	UltraWide Dual Quad HD	Network	
Native aspect ratio *	32:9		,
Display technology *	LED	Ethernet LAN	✓
Panel type *	VA	Ergonomics	
Backlight type	W-LED	VESA mounting *	✓
Touchscreen *	×	Panel mounting interface	100 x 100 mm
Display brightness (typical)	450 cd/m²	Cable lock slot *	✓
Response time	4 ms	Cable lock slot type	Kensington
Anti-glare screen	✓	Height adjustment *	✓
Screen shape *	Curved	Height adjustment	15 cm
Screen curvature rating	1500R	Swivelling	✓
Contrast ratio (typical) *	3000:1	Swivel angle range	-45 - 45°
Contrast ratio (dynamic)	80000000:1	Tilt angle range	-5 - 15°
Dynamic contrast ratio marketing	SmartContrast	Picture-in-Picture	✓
name		On Screen Display (OSD)	✓
Maximum refresh rate *	75 Hz		Simplified Chinese, Traditional
Viewing angle, horizontal	178°		Chinese, Czech, German, Dutch,
Viewing angle, vertical	178°	On Screen Display (OSD) languages	English, Spanish, Finnish, French, Greek, Hungarian, Italian, Japanese,
Display number of colours *	16.7 million colours		Korean, Polish, Portuguese, Russian,
Pixel pitch	0.2124 x 0.2124 mm		Swedish, Turkish, Ukrainian
Pixel density	120 ppi	Number of OSD languages	21
Horizontal scan range	30 - 114 kHz	Plug and Play	1
Vertical scan range	48 - 75 Hz	LED indicators	Operation, Stand-by
Viewable size, horizontal	108.7 cm	Tilt adjustment	1
Viewable size, vertical	30.6 cm	Power	
Display diagonal (metric)	113 cm	Energy efficiency class (SDR) *	G
High Dynamic Range (HDR) supported	✓	Power consumption (typical) *	46.3 W

lips by Namic Range (HDR) DisplayHDR 400 Power consumption (standby)				
technology Power consumption (PowerSave) 3.5. W DDCCI 4 AC input virtiequency 30.5 00 Hz Haze rate 25% AC input virtiequency 50.60 Hz Solar depth 8 bit Power's supply type internal KGBG coverage (typical) 10% Solar depth 2-0.60 °C NTSC coverage (typical) 10% Solar depth 2-0.60 °C Performanc Operating relative humidity (H-H) 0.40% VESA Adaptive Sync support V Operating a latitude 0.2658 n Component video sync support V Non operating a latitude 0.1219 cm Component video sync support Maccess (Mace) Packaging content Filkes Fries technology V Packaging content VERS Adaptive Sync support V Cables included V VERS Adaptive Sync support V Packaging content V VERS Adaptive Sync support V Cables included V Use Internal Sync support V Cables included V Welphan Sync support	Display		Power	
Colour depth 9 bit Operating temperature (T-T) 0-40 °C NTSC coverage (typical) 123% Operating temperature (T-T) -20 - 60 °C Objarly sRGB 20 - 60 °C Component (T-T) -20 - 60 °C VESA Adaptive Synt support V Operating altitude 0 - 2658 m VESA Adaptive Synt support V Non-operating altitude 0 - 2558 m Component video synt V Shading content V HBR3 support Mac OS X, Windows 11/10/8.1/8 Stand included HDM, DisplayPort, USB Type-C, AC Multimedia Mac OS X, Windows 11/10/8.1/8 Stand included HDM, DisplayPort, USB Type-C, AC Bull-in speaker(\$)* Mac OS X, Windows 11/10/8.1/8 Meight & dimensions Marc Color of Smart Control Bull-in speaker(\$)* Windows 11/10/8.1/8 Weight & dimensions Marc Color of Smart Control Bull-in camera* Mack Stand (with stand) 1085 mm 1085 mm Amaret of speakers Bull-in camera* Window (with stand) 11.8 m 12.8 m Postage Black Widely (with stand) 18.5 m 18.5 m	technology DDC/CI Haze rate	√ 25%	Power consumption (PowerSave) AC input voltage AC input frequency	36.5 W 100 - 240 V 50 - 60 Hz
Skild Everage (typical) 12% O-40 °C Display 8KBB V Storage temperature (T-T) -20 · 60 °C Performance Operating statutude 0 - 3658 m VESA Adaptive Sync support V Operating altituude 0 - 2192 m Component Video Sync Separate Sync Packaging content V Filker-free technology V Stand included V WIRR3 support V Stand included V Multimedia Mac OS X, Windows 11/10/81/8 Eables included MIDMID (IsplayPort, USB Type-C, AC Manual Multimedia Welght & dimensions SmartControl Built-in speaker(s)* Welght & dimensions SmartControl Built-in camera* X Weight & dimensions SmartControl Built-in speaker(s)* Weight (with stand) 1085 mm Design Business Weight (with stand) 128 mm Market positioning* Business Weight (with stand) 12.8 kg Product colour* Black Weight (with stand) 12.8 kg Built-in UsB hub* <td< td=""><td>Colour depth</td><td>8 bit</td><td></td><td></td></td<>	Colour depth	8 bit		
	sRGB coverage (typical)	123%	•	
Performance	NTSC coverage (typical)	107%		
Verbandance Component video sync Separate sync Quenating altitude 0 - 3658 m Occomponent video sync Separate sync Packaging content Verbanding of the processor of the pro	Display sRGB	✓	• •	
VESA Adaptive Sync support Separate sync Packaging content Flicker-free technology 4 Stand included 4 HBR3 support 4 Cables included HDMI, DisplayPort, USB Type-C, NC Compatible operating systems Mac OS X, Windows 11/10/8.1/8 Cables included HDMI, DisplayPort, USB Type-C, NC Compatible operating systems Manual SmartControl Built-in speaker(s)* 4 Weight & dimensions SmartControl Built-in speaker(s)* 4 Weight & dimensions 1085 mm Built-in speaker(s)* 4 Weight (with stand) 1085 mm Built-in speaker(s)* 2 Depth (with stand) 12.8 kg Number of speakers 2 Depth (with stand) 12.8 kg Market positioning* Black Width (with stand) 12.8 kg Fround bezil colour* Black Width (without stand) 15.8 cm From bezel colour Black Weight (with stand) 15.8 cm From tezel colour Black Height (without stand) 15.8 cm From tezel colour Black Peckaging 15.8 cm <	Performance			
Component video sync Speaker synch Packaging content Flicker free betchnology 4 Stadl included #MDMI (INDIR) (VESA Adaptive Sync support	√		
	Component video sync	Separate sync		0 12132 III
Cables included HDMI, DisplayPort, USB Type-C, AC Compatible operating systems Mac OS X, Windows 11/10/8.1/8 Manual	Flicker-free technology	✓		
Multimedia Manual SomtControl Built-in speaker(s)* Veight & dimensions Built-in speaker(s)* Weight & dimensions Built-in camera* Width (with stand) 1085 mm Number of speakers 2 Width (with stand) 28 mm Design Height (with stand) 515 mm Market positioning* Business Weight (with stand) 12.8 kg Product colour* Black Width (without stand) 15.8 cm Front bezel colour Black Height (without stand) 3.5 cm Feet colour Black Height (without stand) 3.5 cm Forts & interfaces Package width 180 mm Built-in USB hub* / Package width 180 mm USB upstream port type USB Type-8, USB Type-1 Package depth 535 mm Number of USB Type-8 bustream ports 2 Package weight 171 kg Number of USB Type-8 bustream ports quantity 2 Sustainability certificates ENERCy STAR, RoHs, TCO USB Type-C UsplayPort Alternate / Revisplay for taken	HBR3 support	✓		
Multi-in speaker(s)* Vegith & dimensions Built-in camera* X Number of speakers 2 Design Depth (with stand) 238 mm Market positioning* Business Welght (with stand) 12.8 kg Product colour* Black Welght (with stand) 12.8 kg Frameless design √ Depth (without stand) 15.8 cm From tester colour Black Height (without stand) 15.8 cm From tester colour Black Height (without stand) 9.75 kg Feet colour Black Height (without stand) 9.75 kg Feet colour Black Height (without stand) 9.75 kg Forts & interfaces Package width (without stand) 9.75 kg Built-in QSB hub* 3.2 Gen 1 (3.1 Gen 1) Package depth 235 mm USB tub version 3.2 Gen 1 (3.1 Gen 1) Package wight 17.1 kg USB tub version 3.2 Gen 1 (3.1 Gen 1) Sustainability certificates ENTITY (a) kg USB tub version 3.2 Gen 1 (3.1 Gen 1) Sustainability certificates <t< td=""><td>Compatible operating systems</td><td>Mac OS X, Windows 11/10/8.1/8</td><td></td><td></td></t<>	Compatible operating systems	Mac OS X, Windows 11/10/8.1/8		
Bullt-in camera* X Number of speakers 2 Design Upth (with stand) 1.085 mm Design Business Depth (with stand) 2.15 mm Market positioning* Business Weight (with stand) 12.8 kg Product colour* Black Width (without stand) 12.8 kg From thezel colour Black Weight (without stand) 13.8 cm Front bezel colour Black Height (without stand) 33.7 cm Feet colour Black Height (without stand) 33.7 cm Fort S& interfaces Packaging data Built-in USB hub* ✓ Packaging data USB upsteam port type USB Type-B. USB Type-C. USB Type-C	Multimedia			
Built-in camera* X Weight & dimensions Number of speakers 2 Width (with stand) 1085 mm Design Building in the product colour Building in the product colour Black Weight (with stand) 115. mm Frameless design Joseph (with cut stand) 12.8 kg Front bezel colour Black Height (without stand) 15.8 cm Feet colour Black Height (without stand) 15.8 cm Feet colour Black Height (without stand) 15.8 cm Feet colour Black Height (without stand) 15.8 cm Ports interfaces Percentage Percentage Posts interfaces Percentage Percentage Built-in USB hub 4 Percentage with (without stand) 1180 mm USB trype- to work in terface 9 Percentage with (without stand) 1180 mm USB trype with the product of t	Built-in speaker(s) *	✓		SINGITCONTION
Number of speakers 2 Width (with stand) 1085 mm Design Busines Height (with stand) 15 mm Market positioning ** Business Weight (with stand) 12.8 kg Product colour * Black Width (without stand) 15.8 cm From bezel colour Black Height (without stand) 15.8 cm From bezel colour Black Height (without stand) 33.7 cm Feet colour Black Height (without stand) 33.7 cm Feet colour Black Pockagin data Feet colour Package width 1180 mm Number of USB hub ** 7 Package width 1180 mm USB hub version 3.2 Gen 1 (3.1 Gen 1) Package width 1180 mm USB upstream port type 12.8 Type-B. USB Type-B. USB Type-B. USB Type-C. USB Type-B. USB Type-C. USB Type-B. USB Type-B. USB Type-C. USB Type-B. USB Type-C.			•	
Design Height (with stand) 515 mm Market positioning ** Business Weight (with stand) 2.8 kg Product colour ** Black Weight (with stand) 12.8 kg From to bezel colour Black Depth (without stand) 15.8 cm Front bezel colour Black Depth (without stand) 37.7 cm Feet colour Black Weight (without stand) 37.7 cm Feet colour Black Weight (without stand) 37.7 cm Feet colour Black Peakaging data 180 mm Ports & interfaces Fackage width 1180 mm USB upstream port type USB Type-A sage height 535 mm USB upstream port type USB Type-B, USB Type-C Package height 17.1 kg Number of USB Type-C upstream ports 1 Sustainability certificates ENERGY STAR, RoHS, TCO metros quantity USB Type-C downstream ports 2 Recycling data Feech developed plastic 85% USB Type-C downstream ports 4 Post-consumer recycled plastic 85% Post-consumer recycled plastic 85%	Number of speakers	2	Width (with stand)	1085 mm
Market positioning	Design			
Product colour** Black Width (without stand) 10.8.5 cm Frameless design	-	Rusinass	-	
Frameless design			•	-
Front bezel colour Black Height (without stand) 13-3 cm Feet colour Black Height (without stand) 33.7 cm Feet colour Black Weight (without stand) 33.7 cm Ports & interfaces Package depth 35.8 cm Built-in USB hub ** ✓ Package width 1180 mm USB hub version 3.2 Gen 1 (3.1 Gen 1) Package height 235 mm USB upstream port type USB Type-B, USB Type-C Package height 235 mm Number of USB Type-B upstream ports 2 Package weight 17.1 kg Number of USB Type-C upstream ports quantity 1 Sustainability Emercy STAR, RoHS, TCO Mercury, PVC/BFR USB Type-A downstream ports quantity 4 Recycling data *** *** USB Type-C downstream ports quantity 4 Recycling data *** *** USB Type-C DisplayPort Alternate Mode ✓ Chef features *** ** USB Power Delivery ✓ Exterior finish type Textured ** ** USB Power Delivery up to <				
Feet colour	_		•	
Ports & interfaces Packaging data Built-in USB hub* / Package width 1180 mm USB hub version 3.2 Gen 1 (3.1 Gen 1) Package depth 535 mm USB upstream port type USB Type-B, USB Type-C Package height 235 mm Number of USB Type-B upstream ports 2 Package weight 17.1 kg Number of USB Type-B upstream ports quantity 1 Sustainability certificates ENERGY STAR, RoHS, TCO Mercury, PVC/BFR USB Type-A downstream ports quantity 4 Recycling data ENERGY STAR, RoHS, TCO Mercury, PVC/BFR USB Type-C DisplayPort Alternate quantity 4 Recycling data 55% USB Type-C DisplayPort Alternate quantity 4 Recycling data 55% USB Pype-C DisplayPort Alternate quantity 4 Exterior finish type 55% USB Pype-C DisplayPort Alternate quantity 4 Exterior finish type Textured USB Pype-C DisplayPort Alternate quantity 4 Recyclable packaging material 100% HDMI ** 100 W Recyclable packaging material 100% HDMI version 1.4 CU-EA			• •	
Built-in USB hub*	Ports & interfaces			3.73 kg
USB hub version 3.2 Gen 1 (3.1 Gen 1) Package depth 535 mm USB upstream port type USB Type-B, USB Type-C Package height 235 mm Number of upstream ports 2 Package weight 17.1 kg Number of USB Type-B upstream ports 2 Package weight 17.1 kg Number of USB Type-C upstream ports quantity Push 2 Package weight 2 P		,		
USB upstream port type Number of upstream ports 1 Package height Package weight 17.1 kg Number of USB Type-B upstream ports quantity Number of USB Type-B upstream ports quantity Number of USB Type-C upstream ports quantity Number of USB Type-C upstream ports quantity Number of USB Type-C upstream ports quantity Number of USB Type-C upstream port quantity			Package width	1180 mm
Number of USB Type-B upstream ports 1 Package weight 17.1 kg Number of USB Type-C upstream ports quantity 2 Sustainability certificates 2 ENERGY STAR, ROHS, TCO 2 Doesn't contain 2 Mercury, PVC/BFR USB Type-A downstream ports 2 Post-C downstream ports quantity 3 Post-C downstream ports 3 Post-C downstream ports 3 Post-C downstream ports 4 Post-C downstream ports 4 Post-C downstream ports 4 Post-C downstream ports 5 Post-C downstream ports 6 Post-C DisplayPort Alternate 7 Post-C DisplayPort Alternate 8 Post-C DisplayPort Alternate 8 Post-C DisplayPort Bluernate 9 Picture-Dy-Picture (PbP) Picture-Dy-Picture (PbP) Picture Post-Picture (PbP) Picture Post-Picture	HSR hijh varcion	3 7 Con 1 (3 1 Con 1)		
Number of USB Type-B upstream ports quantity Number of USB Type-C upstream ports quantity USB Type-A downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Pype-C DisplayPort Alternate Mode USB Power Delivery up to IOSB Power Delivery (PbP) I Exterior finish type I Externet Delivery (PbP) I Externet LAN data rates IOSB Power Delivery (PbP) I Evaluate (
ports quantitySustainabilityNumber of USB Type-C upstream ports quantity1Sustainability certificates Doesn't containENERGY STAR, ROHS, TCO Mercury, PVC/BFRUSB Type-A downstream ports quantity4Recycling dataUSB Type-C downstream ports quantity1Post-consumer recycled plastic85%USB Type-C DisplayPort Alternate WodeYPicture-by-Picture (PbP)YUSB Power DeliveryYExterior finish typeTexturedUSB Power Delivery up to100 WPicture enhancementSmartImageHDMI version2.0Recyclable packaging material100%HDMI version2.0CB; CE Mark; FCC Class B; ICES-003; CU-EAC; EAEU ROHS; TUV Ergo; TUV/GS; TUV Eyesafe certified; cETLusDisplayPorts quantity1Regulatory ApprovalsCCU-EAC; EAEU ROHS; TUV Ergo; TUV/GS; TUV Eyesafe certified; cETLusAudio outputYLight sensorYBuilt-in KVM switchYLight sensorYHDCPYEasyRead modeYLowBlue modeYPhilips SmartUniformity93 - 105%Mean time between failures (MTBF)70000 hThe the properties of the propert	USB upstream port type	USB Type-B, USB Type-C	Package height	235 mm
ports quantityDoesn't containMercury, PVC/BFRUSB Type-A downstream ports quantity4Recycling dataUSB Type-C downstream ports quantity1Post-consumer recycled plastic85%USB Type-C DisplayPort Alternate ModeVOther featuresUSB Power Delivery✓Exterior finish typeTexturedUSB Power Delivery up to100 WPicture enhancementSmartlmageUSB Power Delivery up to100 WPicture enhancementSmartlmageHDMI *✓Recyclable packaging material100%HDMI version2.0CB; CE Mark; FCC Class B; ICES-003; CU-EAC; EAEU RoHS; TUV Ergo; TUV/GS; TUV Ergo; TUV/GS; TUV Eyesafe certified; cETLusDisplayPort version1.4CU-EAC; EAEU ROHS; TUV Ergo; TUV/GS; TUV Eyesafe certified; cETLusAudio outputVDelta E2Built-in KVM switchVLight sensor✓HDCPVEasyRead modeVEasyRead modeVLowBlue modeVPhilips SmartUniformity93 - 105%Mean time between failures (MTBF)70000 hTherm LAN data rates10,100,1000 Mbit/s	USB upstream port type Number of upstream ports	USB Type-B, USB Type-C 2	Package height Package weight	235 mm
quantityRecycling dataUSB Type-C downstream ports quantity1Post-consumer recycled plastic85%USB Type-C DisplayPort Alternate ModeVPicture-by-Picture (PbP)VUSB Power DeliveryVExterior finish typeTexturedUSB Power Delivery up to100 WPicture enhancementSmartImageHDMI version2.0CB; CE Mark; FCC Class B; ICES-003; CU-EAC; EAEU RoHS; TUV Ergo; TUV/GS; TUV Eyesafe certified; cETLusDisplayPort version1.4Pelta E2Audio outputVDelta E2Built-in KVM switchVLight sensorVHDCPEasyRead modeVLowBlue modePhilips SmartUniformity93 - 105%Mean time between failures (MTBF)70000 hEthernet LAN data rates10,100,1000 Mbit/s	USB upstream port type Number of upstream ports Number of USB Type-B upstream ports quantity	USB Type-B, USB Type-C 2	Package height Package weight	235 mm
USB Type-C downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Type-C DisplayPort Alternate Mode USB Power Delivery Use Martinge Power USB Power Delivery USB Power Delivery Use Martinge Power USB Power Deliver Use Martinge Power USB Power Deliver USB Power Use Martinge USC	USB upstream port type Number of upstream ports Number of USB Type-B upstream ports quantity Number of USB Type-C upstream ports quantity	USB Type-B, USB Type-C 2	Package height Package weight Sustainability Sustainability certificates	235 mm 17.1 kg ENERGY STAR, RoHS, TCO
quantityOther featuresUSB Type-C DisplayPort Alternate ModePicture-by-Picture (PbP)Image: Vector of this type in the polity of the polity	USB upstream port type Number of upstream ports Number of USB Type-B upstream ports quantity Number of USB Type-C upstream ports quantity USB Type-A downstream ports	USB Type-B, USB Type-C 2 1	Package height Package weight Sustainability Sustainability certificates Doesn't contain	235 mm 17.1 kg ENERGY STAR, RoHS, TCO
Node Picture-by-Picture (PbP) USB Power Delivery USB Power Delivery USB Power Delivery up to HDMI* HDMI version DisplayPorts quantity DisplayPort version Audio output Built-in KVM switch HDCP HDCP HDCP HDCP Picture-by-Picture (PbP) Exterior finish type Exterior finish type Exterior finish type Exterior finish type Textured CB; CE Mark; FCC Class B; ICES-003; CB; CE Mark; FCC Class B; ICES-003; CU-EAC; EAEU ROHS; TUV Ergo; TUV/GS; TUV Eyesafe certified; cETLus Light sensor Light sensor LowBlue mode LowBlue mode Phillips SmartUniformity 93 - 105% Mean time between failures (MTBF) 70000 h Ethernet LAN data rates 10,100,1000 Mbit/s	USB upstream port type Number of upstream ports Number of USB Type-B upstream ports quantity Number of USB Type-C upstream ports quantity USB Type-A downstream ports quantity	USB Type-B, USB Type-C 2 1 4	Package height Package weight Sustainability Sustainability certificates Doesn't contain Recycling data	235 mm 17.1 kg ENERGY STAR, RoHS, TCO Mercury, PVC/BFR
USB Power Delivery USB Power Delivery up to 100 W Picture enhancement SmartImage 100% HDMI * HDMI version 2.0 DisplayPorts quantity DisplayPort version Audio output Built-in KVM switch HDCP **Indeed the packaging material **Indeed the packaging materia	USB upstream port type Number of upstream ports Number of USB Type-B upstream ports quantity Number of USB Type-C upstream ports quantity USB Type-A downstream ports quantity USB Type-C downstream ports	USB Type-B, USB Type-C 2 1 4	Package height Package weight Sustainability Sustainability certificates Doesn't contain Recycling data Post-consumer recycled plastic	235 mm 17.1 kg ENERGY STAR, RoHS, TCO Mercury, PVC/BFR
USB Power Delivery up to HDMI* **Recyclable packaging material* HDMI version 2.0 CB; CE Mark; FCC Class B; ICES-003; CU-EAC; EAEU ROHS; TUV Ergo; TUV/GS; TUV Eyesafe certified; cETLus Audio output Audio output Built-in KVM switch HDCP **Regulatory Approvals* Delta E Light sensor EasyRead mode LowBlue mode Phillips SmartUniformity Phillips SmartUniformity Mean time between failures (MTBF) 70000 h Ethernet LAN data rates SmartImage 100% CB; CE Mark; FCC Class B; ICES-003; CU-EAC; EAEU ROHS; TUV Ergo; TUV/GS; TUV Eyesafe certified; cETLus CB; CE Mark; FCC Class B; ICES-003; CU-EAC; EAEU ROHS; TUV Ergo; TUV/GS; TUV Eyesafe certified; cETLus 4. Light sensor Phillips SmartUniformity 93 - 105% Mean time between failures (MTBF) 70000 h Ethernet LAN data rates	USB upstream port type Number of upstream ports Number of USB Type-B upstream ports quantity Number of USB Type-C upstream ports quantity USB Type-A downstream ports quantity USB Type-C downstream ports quantity USB Type-C DisplayPort Alternate	USB Type-B, USB Type-C 2 1 4 1	Package height Package weight Sustainability Sustainability certificates Doesn't contain Recycling data Post-consumer recycled plastic Other features	235 mm 17.1 kg ENERGY STAR, RoHS, TCO Mercury, PVC/BFR
HDMI *	USB upstream port type Number of upstream ports Number of USB Type-B upstream ports quantity Number of USB Type-C upstream ports quantity USB Type-A downstream ports quantity USB Type-C downstream ports quantity USB Type-C DisplayPort Alternate Mode	USB Type-B, USB Type-C 2 1 1 4	Package height Package weight Sustainability Sustainability certificates Doesn't contain Recycling data Post-consumer recycled plastic Other features Picture-by-Picture (PbP)	235 mm 17.1 kg ENERGY STAR, RoHS, TCO Mercury, PVC/BFR 85%
HDMI version DisplayPorts quantity DisplayPort version Audio output Built-in KVM switch HDCP	USB upstream port type Number of upstream ports Number of USB Type-B upstream ports quantity Number of USB Type-C upstream ports quantity USB Type-A downstream ports quantity USB Type-C downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery	USB Type-B, USB Type-C 2 1 1 4 1	Package height Package weight Sustainability Sustainability certificates Doesn't contain Recycling data Post-consumer recycled plastic Other features Picture-by-Picture (PbP) Exterior finish type	235 mm 17.1 kg ENERGY STAR, RoHS, TCO Mercury, PVC/BFR 85%
DisplayPorts quantity DisplayPort version 1.4 Audio output Built-in KVM switch HDCP Audio output Built-in KVM switch HDCP Audio output Built-in KVM switch HDCP Audio output Built-in KVM switch HDCP Audio output Built-in KVM switch HDCP Audio output Built-in KVM switch Audio output Audio	USB upstream port type Number of upstream ports Number of USB Type-B upstream ports quantity Number of USB Type-C upstream ports quantity USB Type-A downstream ports quantity USB Type-C downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery USB Power Delivery	USB Type-B, USB Type-C 2 1 1 4 1 ✓ ✓ 100 W	Package height Package weight Sustainability Sustainability certificates Doesn't contain Recycling data Post-consumer recycled plastic Other features Picture-by-Picture (PbP) Exterior finish type Picture enhancement	235 mm 17.1 kg ENERGY STAR, RoHS, TCO Mercury, PVC/BFR 85% Textured SmartImage
DisplayPort version 1.4 Audio output	USB upstream port type Number of upstream ports Number of USB Type-B upstream ports quantity Number of USB Type-C upstream ports quantity USB Type-A downstream ports quantity USB Type-C downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery USB Power Delivery USB Power Delivery up to HDMI *	USB Type-B, USB Type-C 2 1 1 4 1	Package height Package weight Sustainability Sustainability certificates Doesn't contain Recycling data Post-consumer recycled plastic Other features Picture-by-Picture (PbP) Exterior finish type Picture enhancement	235 mm 17.1 kg ENERGY STAR, RoHS, TCO Mercury, PVC/BFR 85% ✓ Textured SmartImage 100%
Audio output Built-in KVM switch HDCP Kubha EasyRead mode LowBlue mode LowBlue mode Philips SmartUniformity Mean time between failures (MTBF) Fight Sensor Mean time betwee	USB upstream port type Number of upstream ports Number of USB Type-B upstream ports quantity Number of USB Type-C upstream ports quantity USB Type-A downstream ports quantity USB Type-C downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery USB Power Delivery USB Power Delivery up to HDMI * HDMI version	USB Type-B, USB Type-C 2 1 1 4 1 V 100 W 2.0	Package height Package weight Sustainability Sustainability certificates Doesn't contain Recycling data Post-consumer recycled plastic Other features Picture-by-Picture (PbP) Exterior finish type Picture enhancement Recyclable packaging material	235 mm 17.1 kg ENERGY STAR, RoHS, TCO Mercury, PVC/BFR 85% ✓ Textured SmartImage 100% CB; CE Mark; FCC Class B; ICES-003; CU-EAC; EAEU RoHS; TUV Ergo;
Built-in KVM switch HDCP Light sensor EasyRead mode LowBlue mode Philips SmartUniformity Mean time between failures (MTBF) Town on the street LAN data rates 10,100,1000 Mbit/s	Number of upstream ports Number of USB Type-B upstream ports quantity Number of USB Type-C upstream ports quantity USB Type-A downstream ports quantity USB Type-C downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery USB Power Delivery USB Power Delivery up to HDMI * HDMI version DisplayPorts quantity	USB Type-B, USB Type-C 1 1 4 1 V 100 W 2.0 1	Package height Package weight Sustainability Sustainability certificates Doesn't contain Recycling data Post-consumer recycled plastic Other features Picture-by-Picture (PbP) Exterior finish type Picture enhancement Recyclable packaging material	235 mm 17.1 kg ENERGY STAR, RoHS, TCO Mercury, PVC/BFR 85% ✓ Textured SmartImage 100% CB; CE Mark; FCC Class B; ICES-003; CU-EAC; EAEU RoHS; TUV Ergo; TUV/GS; TUV Eyesafe certified;
HDCP EasyRead mode LowBlue mode Philips SmartUniformity 93 - 105% Mean time between failures (MTBF) 70000 h Ethernet LAN data rates 10,100,1000 Mbit/s	Number of upstream ports Number of USB Type-B upstream ports quantity Number of USB Type-C upstream ports quantity USB Type-A downstream ports quantity USB Type-C downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery USB Power Delivery USB Power Delivery up to HDMI * HDMI version DisplayPorts quantity DisplayPort version	USB Type-B, USB Type-C 2 1 1 4 1	Package height Package weight Sustainability Sustainability certificates Doesn't contain Recycling data Post-consumer recycled plastic Other features Picture-by-Picture (PbP) Exterior finish type Picture enhancement Recyclable packaging material Regulatory Approvals	235 mm 17.1 kg ENERGY STAR, RoHS, TCO Mercury, PVC/BFR 85% ✓ Textured SmartImage 100% CB; CE Mark; FCC Class B; ICES-003; CU-EAC; EAEU RoHS; TUV Ergo; TUV/GS; TUV Eyesafe certified; cETLus
LowBlue mode Philips SmartUniformity 93 - 105% Mean time between failures (MTBF) 70000 h Ethernet LAN data rates 10,100,1000 Mbit/s	Number of upstream ports Number of USB Type-B upstream ports quantity Number of USB Type-C upstream ports quantity USB Type-A downstream ports quantity USB Type-C downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery USB Power Delivery USB Power Delivery up to HDMI * HDMI version DisplayPorts quantity DisplayPort version Audio output	USB Type-B, USB Type-C 2 1 1 4 1	Package height Package weight Sustainability Sustainability certificates Doesn't contain Recycling data Post-consumer recycled plastic Other features Picture-by-Picture (PbP) Exterior finish type Picture enhancement Recyclable packaging material Regulatory Approvals Delta E	235 mm 17.1 kg ENERGY STAR, RoHS, TCO Mercury, PVC/BFR 85% ✓ Textured SmartImage 100% CB; CE Mark; FCC Class B; ICES-003; CU-EAC; EAEU RoHS; TUV Ergo; TUV/GS; TUV Eyesafe certified; cETLus
Philips SmartUniformity 93 - 105% Mean time between failures (MTBF) 70000 h Ethernet LAN data rates 10,100,1000 Mbit/s	Number of upstream ports Number of USB Type-B upstream ports quantity Number of USB Type-C upstream ports quantity USB Type-A downstream ports quantity USB Type-C downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery USB Power Delivery USB Power Delivery up to HDMI * HDMI version DisplayPorts quantity DisplayPort version Audio output Built-in KVM switch	USB Type-B, USB Type-C 2 1 1 4 1	Package height Package weight Sustainability Sustainability certificates Doesn't contain Recycling data Post-consumer recycled plastic Other features Picture-by-Picture (PbP) Exterior finish type Picture enhancement Recyclable packaging material Regulatory Approvals Delta E Light sensor	235 mm 17.1 kg ENERGY STAR, RoHS, TCO Mercury, PVC/BFR 85% ✓ Textured SmartImage 100% CB; CE Mark; FCC Class B; ICES-003; CU-EAC; EAEU RoHS; TUV Ergo; TUV/GS; TUV Eyesafe certified; cETLus
Mean time between failures (MTBF) 70000 h Ethernet LAN data rates 10,100,1000 Mbit/s	Number of upstream ports Number of USB Type-B upstream ports quantity Number of USB Type-C upstream ports quantity USB Type-A downstream ports quantity USB Type-C downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery USB Power Delivery USB Power Delivery up to HDMI * HDMI version DisplayPorts quantity DisplayPort version Audio output Built-in KVM switch	USB Type-B, USB Type-C 2 1 1 4 1	Package height Package weight Sustainability Sustainability certificates Doesn't contain Recycling data Post-consumer recycled plastic Other features Picture-by-Picture (PbP) Exterior finish type Picture enhancement Recyclable packaging material Regulatory Approvals Delta E Light sensor EasyRead mode	235 mm 17.1 kg ENERGY STAR, RoHS, TCO Mercury, PVC/BFR 85% ✓ Textured SmartImage 100% CB; CE Mark; FCC Class B; ICES-003; CU-EAC; EAEU RoHS; TUV Ergo; TUV/GS; TUV Eyesafe certified; cETLus
Ethernet LAN data rates 10,100,1000 Mbit/s	Number of upstream ports Number of USB Type-B upstream ports quantity Number of USB Type-C upstream ports quantity USB Type-A downstream ports quantity USB Type-C downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery USB Power Delivery USB Power Delivery up to HDMI * HDMI version DisplayPorts quantity DisplayPort version Audio output Built-in KVM switch	USB Type-B, USB Type-C 2 1 1 4 1	Package height Package weight Sustainability Sustainability certificates Doesn't contain Recycling data Post-consumer recycled plastic Other features Picture-by-Picture (PbP) Exterior finish type Picture enhancement Recyclable packaging material Regulatory Approvals Delta E Light sensor EasyRead mode LowBlue mode	235 mm 17.1 kg ENERGY STAR, RoHS, TCO Mercury, PVC/BFR 85% Textured SmartImage 100% CB; CE Mark; FCC Class B; ICES-003; CU-EAC; EAEU RoHS; TUV Ergo; TUV/GS; TUV Eyesafe certified; cETLus 2
Wake-on-LAN ✓	Number of upstream ports Number of USB Type-B upstream ports quantity Number of USB Type-C upstream ports quantity USB Type-A downstream ports quantity USB Type-C downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery USB Power Delivery USB Power Delivery up to HDMI * HDMI version DisplayPorts quantity DisplayPort version Audio output Built-in KVM switch	USB Type-B, USB Type-C 2 1 1 4 1	Package height Package weight Sustainability Sustainability certificates Doesn't contain Recycling data Post-consumer recycled plastic Other features Picture-by-Picture (PbP) Exterior finish type Picture enhancement Recyclable packaging material Regulatory Approvals Delta E Light sensor EasyRead mode LowBlue mode Philips SmartUniformity	235 mm 17.1 kg ENERGY STAR, RoHS, TCO Mercury, PVC/BFR 85% Textured SmartImage 100% CB; CE Mark; FCC Class B; ICES-003; CU-EAC; EAEU RoHS; TUV Ergo; TUV/GS; TUV Eyesafe certified; CETLus 2 4 93 - 105%
	Number of upstream ports Number of USB Type-B upstream ports quantity Number of USB Type-C upstream ports quantity USB Type-A downstream ports quantity USB Type-C downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery USB Power Delivery USB Power Delivery up to HDMI * HDMI version DisplayPorts quantity DisplayPort version Audio output Built-in KVM switch	USB Type-B, USB Type-C 2 1 1 4 1	Package height Package weight Sustainability Sustainability certificates Doesn't contain Recycling data Post-consumer recycled plastic Other features Picture-by-Picture (PbP) Exterior finish type Picture enhancement Recyclable packaging material Regulatory Approvals Delta E Light sensor EasyRead mode LowBlue mode Philips SmartUniformity Mean time between failures (MTBF)	235 mm 17.1 kg ENERGY STAR, RoHS, TCO Mercury, PVC/BFR 85% Textured SmartImage 100% CB; CE Mark; FCC Class B; ICES-003; CU-EAC; EAEU RoHS; TUV Ergo; TUV/GS; TUV Eyesafe certified; cETLus 2 93 - 105% 70000 h



8712581797454

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.