Lexmark CS730de Colour 1200 x 1200 DPI A4

Brand : Lexmark Product code: 47C9063

Product name: CS730de

- Color Laser
- Duplex (2-sided) Printing: Integrated Duplex
- Print Speed: Up to 42 ppm
- Recommended Monthly Page Volume: 1500 15000 pages

A4, Color Laser, 40 ppm, e-Task 4.3", Ethernet, USB 2.0 A/B, 32 kg

Lexmark CS730de. Print technology: Laser, Colour. Maximum duty cycle: 120000 pages per month. Maximum resolution: 1200 x 1200 DPI. Maximum ISO A-series paper size: A4. Print speed (black, normal

quality, A4/US Letter): 40 ppm, Duplex printing. Product colour: Black, White





Printing		Ports & interfaces	
Print speed (colour, normal quality, A4/US Letter)	40 ppm	USB connector	USB Type-A / USB Type-B
Colour *	√	Network	
Print technology *	Laser	Wi-Fi *	×
Duplex printing *	✓	Ethernet LAN *	✓
Maximum resolution *	1200 x 1200 DPI	Ethernet LAN data rates	10,100,1000 Mbit/s
Print speed (black, normal quality, A4/US Letter) *	40 ppm	Security algorithms	IPSec, MD5, PEAP, SSL/TLS, TLS, TTLS
Time to first page (black, normal)	6.4 s	Management protocols	DHCP, APIPA (AutoIP), BOOTP, RARP, mDNS, IGMP, WINS, DDNS, SNMPv3, SNMPv1, SNMPv2c, Telnet, NTP, ICMP, HTTP, DNS, ARP, HTTPs (SSL/TLS), Finger
Time to first page (colour, normal)	7 s		
Features			
Maximum duty cycle * Recommended duty cycle Printing colours *	120000 pages per month 1500 - 15000 pages per month Black, Cyan, Magenta, Yellow	Performance	
		Internal memory *	1024 MB
Page description languages *	PCL 5, PCL 6, PDF 1.7, PostScript 3	Built-in processor	✓
Printer fonts	PPDS, PostScript	Sound pressure level (printing)	14 dB
Input & output capacity		Design	
Total number of input trays *	1	Market positioning *	Home & office
Total input capacity *	650 sheets	Product colour *	Black, White
Total output capacity *	300 sheets	Built-in display *	✓
Maximum input capacity	2850 sheets	Display diagonal	10.9 cm (4.3")
Maximum output capacity	300 sheets	Control type	Touch
Paper handling		Power	
Maximum ISO A-series paper size *	A4	Energy Star Typical Electricity Consumption (TEC)	0.53 kWh/week
Paper tray media types *	Banner, Card stock, Envelopes, Plain paper	System requirements	
ISO A-series sizes (A0A9) *	A4, A5, A6	NAVinal according to the second	Windows 10, Windows 11, Windows
Non-ISO print media sizes	Executive, Folio, Legal, Letter, Statement, Universal	Windows operating systems supported	7 x64, Windows 8 x64, Windows 8.1, Windows Vista
JIS B-series sizes (B0B9)	B5	Linux operating systems supported	✓
Envelopes sizes	7 3/4, 9, 10, B5, C5, DL	Server operating systems supported	Windows Server 2008, Windows
Paper tray media weight	60 - 218 g/m ²		Server 2008 R2, Windows Server 2012, Windows Server 2016,
Ports & interfaces		September 1	Windows Server 2019, Windows Server 2022
Direct printing * USB port *	4	Operational conditions	
		Operating temperature (T-T)	10 - 32 °C
		operating temperature (1-1)	10 32 0

Operational conditions

Operating relative humidity (H-H) 15 - 80%

Weight & dimensions

Width 479 mm
Depth 489 mm
Height 413 mm
Weight 32 kg

