



DELL UltraSharp U4323QE 109.2 cm (43") 3840 x 2160 pixels 4K Ultra HD LCD Silver

Brand : DELL

Product family: UltraSharp

Product code: DELL-U4323QE

Product name : U4323QE

- 109.22 cm (43") 4K Ultra HD 3840 x 2160, W-LED IPS

- 8ms, 16:9, 350cd/m², 1000:1

- USB, HDMI, DisplayPort

109.22 cm (43") 4K Ultra HD 3840 x 2160, W-LED IPS, 16:9, 350cd/m², 8ms, 178°/178°, 1000:1

DELL UltraSharp U4323QE 109.2 cm (43") 3840 x 2160 pixels 4K Ultra HD LCD Silver:

Multiply your productivity with this 42.5" monitor featuring multi-PC connectivity, 4 unique FHD partitions via iMST, ComfortView Plus and wired Ethernet.

DELL UltraSharp U4323QE. Display diagonal: 109.2 cm (43"), Display resolution: 3840 x 2160 pixels, HD type: 4K Ultra HD, Display technology: LCD, Response time: 8 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub, USB version: 3.2 Gen 2 (3.1 Gen 2). VESA mounting, Height adjustment. Product colour: Silver



Display		Ports & interfaces	
Display diagonal *	109.2 cm (43")	Headphone outputs	1
Display resolution *	3840 x 2160 pixels	Built-in KVM switch	✓
HD type *	4K Ultra HD	Charging port type	USB Type-C
Native aspect ratio *	16:9	AC (power) in	✓
Display technology *	LCD	Network	
Panel type *	IPS	Wi-Fi	✗
Backlight type	W-LED	Ergonomics	
Touchscreen *	✗	VESA mounting *	✓
Display brightness (typical)	350 cd/m ²	Panel mounting interface	100 x 100,200 x 200 mm
Response time	8 ms	Cable management	✓
Anti-glare screen	✓	Cable lock slot *	✓
Screen shape *	Flat	Height adjustment *	✓
Supported graphics resolutions	640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 1024 x 768 (XGA), 1152 x 864 (XGA+), 1280 x 1024 (SXGA), 1280 x 800, 1600 x 1200 (UXGA), 1920 x 1080 (HD 1080), 1920 x 1200 (WUXGA), 2048 x 1152, 3840 x 2160	Height adjustment	6 cm
		Pivot	✗
		Swivelling	✓
		Swivel angle range	-20 - 20°
Supported video modes	480p, 576p, 720p, 1080i, 1080p, 2160p	Tilt angle range	-5 - 10°
		On Screen Display (OSD)	✓
Contrast ratio (typical) *	1000:1	Plug and Play	✓
Maximum refresh rate *	60 Hz	LED indicators	✓
Viewing angle, horizontal	178°	Tilt adjustment	✓
Viewing angle, vertical	178°	Power	
Display number of colours *	1.07 billion colours	Energy efficiency class (SDR) *	G
Response time (fast)	5 ms	Energy consumption (SDR) per 1000 hours *	52 kWh
Pixel pitch	0.2451 x 0.2451 mm	Power consumption (typical) *	52.1 W
Pixel density	103.6 ppi	Power consumption (standby) *	0.3 W
Horizontal scan range	30 - 140 kHz	Power consumption (max)	250 W
Vertical scan range	29 - 76 Hz		

Display		Power	
Viewable size, horizontal	94.1 cm	Power consumption (off)	0.3 W
Viewable size, vertical	52.9 cm	AC input voltage	100 - 240 V
Viewable size diagonal	10.8 cm	AC input frequency	50/60 Hz
High Dynamic Range (HDR) supported	✗	Power supply type	Internal
Surface hardness	3H	Operational conditions	
RGB colour space	sRGB	Operating temperature (T-T)	0 - 40 °C
Colour gamut	95%	Storage temperature (T-T)	-20 - 60 °C
Multimedia		Operating relative humidity (H-H)	10 - 80%
Built-in speaker(s) *	✓	Storage relative humidity (H-H)	5 - 90%
Built-in camera *	✗	Operating altitude	0 - 5000 m
Number of speakers	2	Non-operating altitude	0 - 12192 m
RMS rated power	8 W	Weight & dimensions	
Design		Width (with stand)	967.2 mm
Market positioning *	Business	Depth (with stand)	256.4 mm
Product colour *	Silver	Height (with stand)	595.2 mm
Front bezel colour	Black	Weight (with stand)	18.6 kg
Feet colour	Silver	Width (without stand)	96.7 cm
Heavy metals free	Hg (mercury)	Depth (without stand)	6.41 cm
Ports & interfaces		Height (without stand)	56 cm
Built-in USB hub *	✓	Weight (without stand)	13.2 kg
USB hub version	3.2 Gen 2 (3.1 Gen 2)	Bezel width (side)	1.3 cm
USB upstream port type	USB Type-C	Bezel width (top)	1.3 cm
Number of USB Type-C upstream ports quantity	4	Bezel width (bottom)	1.81 cm
USB Type-A downstream ports quantity	4	Packaging data	
USB Type-C downstream ports quantity	1	Package weight	25.2 kg
USB Type-C DisplayPort Alternate Mode	✓	Sustainability	
USB Power Delivery	✓	Sustainability certificates	ENERGY STAR, RoHS
USB Power Delivery up to	90 W	Doesn't contain	PVC/BFR
HDMI *	✓	Brand-specific features	
HDMI ports quantity	2	Dell Display Manager (DDM) compatibility	✓
HDMI version	2.1	Other features	
DisplayPorts quantity	2	On/off switch	✓
DisplayPort version	1.4	RJ-45 ports quantity	1
Headphone out *	✓		



5397184656976

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 29-MAR-2023. Prints or copies of Information are only valid on the printed Publication date