## Yealink Video Conferencing A20 + TCP18 + Wpp30 + BYOD video conferencing system 20 MP Ethernet LAN Video collaboration bar

Brand : Yealink

**Product name :** Video Conferencing A20 + TCP18 + Wpp30 + BYOD

Product code: A20-025



A20 Collaboration Bar for Small Rooms, includes CTP18 Touch Panel and Wpp30 Wireless Content Sharing and BYOD

Yealink Video Conferencing A20 + TCP18 + Wpp30 + BYOD. Product type: Video collaboration bar. HD type: 4K Ultra HD, Maximum frame rate: 30 fps. Field of view (FOV) angle: 133°. Ethernet LAN, Wi-Fi. Bluetooth. Operating system installed: Android 9. Product colour: Black

PerformanceCaractBluetonth(apapikel approx)*20 MPProduct colorsBlackMerra type(approx)*(apple caract)Auto framingPresenter modeCaract aprival shutter(apple caract)Presenter modeMerra type(ander porte)(ander porte)(ander porte)Product type*Video calaboration color(ander porte)(ander porte)Product type*Video calaboration barPresenter mode(ander porte)(ander porte)Namium video resolution8400 x 2160 prixelsProcesor model8400 x 2160 prixels(ander porte)Namium rane rate10,216 prixelsProcesor model8400 x 2160 prixels(ander porte)(ander porte)Nationapper fueld (ander porte)10,226 present model(ander porte)(ander porte)(ander porte)Nationapper fueld (ander porte)10,226 present model(ander porte)(ander porte)(ander porte)Nationapper fueld (ander porte)10,226 present model(ander porte)(ander porte)(ander porte)Nationapper fueld (ander porte)10,226 present model(ander porte) <td< th=""><th></th><th></th><th></th><th></th></td<>				
Product colour*BlackCamera typeSingle cameraAuto framing/Field of view (FOV) angle133*Tracking modesAdd participates, Calendar, contex by sharing, Hold/Resume, One-cike join, WiteboardMicrophone mute/Meeting featuresVideo collaboration barMumber of microphone arrays8PTZ contolVideo collaboration barMumber of microphone arrays8PTZ contolVideo collaboration barMumber of microphone arrays8PTZ contolVideo collaboration barMumber of microphone arrays8Video collaboration barStorphone mute/10Maximum video resolutionStdo x 2160 pixels bas 2160 pixelsStorphone Strays0ualcomm Snapdragon 845Video codecsH264 High profile, H.264 SVC H.264Porectsor family Processor model0ualcomm Snapdragon 845Audio system full dupiex/Operating relative humidity (H+H) 10 - 95%0.40 °CStarage tongel full dupiex/Operating relative humidity (H+H) 10 - 95%0.90 °CStarage tongel full dupiex/Storage temperature (T-T) 10 - 95%-30 · 70 °CStarage tongel full dupiex/Ouer consumption (typica)10 · 240 VStarage tongel full dupiex/Ouer consumption (typi	Performance		Camera	
Meeting features     sharing, Hold/Resume, One-click join, Whiteboard     Microphone mute Microphone mute     Image of Microphone arrays     Image of Microphone arrays       Product type *     Video     Image of Microphone arrays     8       PTZ control     Image of Microphone arrays     8       Video     Image of Microphone arrays     8       Video     Image of Microphone arrays     8       Video     Image of Microphone arrays     8       Maximum video resolution *     At Ultra HD     Cable lock slot     Image of Microphone arrays       Maximum video resolution *     3840 x 2160 pxiels     Processor family     Qualcomm Snapdragon       Maximum frame rate     30 fps     Processor family     Qualcomm Snapdragon       Maximum frame rate     30 fps     Processor family     Qualcomm Snapdragon       Audio     H.264 High profile, H.264 SVC, H.264 SVC, H.264 SVC, H.264     Operating temperature (1-T)     0 + 01 °C       Sudia system full duplex     Image of Microphone arrays     Storage temperature (1-T)     -0 + 01 °C       Storage temperature (1-T)     -0 + 00 °C     Operating temperature (1-T)     -0 + 0 °C       Storage temperature (1-T)	Product colour * Auto framing	Black	Camera type Field of view (FOV) angle	Single camera 133°
Meeting reatures     Sharing, Hou/Mesume, Une-Click join, Whiteboard     Microphone mute     ✓       Product type *     Video collaboration bar     Mumber of microphone arrays     8       PTZ control     ✓     Features     8       Video     ✓     Cable lock slot     ✓       PTZ control     ✓     Cable lock slot     ✓       Maximum video resolution *     3840 x 2160 pixels     Computer system     Qualcomm Snapdragon       Maximum frame rate     30 fps     Processor family     Qualcomm Snapdragon       Mutico codecs     H.264 High profile, H.264 SVC, H.264     Percessor model     845       Audio      Operating temperature (T-T)     0 - 40 °C       Built-in speaker(s)     ✓     Operating temperature (T-T)     0 - 40 °C       Audio system full duplex     ✓     Storage temperature (T-T)     0 - 40 °C       Speaker power     SW     Power     100 - 240 V       Post S interfaces     Fower consumption (typical)     10.5 W       Post S interfaces     Videh Ga Gamma     Meeting features     200 regular       ViDM loutput ports quantity     1		sharing, Hold/Resume, One-click	Microphone	
PTZ control Image: second se	Meeting features		-	4
Video   Features     Video   Cable lock slot   Cable lock slot     Maximum video resolution *   3840 x 2160 pixels   Processor family   Qualcomm Snapdragon     Maximum frame rate   30 fps   Processor family   Qualcomm Snapdragon     Video codecs   H.264 High profile, H.264 SVC, L.264   Processor model   845     Audio   H.264   Operating system installed   Android 9     Audio system full duplex   ✓   Operating relative humidity (H-H)   10 - 95%     Storage tamperature (T-T)   0 - 40 °C   -40 °C     Audio system full duplex   ✓   Operating relative humidity (H-H)   10 - 95%     Storage tamperature (T-T)   -30 - 70 °C   -00 °C   -00 °C     Speaker power   5   Storage tamperature (T-T)   -30 - 70 °C   -00 °C     Memory   5   Swer source type   AC   -00 °C   -00 °C     Potts & interfaces   5   Power consumption (typical)   10.5 W   -00 °C     HDMI output ports quantity   1   Power consumption (tale)   10 W   -00 °C     USB 2.0 ports quantity   1   Ethernet LAN (R)-45) ports   4	31	Video collaboration bar	Number of microphone arrays	8
Ho type* 4K Ultra HD Computer solution Qualcomm Snapdragon   Maximum video resolution* 3840 x 2160 pixels Processor family Qualcomm Snapdragon   Maximum frame rate 30 fps Processor model 845   Video codecs H.264 High profile, H.264 SVC, H.266 SVC, H.266 Operating system installed Android 9   Audio You consumption in the processor model Reserve the processor model Reserve the processor model   Built-in speaker(s) Image and the processor model Operating temperature (T-T) 0 - 40 °C   Audio system full duplex Image and the processor model 0 Poreting relative humidity (H-H) 10 - 95%   Storage temperature (T-T) -30 - 70 °C -30 - 70 °C -30 - 70 °C   Speaker power SW Power Image and the processor model Image and the processor and the procesor and the processor and the processor and the pr	PTZ control	4	Features	
Maximum video resolution *     3840 x 2160 pixels     Processor family     Quadromm Snapdragon       Maximum frame rate     30 fps     Processor family     Quadromm Snapdragon       Video codecs     H.264 High profile, H.264 SVC, H.264 High profile, H.264 SVC, H.264 High profile, H.264 SVC, H.264 Migh profile, H.264 SVC, H.264 Migh profile, H.264 SVC, H.264 Migh profile, H.264 SVC, H.264 Migh profile, H.264 SVC, Multio system full duplex     Operating temperature (T-T)     0 - 40 °C       Built-in speaker(s)     /     Operating temperature (T-T)     0 - 40 °C       Audio system full duplex     /     Operating temperature (T-T)     0 - 40 °C       Speaker power     5 W     Operating temperature (T-T)     -30 - 70 °C       Memory     -     Power consumption (typical)     10 - 240 V       Pots & interfaces     -     Power consumption (typical)     10.5 W       Prote consumption (typical)     10 V     -     -       USB 2.0 ports quantity     2     Power consumption (typical)     10 W       USB 2.0 ports quantity     1     Power consumption (tidle)     10 W       USB 2.0 ports quantity     1     Poeth     68 mm       Reset slot     /     Might & dimensions	Video		Cable lock slot	√
Maximum frame rate30 fps H.264 High profile, H.264 SVC, H.264 High profile, H.264 SVC, H.264 High profile, H.264 SVC, H.264Processor model Processor model845AudioProcessor model845AudioOperating system installedAndroid 9Built-in speaker(s)0 operating temperature (T-T)0 - 40 °CAudio system full duplexOperating relative humidity (H-H)10 - 95%Speaker power5 WPower			Computer system	
Built-in speaker(s) Image: Constraint of the system full duplex   Built-in speaker(s) Image: Constraint of the system full duplex Image: Constraint of the system full duplex Image: Constraint of the system full duplex   Built-in speaker(s) Image: Constraint of the system full duplex Image: Constraint of the system full duplex Image: Constraint of the system full duplex   Speaker power SW Power Power -30 - 70 °C   Speaker power SW Power -30 - 70 °C   Memory SW Power -30 - 70 °C   Total storage capacity 64 GB Power consumption (typical) 100 - 240 V   Ports & interfaces Power consumption (typical) 10.5 W   Power consumption (max) 14 W   HDMI output ports quantity 1 9 over consumption (max) 14 W   USB 2.0 ports quantity 1 Weight & dimensions 10 W   USB 2.0 ports quantity 1 Depth 68 mm   Reset slot Image: Constraint of the system full state ates Image: Constraint of the system full state ates   Network Image: Constraint of the system full state ates 10,100,1000 Mbit/s Cables included HDMI, LAN (RJ-45)	Maximum frame rate	30 fps H.264 High profile, H.264 SVC,	Processor model	845
Built-in speaker(s)/Operating temperature (T-T)0 - 40 °CBuilt-in speaker (s)/Operating relative humidity (H-H)10 - 95%Audio system full duplex/Storage temperature (T-T)-30 - 70 °CEcho cancellation/Power-30 - 70 °CSpeaker power5 WPower-30 - 70 °CMemory64 GBPower00 - 240 VPorts & interfaces00 - 240 VPower consumption (typical)10.5 WPotts & interfaces-00 - 240 VPower consumption (max)14 WHDMI output ports quantity2Power consumption (max)14 WUSB 2.0 ports quantity1Weight & dimensions10 WUSB 2.0 ports quantity1Width600 mmReset slot/Depth68 mmReset slot/Depth68 mmNetworkIn 10,100,1000 Mbit/sCables includedHDMI, LAN (RJ-45)Wi-Fi/Quick start guide/VLAN support/256-bit AES, EAP-MDS, EAP-TTLS,Start guide	Audio		Operational conditions	
Memory   AC     Total storage capacity   64 GB   AC input voltage   100 - 240 V     Ports & interfaces   Power consumption (typical)   10.5 W     HDMI output ports quantity   2   Power consumption (max)   14 W     HDMI input ports quantity   1   Weight & dimensions   10 V     USB 2.0 ports quantity   1   Weight & dimensions   600 mm     Reset slot   ✓   Depth   68 mm     Reset slot   ✓   Depth   82 mm     Ethernet LAN *   ✓   Packaging content   Edites included     Kithriet   ✓   Cables included   HDMI, LAN (RJ-45)     VLAN support   ✓   Cables included   ✓     VLAN support   ✓   Cables included   ✓     VLAN support   ✓   Store Jack Start guide   ✓	Audio system full duplex		Operating relative humidity (H-H)	10 - 95%
Total storage capacity64 GBAC input voltage100 - 240 VPorts & interfacesPower consumption (typical)10.5 WHDMI output ports quantity2Power consumption (max)14 WHDMI input ports quantity1Weight & dimensions00 - 240 VUSB 2.0 ports quantity1Weight & dimensions10 WUSB 2.0 ports quantity1Weight & dimensions00 - 240 VKetwerk1Power consumption (max)14 WEthernet LAN (RJ-45) ports1Depth600 mmNetworkIPoetaging contentPoetaging contentEthernet LAN *✓Packaging contentPoetaging contentWi-Fi✓Packaging contentIVLAN support✓Security algorithmeIDMI, LAN (RJ-45)VLAN support✓Security algorithmeZ56-bit AES, EAP-MDS, EAP-TTLS,	Speaker power	5 W	Power	
Pote storage capacity 04 GB   Ports & interfaces Power consumption (typical) 10.5 W   Power consumption (max) 14 W   PDMI output ports quantity 2 Power consumption (max) 14 W   HDMI input ports quantity 1 Power consumption (idle) 10 W   USB 2.0 ports quantity 1 Weight & dimensions 10 W   USB 2.0 ports quantity 1 Weight & dimensions 10 W   Ethernet LAN (RJ-45) ports 1 Depth 600 mm   Reset slot Image: storage content 82 mm   Network Packaging content Packaging content   Ethernet LAN * Image: storage content Cables included HDMI, LAN (RJ-45)   Wi-Fi Image: storage content Quick start guide Image: storage content   VLAN support 256-bit AES, EAP-MDS, EAP-TTLS, 256-bit AES, EAP-MDS, EAP-TTLS,	Memory		Power source type	AC
Ports & interfaces Power consumption (max) 14 W   HDMI output ports quantity 2 Power consumption (max) 14 W   HDMI input ports quantity 1 Power consumption (idle) 10 W   USB 2.0 ports quantity 1 Weight & dimensions Weight & dimensions   USB 2.0 ports quantity 1 Weight & dimensions 600 mm   Ethernet LAN (RJ-45) ports 1 Depth 68 mm   Reset slot ✓ Depth 82 mm   Network ✓ Packaging content 1   Ethernet LAN * ✓ Cables included HDMI, LAN (RJ-45)   Wi-Fi ✓ Quick start guide ✓   VLAN support ✓ 256-bit AES, EAP-MD5, EAP-TTLS, ✓	Total storage capacity	64 GB		
HDMI output ports quantity2Power consumption (idle)10 WHDMI input ports quantity1Weight & dimensionsWeight & dimensionsUSB 2.0 ports quantity1Width600 mmEthernet LAN (RJ-45) ports1Depth68 mmReset slot✓Poker consumption (idle)82 mmNetwork✓Packaging contentPackaging contentEthernet LAN *✓Cables includedHDMI, LAN (RJ-45)Wi-Fi✓✓Cables included✓VLAN support✓256-bit AES, EAP-MD5, EAP-TTLS,✓	Ports & interfaces			
Weight & dimensions     USB 2.0 ports quantity   1     Ethernet LAN (RJ-45) ports   1     Reset slot   ✓     Network   ✓     Ethernet LAN *   ✓     Ethernet LAN data rates   10,100,1000 Mbit/s     Wi-Fi   ✓     VLAN support   ✓     Security algorithme   256-bit AES, EAP-MD5, EAP-TTLS,				
Ethernet LAN (RJ-45) ports1Width600 mmReset slot✓Depth68 mmNetworkHeight82 mmEthernet LAN *✓Packaging contentEthernet LAN data rates10,100,1000 Mbit/sCables includedHDMI, LAN (RJ-45)Wi-Fi✓Cables included✓VLAN support✓✓✓Scaurity algorithms256-bit AES, EAP-MD5, EAP-TTLS,✓		-	Weight & dimensions	
Reset slot Image: Constraint of the state		-	Width	600 mm
Network Packaging content   Ethernet LAN * ✓   Ethernet LAN data rates 10,100,1000 Mbit/s   Wi-Fi ✓   VLAN support ✓   Security algorithme 256-bit AES, EAP-MD5, EAP-TTLS,		1	•	••
Ethernet LAN*   IO,100,1000 Mbit/s   Cables included   HDMI, LAN (RJ-45)     Wi-Fi   VLAN support   Quick start guide   IO,100,1000 Mbit/s     VLAN support   256-bit AES, EAP-MD5, EAP-TTLS,   IO,100,1000 Mbit/s	Network		J.	82 mm
Wi-Fi VLAN support   VLAN support   256-bit AES, EAP-MD5, EAP-TTLS,	Ethernet LAN *	✓		
VLAN support Security algorithms 256-bit AES, EAP-MD5, EAP-TTLS,				
Security algorithms 256-bit AES, EAP-MD5, EAP-TTLS,		4	Yuick start yulue	Y



6938818315013

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.