Manhattan USB-A to HDMI Cable, 1080p@60Hz, Converts USB 3.2 Gen1 (aka USB 3.0) signal to HDMI, 15cm, Black, Male to Female, Three Year Warranty, Retail Box

Brand : Manhattan

Product code: 153690

Product name : USB-A to HDMI Cable, 1080p@60Hz, Converts USB 3.2 Gen1 (aka USB 3.0) signal to HDMI, 15cm, Black, Male to Female, Three Year Warranty, Retail Box

- Easily connects a USB-A device to an HDMI display
- Resolutions up to Full HD 1080p@60Hz (1980×1080)
- Converts a USB 3.2 Gen 1 (formerly USB 3.0) signal into an HDMI signal with video and audio
- Ideal for connecting an HDMI display to a PC or laptop that doesn't have an HDMI port or for adding a display if the HDMI port is already in use
- Supports display modes Extended or Mirror on Windows®, and Mirror on Mac®
- Serves as an external graphics card, which allows adding up to two external displays to your system (requires one adapter per display)
- Built-in, sturdy 15 cm (6 in.) cable
- Bus powered: no external power supply needed
- Backward compatible with USB 2.0
- Portable, compact, lightweight design that easily fits into laptop bag pockets
- HDCP 1.4 compliant
- Plug-and-play installation; Windows®, and macOS® compatible
- Three-year warranty
USB-A to HDMI Cable, 1080p@60Hz, Converts USB 3.2 Gen1 (aka USB 3.0) signal to HDMI, 15cm, Black, Male to Female, Three Year Warranty, Retail Box

Ports & interfaces

Connectivity technology *	Wired
Host interface *	USB 3.2 Gen 1 (3.1 Gen 1) Type-A
HDMI ports quantity *	1
Microphone in *	✘
HDCP	✔
HDCP version	1.4

Network

Ethernet LAN *	✘

Performance

Card reader integrated *	✘
Maximum digital resolution	1920 x 1080 pixels
Maximum refresh rate	60 Hz
Product colour *	Black
Plug and Play	✔
Housing material	Plastic
Certification	CE FCC RoHS REACH UKCA

Power

USB cable length	0.15 m

Software

Windows operating systems supported	Windows 10, Windows 11, Windows 7, Windows 8.1
Mac operating systems supported	MacOS

Operational conditions

Operating temperature (T-T)	-20 - 45 °C
Storage temperature (T-T)	-20 - 80 °C
Operating relative humidity (H-H)	5 - 90%

Weight & dimensions

Width	45 mm
Depth	234 mm
Height	16 mm
Weight	36 g

Packaging data

Quantity per pack	1 pc(s)
Package weight	64 g

0766623153690

766623153690