SAMSUNG

Samsung SBB-SSNV Black 4K Ultra HD 8 GB 3840 x 2160 pixels Wi-Fi

Brand : Samsung Product code: SBB-SS08NV2XEN

Product name: SBB-SSNV

- Seamless UHD Content Delivery
- Intuitive All-in-One Operations
- Fully-Integrated Performance Management

UHD Signage Player Box

Samsung SBB-SSNV. Product colour: Black, Video formats supported: AVC, AVS+, H.263, H.264, HEVC, MPEG1, MPEG2, MPEG4, VC-1, VP8, VP9, Image formats supported: JPEG, PNG. Processor architecture: Cortex-A72, Processor frequency: 1700 MHz. Storage media type: eMMC, Total storage capacity: 8 GB, Compatible memory cards: SD. Internal memory: 2500 MB, Internal memory type: LPDDR4. HD type: 4K Ultra HD, Maximum video resolution: 3840 x 2160 pixels





Features		Ports & interfaces	
Product colour *	Black	RS-232C	✓
Video formats supported *		Network	
Image formats supported * Audio formats supported	VP9 JPEG, PNG AC3	Ethernet LAN * Wi-Fi * Wi-Fi standards	√ √ 802.11b, 802.11g, Wi-Fi 4 (802.11n)
Display		Software	
Built-in display *	×	Operating system installed	Tizen
Processor		Operating system version	4.0
Built-in processor	✓	Ergonomics	
Processor architecture	Cortex-A72	LED indicators	✓
Processor frequency	1700 MHz	Power	
Processor cores	4	Power consumption (typical)	21 W
Storage		Weight & dimensions	
Built-in storage media * Storage media type * Total storage capacity * Card reader integrated * Compatible memory cards	✓ eMMC 8 GB ✓ SD	Width Depth Height Weight	206.4 mm 165.6 mm 29.9 mm 600 g
Memory		Packaging data	
Internal memory Internal memory type	2500 MB LPDDR4	Package width Package depth Package height	379 mm 249 mm 80 mm
Video		Package weight	1.5 kg
HD type * Maximum video resolution	4K Ultra HD 3840 x 2160 pixels	Packaging content	
Ports & interfaces	3040 X 2100 PIXCI3	Remote control included	√
HDMI ports quantity *	1	Cables included AC adapter included	AC, HDMI ✓
HDCP *	√	·	V
Ethernet LAN (RJ-45) ports *	2.0 ports quantity * 2	Operational conditions	0.40%
USB 2.0 ports quantity * Headphone outputs		Operating temperature (T-T) Operating relative humidity (H-H)	0 - 40 °C 10 - 80%
DC-in jack	✓		





8806094402674

8592978429324

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.