i-tec USB-C HDMI Dual DP Docking Station with Power Delivery 100 W + Universal Charger 100 W

Brand : i-tec

Product code: C31TRI4KDPDPRO100UK

Product name : USB-C HDMI Dual DP Docking Station with Power Delivery 100 W + i-tec Universal Charger 100 W

USB-C HDMI Dual DP Docking Station with Power Delivery 100 W + i-tec Universal Charger 100 W
i-tec USB-C HDMI Dual DP Docking Station with Power Delivery 100 W + Universal Charger 100 W. Connectivity technology: Wired, Host interface: USB 3.2 Gen 1 (3.1 Gen 1) Type-C, USB Power Delivery up to: 100 W. Ethernet LAN data rates: 10,100,1000 Mbit/s. Product colour: Black, Data transfer rate: 10 Gbit/s, Maximum refresh rate: 144 Hz. Power source type: AC, AC input voltage: 100-240 V, AC input frequency: 50-60 Hz. Mobile operating systems supported: Android, iOS, Other operating systems supported: ChromeOS

Ports & interfaces

Connectivity technology *	Wired
Host interface *	USB 3.2 Gen 1 (3.1 Gen 1) Type-C
USB 2.0 ports quantity *	2
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity *	3
USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity	2
USB Power Delivery	✓
USB Power Delivery up to	100 W
HDMI ports quantity *	1
DisplayPorts quantity	2
DisplayPort version	1.4
Combo headphone/mic port	✓

Network

Ethernet LAN *	✓
Ethernet LAN (RJ-45) ports	1
Ethernet LAN data rates	10,100,1000 Mbit/s

Performance

Card reader integrated *	✗
Data transfer rate	10 Gbit/s
Number of displays supported	3
Maximum refresh rate	144 Hz
Cable lock slot	✓
Cable lock slot type	Kensington
Product colour *	Black
On/off switch	✓

Power

Power source type	AC
AC input voltage	100-240 V

Power

AC input frequency	50-60 Hz
Input current	2.3 A
Power supply	100 W
Output voltage	5/9/12/19/20 V
Output current	5 A
Compatible power plug types	UK
USB cable length	1 m

Software

Windows operating systems supported	✓
Mac operating systems supported	✓
Linux operating systems supported	✓
Mobile operating systems supported	Android, iOS
Other operating systems supported	ChromeOS

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	10 - 100%

Weight & dimensions

Width	113 mm
Depth	113 mm
Height	31.2 mm
Weight	340 g

Packaging content

AC adapter included	✓
Manual	✓

8595611706141