ZYXEL

Zyxel XGS2220-30 Managed L3 Gigabit Ethernet (10/100/1000) Black

Brand : Zyxel

Product code: XGS2220-30-GB0101F

Product name : XGS2220-30

24-port GbE L3 Access Switch with 6 10G Uplink
Zyxel XGS2220-30. Switch type: Managed, Switch layer: L3. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 24, Installed SFP+ modules quantity: 4. MAC address table: 32000 entries, Switching capacity: 168 Gbit/s. Networking standards: IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1x, IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3an,.... Rack mounting

Management features	
Switch type *	Managed
Switch layer	L3
Quality of Service (QoS) support	✓
Web-based management	✓
Cloud-managed	✓
ARP inspection	✓

Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity *	24
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)
10G Ethernet (copper) ports quantity	2
Installed SFP+ modules quantity *	4

Network	
Networking standards *	IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1x, IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3an, IEEE 802.3az, IEEE 802.3x, IEEE 802.3z
10G support *	✓
Routing entries	64

Data transmission	
Switching capacity *	168 Gbit/s
Forwarding rate	125 Mpps
MAC address table *	32000 entries
Static route	✓
Jumbo frames support	✓
Packet buffer memory	2 MB

Security	
DHCP features	DHCP relay, DHCP server
IGMP snooping	✓
IGMP proxy	✓

Protocols	
GARP VLAN Registration Protocol (GVRP)	✓

Design	
Rack mounting *	✓
Product colour	Black
LED indicators	✓

Performance	
Internal memory	1024 MB
Flash memory	64 MB
Mean time between failures (MTBF)	520.185 h

Power	
Power source *	AC
Power supply included *	✓
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power consumption (max)	37.62 W

Power over Ethernet (PoE)	
Power over Ethernet (PoE) *	✗

Operational conditions	
Operating temperature (T-T)	-20 - 50 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 95%
Storage relative humidity (H-H)	10 - 90%
Heat dissipation	128.28 BTU/h

Weight & dimensions	
Width	441 mm
Depth	270 mm
Height	44 mm
Weight	3.4 kg

Security	
Security algorithms	SNMP, SNMPv2, SNMPv3
BPDU filtering/protection	✓
Authentication type	IEEE 802.1x, RADIUS, TACACS+

Multicast features	
Multicast support	✓
Multicast Listener Discovery (MLD) snooping	MLD v1/v2

Packaging data	
Cables included	AC
Rack mount kit	✓
Package width	616 mm
Package depth	355 mm
Package height	107 mm
Package weight	4.73 kg

Sustainability	
Sustainability certificates	CE, Federal Communications Commission (FCC), Low Voltage Directive (LVD), RoHS

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 30-NOV-2023. Prints or copies of Information are only valid on the printed Publication date