



## BenQ LH730 data projector Standard throw projector 4000 ANSI lumens DLP 1080p (1920x1080) White

**Brand :** BenQ

**Product code:** 9H.JLK77.15E


**Product name :** LH730



BenQ LH730. Projector brightness: 4000 ANSI lumens, Projection technology: DLP, Projector native resolution: 1080p (1920x1080). Light source type: LED, Service life of light source: 20000 h, Service life of light source (economic mode): 30000 h. Focal length range: F/#=1.6~1.75,f=19.16~23.02mm, Zoom ratio: 1.2:1, Throw ratio: 1.3~1.56. Serial interface type: RS-232, HDMI version: 2.0b. Noise level: 33 dB, Noise level (economic mode): 28 dB, High Dynamic Range (HDR) technology: High Dynamic Range 10 (HDR10), Hybrid Log-Gamma (HLG)

Projector		Features	
Projector brightness *	4000 ANSI lumens	HDCP	✓
Projection technology *	DLP	On Screen Display (OSD)	✓
Projector native resolution *	1080p (1920x1080)	Number of OSD languages	30
Contrast ratio (typical) *	500000:1	Noise level *	33 dB
Native aspect ratio *	16:9	High Dynamic Range (HDR) supported	✓
Number of colours	1.07 billion colours	High Dynamic Range (HDR) technology	High Dynamic Range 10 (HDR10), Hybrid Log-Gamma (HLG)
Keystone correction, horizontal	-30 - 30°	<b>Multimedia</b>	
Keystone correction, vertical	-30 - 30°	Built-in speaker(s) *	✓
<b>Light source</b>		RMS rated power	10 W
Light source type *	LED	<b>Design</b>	
Service life of light source *	20000 h	Market positioning *	Business
Service life of light source (economic mode)	30000 h	Product type *	Standard throw projector
Lamps quantity	4 lamp(s)	Product colour *	White
<b>Lens system</b>		<b>Display</b>	
Focal length range	F/#=1.6~1.75,f=19.16~23.02mm	Built-in display *	✗
Zoom ratio	1.2:1	<b>Power</b>	
Throw ratio	1.3~1.56	Power source *	AC
Offset	91.7%	Power consumption (typical) *	365 W
<b>Video</b>		Power consumption (standby) *	2 W
Full HD *	✓	AC input voltage	100 - 240 V
<b>Ports &amp; interfaces</b>		AC input frequency	50/60 Hz
HDMI version	2.0b	<b>Operational conditions</b>	
USB 2.0 ports quantity *	2	Operating temperature (T-T)	0 - 40 °C
Headphone outputs	1	<b>Weight &amp; dimensions</b>	
Serial interface type *	RS-232	Width	420 mm
HDMI ports quantity *	1	Depth	286.7 mm
<b>Features</b>		Height	131.7 mm
Noise level (economic mode)	28 dB	Weight *	5.3 kg

### Packaging content

Remote control included \* 



4718755079412

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 29-MAR-2023. Prints or copies of Information are only valid on the printed Publication date