

## Jabra Evolve2 50 - USB-C MS Mono

**Brand :** Jabra

**Product code:** 25089-899-899

**Product name :** Jabra Evolve2 50 - USB-C MS Mono

- Designed for maximum comfort with Jabra Air Comfort technology
- Silence your surroundings with Active Noise Cancellation (ANC)
- Work-anywhere professionalism, with noise-cancelling microphone technology
- Optimised sound for professional and personal use
- Fast plug-and-play and dual connectivity
- Certified for leading virtual meeting platforms

Jabra Evolve2 50 - USB-C MS Mono

Jabra Evolve2 50 - USB-C MS Mono. Product type: Headset. Connectivity technology: Wired.

Recommended usage: Office/Call center. Headphone frequency: 20 - 20000 Hz. Cable length: 1.7 m.

Weight: 99 g. Product colour: Black



<b>Performance</b>		<b>Microphone</b>	
Product type *	Headset	Microphone type *	Boom
Wearing style *	Head-band	Microphone frequency	20 - 10000 Hz
Recommended usage *	Office/Call center	Microphone sensitivity	-38 dB
Headset type	Monaural	Folding microphone	✓
Product colour *	Black	Number of microphones	3
Operating keys	Volume +, Volume -	MEMS (Micro-Electro-Mechanical System) microphone	✓
Volume control	Button	Microphone mute	✓
Control unit type	On-ear control unit	<b>Operational conditions</b>	
Control type	Buttons	Operating temperature (T-T)	-10 - 55 °C
Cable length	1.7 m	Storage temperature (T-T)	-10 - 55 °C
Cable colour	Black	<b>Weight &amp; dimensions</b>	
Optimized for	Microsoft Teams	Width	193 mm
Music playback	✓	Depth	175 mm
HD voice	✓	Height	65 mm
Auto-connect	✓	Weight	99 g
<b>Ports &amp; interfaces</b>		<b>Packaging data</b>	
Connectivity technology *	Wired	Package width	50 mm
USB connectivity	✓	Package depth	170 mm
USB connector	USB Type-C	Package height	202 mm
Frequency response (music mode)	20 - 20000 Hz	<b>Packaging content</b>	
Frequency response (talk mode)	150 - 6800 Hz	Quick start guide	✓
<b>Headphones</b>		Pouch	✓
Maximum input power	30 mW	Quantity	1
Ear coupling *	Supraaural	<b>Supplier features</b>	
Headphone frequency	20 - 20000 Hz	Material	Acrylonitrile butadiene styrene (ABS), Leatherette, Polycarbonate (PC), Stainless steel
Driver unit	2.8 cm	<b>Other features</b>	
Noise canceling	✓	Voice guidance languages	English, French, German, Japanese, Korean
Noise canceling type	Active		

#### Other features

Call management	✓
Applications supported	Jabra Direct, Jabra Xpress
Digital Signal Processing (DSP)	✓



5706991027396



0706487023678



706487023678

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.