

ZYXEL

Zyxel GS1920-24V2 Managed Gigabit Ethernet (10/100/1000) Black

Brand : Zyxel

Product code: GS1920-24V2-GB0101F

Product name : GS1920-24V2



- Inbuilt 'awareness' of other zyxel units in your network
- Web GUI interface for centralised management
- One-click remote factory resets and power cycling
- No additional software required

GS1920-24V2, 24x 1G RJ-45, 4x 1G RJ-45/SFP, 56 Gbps, 42 Mpps, 441x131x44 mm, GB
Zyxel GS1920-24V2. Switch type: Managed. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 24. MAC address table: 16000 entries, Switching capacity: 56 Gbit/s. Networking standards: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE.... Rack mounting



Management features		Multicast features	
Switch type *	Managed	Multicast support	✓
Quality of Service (QoS) support	✓	Design	
ARP inspection	✓	Rack mounting *	✓
System event log	✓	Product colour	Black
	RFC 1066, RFC 1213, RFC 1157, RFC 1493, RFC 1643, RFC 1757, RFC 2011.2012,2013, RFC 2233, RFC 2358, RFC 2674, RFC 2819,2925, RFC 3621, RFC 4022, RFC 4113, RFC 4292, RFC 4293	LED indicators	✓
MIB support		Safety	LVD, BSMI
		Electromagnetic compatibility	FCC 15 A, CE A, BSMI EMC
		Certification	RoHS
Ports & interfaces		Performance	
Basic switching RJ-45 Ethernet ports quantity *	24	Internal memory	256 MB
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Flash memory	32 MB
Combo SFP ports quantity	4	Mean time between failures (MTBF)	911301 h
Fiber optic connector	SFP	Power	
Network		AC input voltage	100 - 240 V
	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	AC input frequency	50 - 60 Hz
Networking standards *		Power consumption (max)	22.5 W
10G support *	✗	Power over Ethernet (PoE)	
Copper ethernet cabling technology	100BASE-TX, 1000BASE-T	Power over Ethernet (PoE) *	✗
Flow control support	✓	Operational conditions	
Rate limiting	✓	Operating temperature (T-T)	0 - 50 °C
Spanning tree protocol	✓	Storage temperature (T-T)	-40 - 70 °C
VLAN support	✓	Operating relative humidity (H-H)	10 - 95%
	Private VLAN, Voice VLAN, Protocol- based VLAN, MAC address-based VLAN, Port-based VLAN, IP subnet-based VLAN	Storage relative humidity (H-H)	10 - 95%
Virtual LAN features		Heat dissipation	76.73 BTU/h
Optical fiber		Weight & dimensions	
Fiber ethernet cabling technology	1000BASE-X	Width	441 mm
		Depth	131 mm
		Height	44 mm
		Weight	2.1 kg

Data transmission		Packaging data	
Switching capacity *	56 Gbit/s	Cables included	AC
Forwarding rate	42 Mpps	Rack mount kit	✓
MAC address table *	16000 entries	Package width	558 mm
Packet buffer memory	1.5 MB	Package depth	214 mm
Security		Package height	79 mm
DHCP features	DHCP snooping, DHCP relay, DHCPv6 relay, DHCP client	Package weight	2.91 kg
Access Control List (ACL)	✓	Logistics data	
IGMP snooping	✓	Harmonized System (HS) code	85176990
Security algorithms	802.1x RADIUS, SNMP, SNMPv3		
MAC address filtering	✓		
IP-MAC-Port binding	✓		
Authentication	Guest VLAN, Port-based authentication		
Password protection	✓		
Authentication type	IEEE 802.1x, RADIUS		
CPU defense	✓		
Queue scheduling algorithms	SPQ, WFQ, Weighted Round Robin (WRR)		

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 28-APR-2023. Prints or copies of Information are only valid on the printed Publication date