




ASUS ROG Loki SFX-L 850W Platinum White power supply unit 24-pin ATX

Brand : ASUS

Product family: ROG

Product code: 90YE00N2-B0NA00

Product name : Loki SFX-L 850W Platinum White



ROG Loki SFX-L 850W Platinum power supply (fully modular power supply, 80+ Platinum, Lambda A certified, 120mm PWM ARGB fan, Aura Sync RGB lighting, ATX 3.0 compatible, PCIe 5.0 ready, white) ASUS ROG Loki SFX-L 850W Platinum White. Total power: 850 W, AC input voltage: 100 - 240 V, Combined power (+3.3V): 110 W. Motherboard power connector: 24-pin ATX, Motherboard power cable length: 45 cm, SATA power cable length: 600 mm. Purpose: PC, Power supply unit (PSU) form factor: SFX-L, 80 PLUS certification: 80 PLUS Platinum. Product colour: White, Cooling type: Active, Fan diameter: 12 cm. Width: 125 mm, Depth: 125 mm, Height: 63.5 mm



Power		Ports & interfaces	
Total power *	850 W	CPU power connector (4+4 pin)	✓
AC input voltage *	100 - 240 V	CPU power cable length	55 cm
Combined power (+3.3V)	110 W	Cabling type	Modular
Combined power (+12V)	850 W	Performance	
Combined power (+5V)	110 W	80 PLUS certification *	80 PLUS Platinum
Combined power (-12V)	9.6 W	Supported motherboard form factors	ATX
Combined power (+5Vsb)	12.5 W	Purpose *	PC
Max output current (+3.3V)	20 A	Power supply unit (PSU) form factor *	SFX-L
Max output current (+12V)	70.8 A	Bearing technology	Ball bearing
Max output current (+5V)	20 A	Design	
Max output current (-12V)	0.8 A	Product colour	White
Max output current (+5Vsb)	2.5 A	Cooling type	Active
Power protection features	Over power, Over voltage, Overcharge, Overheating, Short circuit, Under voltage	Fan diameter	12 cm
Ports & interfaces		Number of fans	1 fan(s)
Motherboard power connector *	24-pin ATX	Illumination	✓
Motherboard power cable length	45 cm	On/off switch	✓
Number of SATA power connectors	6	Weight & dimensions	
SATA power cable length	600 mm	Width	125 mm
Peripheral (Molex) power connectors (4-pin) *	4	Depth	125 mm
Peripheral (Molex) power cable length	600 mm	Height	63.5 mm
PCI Express power connectors (8-pin)	3	Weight	1.81 kg
PCI Express power connectors (16-pin)	1	Packaging data	
PCI Express power cable length	45 cm	Package width	285 mm
		Package depth	190 mm
		Package height	100 mm
		Package weight	2.5 kg
		Package type	Box
		Technical details	
		Sustainability compliance	✓
		Sustainability certificates	RoHS



4711081722229

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 16-FEB-2023. Prints or copies of Information are only valid on the printed Publication date