PHILIPS

Philips 5000 series 34B1U5600CH/75 LED display 86.4 cm (34") 3440 x 1440 pixels Wide Quad HD LCD Black

Brand : Philips **Product family:** 5000 series **Product code:** 34B1U5600CH/75

Product name: 34B1U5600CH/75

Curved UltraWide display with USB-C dock

Philips 5000 series 34B1U5600CH/75 LED display 86.4 cm (34") 3440 x 1440 pixels Wide Quad HD LCD Black:

This USB-C monitor is for data transfer, power delivery and watching videos. The integrated 5 MP webcam delivers sharp images, and the noise cancelling mic lets people hear you fine. Windows Hello Webcam for quick access and strong security.

Philips 5000 series 34B1U5600CH/75. Display diagonal: 86.4 cm (34"), Display resolution: 3440 x 1440 pixels, HD type: Wide Quad HD, Display technology: LCD, Response time: 4 ms, Native aspect ratio: 21:9, Viewing angle, horizontal: 178° , Viewing angle, vertical: 178° . Built-in speaker(s). Built-in USB hub, USB hub version: 3.2 Gen 2 (3.1 Gen 2). VESA mounting, Height adjustment. Product colour: Black







Display		Ergonomics	
Display diagonal *	86.4 cm (34")	VESA mounting *	✓
Display resolution *	3440 x 1440 pixels	Panel mounting interface	100 x 100 mm
HD type *	Wide Quad HD	Cable lock slot *	✓
Native aspect ratio *	21:9	Cable lock slot type	Kensington
Display technology *	LCD	Height adjustment *	✓
Panel type *	VA	Height adjustment	18 cm
Backlight type	W-LED	Swivelling	✓
Touchscreen *	×	Swivel angle range	-180 - 180°
Display brightness (typical)	350 cd/m ²	Tilt angle range	-5 - 25°
Response time	4 ms	Picture-in-Picture	✓
Anti-glare screen	✓	On Screen Display (OSD)	✓
Screen shape *	Curved		Simplified Chinese, Traditional
Screen curvature rating	1500R		Chinese, Czech, German, Dutch, English, Spanish, Finnish, French,
Contrast ratio (typical) *	3000:1		Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian
Contrast ratio (dynamic)	50000000:1		
Dynamic contrast ratio marketing name	SmartContrast	Plug and Play	Swedish, Turkish, Ukrainian ✓
Maximum refresh rate *	100 Hz	LED indicators	Operation, Stand-by
Viewing angle, horizontal	178°	Power	
Viewing angle, vertical	178°	Energy efficiency class (SDR) *	G
Display number of colours *	16.7 million colours	Energy efficiency class (5DR) *	Not available
Pixel pitch	0.23175 x 0.23175 mm	Energy consumption (SDR) per 1000	
Pixel density	110 ppi	hours *	40 kWh
Vertical scan range	48 - 100 Hz	Power consumption (typical) *	35 W
Viewable size, horizontal	79.7 cm	Power consumption (standby) *	0.3 W
Viewable size, vertical	33.4 cm	Power consumption (PowerSave)	31 W
Display diagonal (metric)	86.36 cm	AC input voltage	100 - 240 V
DDC/CI	✓	AC input frequency	50/60 Hz
Haze rate	25%	Power supply type	Internal

Objety United by March (Colour depth) 3 H Colour depth (Colour depth) 4 h G Colour depth (Colour depth) 8 h GB Colour depth (Colour depth) 8 h GB Colour depth (Colour depth) 8 h GB Colour depth (Colour depth) 4 h G G Colour depth (Colour depth) 4 h GB Colour depth (Colour depth) 4 h GB Colour depth (Colour depth) 2 h G G Colour depth (Colour depth) 3 h G G A G G Separate synce 4 h G G A G G <	Disular		Paris and the same	
Circuit depth 8 bR. Operational conditions 6RB columspace sRGB Operating temperature (TT) 20 - 60 °C SRGB columspace 100% Operating patheure (TT) 20 - 60 °C NTSC coverage (typical) 100% Operating altitude 20 - 60 °C Display SRGB V Operating altitude 3658 - 12192 m NONDAG SYNC* X Packaging content	Display		Power	
			Energy efficiency scale	A to G
sRGB coverage (typical) 120% Operating temperature (TT) 0 - 40 °C VTNSC coverage (typical) 100% Scorage temperature (TT) 20 - 60 °C Display sRGB 4 Operating altitude 3658 - 12192 m NOMDA G-SYNC* X Operating altitude 3658 - 12192 m MDIDA G-SYNC* X Scala Included 4 C.D. SplayPort, HDM, USB Type-C to USB Ty	•		Operational conditions	
NTSC coverage (typical) 10% Storage temperature (T.T.) -2.0.60 °C Display sRGB ✓ York Operating altitude 0.3658 m PorFormance X Storage and stitude 0.3658 ± 1219 m NVIDIA G-SYNC* X Stand included ✓ AMD FreeSync* Seat charging tenhology Power Delivery Cachise included ✓ Fast charging tenhology Power Delivery Cachise included ✓ Component Video sync Separate sync Manual ✓ Component Video sync Separate sync Manual ✓ Like Light technology ✓ Weight & dimensions Marc Tontrol Low Blue Light technology ✓ Weight & dimensions Marc Tontrol HBR3 support Manual Ø Marc Tontrol Low Blue Light technology Manual Manual<	•		Operating temperature (T-T)	0 - 40 °C
Display sRGB	- ··		Storage temperature (T-T)	-20 - 60 °C
Performance Operating altitude 0.3558 m 3558 m 3558 m 3658 m 3658 m 3658 m 3658 m 3658 m 3658 m 3659 m 36	- ··		Operating relative humidity (H-H)	20 - 80%
NUIDIA G-SYNC "	Display sRGB	√	Operating altitude	0 - 3658 m
AMD FreeSynt* Season included Common to USB Type-C Colleging betnology Manual Colleging betnology Colleging betnology Colleging betnology Manual Colleging betnology Colleging betnology Colleging betnology Colleging betnology Colleging betnology Manual Colleging betnology Colleging betnology <th< td=""><td>Performance</td><td></td><td>Non-operating altitude</td><td>3658 - 12192 m</td></th<>	Performance		Non-operating altitude	3658 - 12192 m
AMD FreeSynt* X Stand included V Fast charging V Cables included CD, EpislayPort, HDMI, USB Type-C Fast charging technology Power Delivery Cables included Type-C VESA Adaptive Sync support Separate sync Manual V Flicker-free technology Separate sync Multide software SmartControl Low Blue Light technology Mac OS X Windows 11 / 10 / 8.1 / 9 Width (with stand) 807 mm Compatible operating systems Mac OS X Windows 11 / 10 / 8.1 / 9 Width (with stand) 807 mm Bullt-in speaker(s)* V Width (with stand) 80.7 cm Bullt-in speaker(s)* V Width (with stand) 80.7 cm Sullt-in speaker(s)* V Width (with stand) 80.7 cm Bullt-in speaker(s)* V Weight (with stand) 80.7 cm Sullt-in speaker(s)* V Depth (with stand) 80.7 cm Sullt-in speaker(s)* J Weight (with stand) 80.7 cm Weight (without stand) 80.7 cm 80.7 cm Weight (approx.)	NVIDIA G-SYNC *	×	Packaging content	
Fast charging bethnology Power Delivery Cables included NC. DisplayPort, HDML USB Type-C to USB Type-C to USB Type-C, USB Type-C, USB Type-C to USB Type-C, USB Type-C to USB Type-C, USB Type-C to USB Type-C t	AMD FreeSync *	×		1
Fast charging technology Power Delivery Cables included to USB Type-A, USB Type-C to USB Type-C	Fast charging	✓	Stand included	
Component video sync Separate sync Manual Verafficher from the chinology Manual bundled offware SmartControl Low Blue Light betchnology Very Mich with stands 807 mm Compatible operating systems Mac OS X Windows 11/10/8.1/8 / 7 Width (with stand) 807 mm Muttimedia Feight (with stand) 50 mm 1.7 kg Built-in speaker(s)* V Meight (with stand) 80.7 cm Built-in speaker(s)* V Meight (without stand) 80.7 cm Built-in speaker(s)* V Meight (without stand) 80.7 cm Number of speakers 2 Height (without stand) 80.7 cm Miss rated power 10 W Package with 80.9 kg Megapixel (approx.) 5 MP Package widh 80.9 kg Built-in microphone J Package widh 92 mm Product colour* Black Package weight 525 mm Front beel colour Black Package weight 525 mm Forts & interfaces Black Sustainability compliance 50 kg Bui	Fast charging technology	Power Delivery	Cables included	
Fileker-free technology √ Weight & dimensions Low Blue Light technology √ Weight & dimensions HBRB3 support √ Width (with stand) 807 mm Compatible operating systems A COS X Windows 11/10/81/8 / 7 bepth (with stand) 601 mm 601 mm Multi-media ✓ Width (with stand) 610 mm 607 cm Built-in speaker(s) * ✓ Width (without stand) 11 cm Number of speakers 2 Height (without stand) 11 cm Number of speakers 2 Height (without stand) 36.7 cm RMS rated power 10 W Weight (without stand) 36.7 cm Meseapaixel (approx.) 5 MP Package width 904 mm Built-in microphone √ Package depth 282 mm Market positioning * Black 928 mm 282 mm Front bazel colour Black 928 mm 282 mm Forth bazel colour Black 92 mm 482 mm Forth bazel colour Slack (siteriace) 92 mm 482 mm	VESA Adaptive Sync support	✓		Type-C
Low Blue Light technology ✓ Weight & dimensions HBR3 support Mac OS X Windows 11/10 / 8.1 / 8 Width (with stand) 807 mm Compatible operating systems Mac OS X Windows 11/10 / 8.1 / 8 Depth (with stand) 601 mm Multimedia February (belief) (with stand) 11.7 kg Built-in camera* ✓ Width (without stand) 11.7 kg Built-in camera* ✓ Height (without stand) 36.7 cm Number of speakers 2 Height (without stand) 36.7 cm MRS rated power 10 Weight (without stand) 36.7 cm MRS rated power 10 Weight (without stand) 36.7 cm Megapixel (approx.) 5 MP Package weight 36.7 cm Market positioning* Business 9ackage depth 282 mm Postage depth 282 mm 282 mm Product colour* Black Sustainability compliance 15.4 kg Fort seel colour Black Sustainability compliance Entert of the set of	Component video sync	Separate sync	Manual	1
HBR3 support V Width (with stand) 807 mm Compatible operating systems 7 begith (with stand) 250 mm Multimedia Height (with stand) 601 mm Built-in speaker(s)* 4 Width (without stand) 80.7 cm Built-in camera* 4 Width (without stand) 80.7 cm Number of speakers 2 Height (without stand) 36.7 cm RMS rated power 10 W Weight (without stand) 36.7 cm RMS rated power 10 W Weight (without stand) 36.7 cm Market positioning* 5 MP Package width 30.04 kg Market positioning* Business Package weight 25 5 mm Product colour* Black Package depth 25 5 mm Front bezel colour Black Sustainability Feet colour Black Weight (with stand) 4 Verst & interfaces Black Package weight 15.4 kg Will-in Justy Bhub* ✓ Sustainability Weight (with stand) 16.7 kg US	Flicker-free technology	✓	Bundled software	SmartControl
Compatible operating systems Mac OS X Windows 11/10/8.1/9 Width (with stand) 807 mm Multimedia Feet by the with stand 250 mm Built-in speaker(s)* 4 Weight (with stand) 610 mm Built-in speaker(s)* 4 Weight (with stand) 11.7 kg Built-in camera* 4 Weight (without stand) 11 cm Number of speakers 2 Depth (without stand) 36.7 cm RWS rated power 10 W Height (without stand) 36.7 cm Wegaptkel (approx.) 5 MP Perbuilt (without stand) 36.7 cm Built-in microphone 4 Package depth (without stand) 36.0 kg Beilit-in microphone 4 Package depth 32.0 mm Built-in microphone Built-in microphone 32.0 mm 32.0 mm Postsign Built-in microphone Built-in microphone Sustainability compliance \$2.5 mm Product colour* Black Sustainability compliance \$2.5 mm Front See interfaces Sustainability compliance Mercury, PVC/BFR Built-in USB hub*	Low Blue Light technology	✓	Weight & dimensions	
Compatible operating systems Mac OS X Windows 11/10/18.1/ y Height (with stand) 250 mm Multimedia Height (with stand) 250 mm Built-in speaker(s) * 4 Width (without stand) 80.7 cm Built-in camera * 4 Width (without stand) 80.7 cm Number of speakers 2 Height (without stand) 36.7 cm RMS rated power 10 W Weight (without stand) 36.7 cm Megapixel (approx.) 5 MP Peckage width (without stand) 36.7 cm Built-in microphone 7 Peckaging data Built-in microphone 4 Peckage width 904 mm Product colour * Black Package weight 15.4 kg Front bezel colour Black Statianability Feet colour Ports interfaces Sustainability compliance Feet colour Kerror STAR, TCO, RoHS USB hub version 3.2 Gen 2 (3.1 Gen 2) Recycling data Feet store USB Type-A downstream ports quantity 1 Procession state of the store Recycling data USB Type-C flowing vape-C works are appeared ports quant	HBR3 support	✓	Width (with stand)	807 mm
Multimedia Height (with stand) 601 mm Built-in speaker(s)* ✓ Weight (with stand) 10.7 kg Built-in camera* ✓ Depth (with out stand) 36.7 cm Number of speakers 10 W Height (without stand) 36.7 cm MKS rated power 10 W Weight (without stand) 36.7 cm MRS rated power 10 W Weight (without stand) 36.7 cm Megapixel (approx.) 5 MP Package width 904 mm Megapixel (approx.) 7 Package width 904 mm Mercy Package weight 28.2 mm Market positioning* Business Package weight 52.5 mm Product colour* Black Package weight 15.4 kg Product colour* Black Sustainability Mercyr. Ports & interfaces Sustainability Mercyr. Built-in USB hub* ✓ Sustainability compliance Mercyr., PVC/BFR USB hub version 3.2 Gen 2 (3.1 Gen 2) Beryle (with stand) Mercyr., PVC/BFR USB Type-A downstream port squantity 1	Compatible operating systems	Mac OS X Windows 11 / 10 / 8.1 / 8 /		250 mm
Multimedia Weight (with stand) 1.7 kg Built-in speaker(s)* √ Width (without stand) 8.0 7 cm Built-in camena* √ Peth (without stand) 1.1 cm Number of speakers 2 Height (without stand) 36.7 cm RMS rated power 10 W Weight (without stand) 36.7 cm Megapixel (approx.) 5 MP Package width 904 mm Built-in microphone √ Package width 904 mm Market positioning * Busines Package wight 525 mm Product colour* Black 9ackage weight 15.4 kg Front bezel colour Black 525 mm Feet colour Black 525 mm Ports & interfaces Sustainability compliance ✓ Built-in USB hub* √ Mercury, PVC/BFR USB Type-A downstream ports 2 Post-Consumer recycled plastic 85% Built-in byse-A downstream ports 1 Post-consumer recycled plastic 85% USB Type-C DisplayPort Alternate Post-consumer recycled plastic P		,	•	601 mm
Built-in camera* V Depth (without stand) 11 cm Number of speakers 2 Height (without stand) 36.7 cm MKS rated power 10 W Weight (without stand) 36.7 cm Megapixel (approx.) 5 MP Weight (without stand) 8.04 kg Built-in microphone 7 Packagin dat 90.4 mm Built-in microphone 7 Package depth 282 mm Market positioning* Business Package depth 252 mm Frout colour* Black Package weight 525 mm Front bezel colour Black Sustainability Feet colour Black Sustainability compliance \$ Forts & interfaces \$ Sustainability compliance \$ Built-in USB hub* \$ Sustainability compliance \$ Built-in USB hub* \$ Doesn't contain Mercury, PVC/BFR USB Type-A downstream ports quantity \$ Recycling data * USB Type-A downstream ports quantity \$ Exterior finish type Textured	Multimedia		-	11.7 kg
Number of speakers 2 Height (without stand) 3.6.7 cm RMS rated power 10 W Weight (without stand) 3.6.7 cm Megapixel (approx.) 5 MP Packaging data Built-in microphone	Built-in speaker(s) *	✓	Width (without stand)	80.7 cm
RMS rated power 10 W Weight (without stand) 8.0° CM Megapixel (approx.) 5 MP Packaging data 904 mm Built-in microphone Package width 904 mm Design Business Package depth 282 mm Market positioning ** Business Package height 525 mm Product colour * Black Package weight 15.4 kg Front bezel colour Black Sustainability 525 mm Feet colour Black Sustainability compliance 525 mm Ports & interfaces Sustainability compliance Mercury, PVC/BFR USB tub version 3.2 Gen 2 (3.1 Gen 2) Recycling data Wereury, PVC/BFR USB tub version 3.2 Gen 2 (3.1 Gen 2) Recycling data Wereury, PVC/BFR USB Type-A downstream ports quantity 4 Other features S% USB Type-C downstream ports quantity 1 Exterior finish type Textured USB Type-C downstream ports quantity 4 Exterior finish type Textured USB Power Delivery 4 Quest to push	Built-in camera *	✓	Depth (without stand)	11 cm
Megapixel (approx.) 5 MP Packaging data Built-in microphone Package width 904 mm Design Package depth 282 mm Market positioning* Business Package height 525 mm Frond to colour* Black 255 mm Front bezel colour Black 525 mm Feet colour Black Sustainability Ports & interfaces Sustainability certificates ENERGY STAR, TCO, RoHS Built-in USB hub* 4 Doesn't contain Mercury, PVC/BFR USB ubstream port type 3.2 Gen 2 (3.1 Gen 2) Recycling data Sevening data USB Type-A downstream ports quantity 1 Post-consumer recycled plastic 85% USB Type-C downstream ports quantity 1 Exterior finish type Textured USB Type-C DisplayPort Alternate Mode 4 Exterior finish type Textured USB Power Delivery 4 Regulatory Approvals CB: CE Mark: FCC Class B: ICES-003; EMICS; TUV Ergo; TUV/GS; TUV Ergo; TU	Number of speakers	2	Height (without stand)	36.7 cm
Built-in microphone Packaging data Design Package depth 282 mm Market positioning* Business Package depth 252 mm Product colour* Black Package weight 15.4 kg Front bezel colour Black Sustainability Feet colour Black Sustainability compliance ✓ Feet colour Justinability compliance Sustainability compliance ✓ Ports & interfaces Justinability compliance Sustainability comp	RMS rated power	10 W	Weight (without stand)	8.04 kg
Design Package width 904 mm Design Package depth 282 mm Market positioning * Business Package height 525 mm Product colour * Black Package weight 15.4 kg Front bezel colour Black Sustainability compliance ✓ Feet colour Black Sustainability cortificates ENERGY STAR, TCO, RoHS Built-in USB hub * ✓ Doesn't contain Mercury, PVC/BFR USB bub version 3.2 Gen 2 (3.1 Gen 2) Recycling data SS USB type-A downstream port type USB Type-C Post-consumer recycled plastic 85% USB Type-A downstream ports quantity 1 Post-consumer recycled plastic 85% USB Type-C downstream ports quantity 1 Picture eby-Picture (PbP) ✓ USB Type-C DisplayPort Alternate Quantity ✓ Recyclable packaging material 100% CB; CE Mark; FCC Class B; ICES-003; CLES-003; C		5 MP	Packaging data	
Design Package depth 282 mm Market positioning * Business Package height 525 mm Product colour * Black Package weight 15.4 kg Front bezel colour Black 20 sustainability 15.4 kg Feet colour Black Sustainability compliance ✓ Forts & interfaces Sustainability certificates ENERGY STAR, TCO, RoHS Built-in USB hub * ✓ Doesn't contain Mercury, PVC/BFR USB type but version 3.2 Gen 2 (3.1 Gen 2) Recycling data 85% USB type-A downstream ports quantity USB Type-C 85% Sost-consumer recycled plastic 85% USB Type-C downstream ports quantity 1 Picture by-Picture (PbP) ✓ USB Type-C DisplayPort Alternate Mode ✓ Picture enhancement Smarttmage USB Power Delivery ✓ Recyclable packaging material 100% USB Power Delivery up to 100 W CB: CE Mark; FCC Class B; ICES-003; CU-EAC; EAEU RoHS; SEMKO; TUV Ergo: CU-EAC; EAEU RoHS; SEMKO; TUV HDMI ports quantity 1 Light sensor	Built-in microphone	✓		904 mm
Market positioning * Business Package height 525 mm Product colour * Black Package weight 15.4 kg Front bezel colour Black Sustainability Feet Colour Black Sustainability Ports & interfaces Built-in USB hub * ✓ Doesn't contain Mercury, PVC/BFR USB bub version 3.2 Gen 2 (3.1 Gen 2) Recycling data Werzury, PVC/BFR USB type-A downstream ports quantity 4 Other features 55% USB Type-A downstream ports quantity 1 Picture-by-Picture (PbP) ✓ USB Type-C DisplayPort Alternate Mode Y Picture-by-Picture (PbP) ✓ USB Pype-C DisplayPort Alternate Mode Y Recyclable packaging material 100% USB Power Delivery up to MDM in yersion 1 Regulatory Approvals CU-EAC; EAEU RoHS; SEMKO; TUV Ergo; TUV/GS; TUV Eye Comfort certified HDMI version 2.0 Delta E 2 DisplayPort version 1.4 EasyRead mode ✓ Headphone out * 4 LowBlue mode ✓	Design			
Product colour* Black Package weight 15.4 kg Front bezel colour Black Sustainability ************************************	Market positioning *	Business	- '	
Front bezel colour Feet colour Black Black Sustainability compliance Sustainability certificates Sustainability certificates Sustainability certificates Sustainability certificates ENERGY STAR, TCO, RoHS Sustainability certificates Sustainability Association Sustainability Certificates Sustainability Association Sustainability Certificates Sustainability Association Susta	Product colour *	Black		
Ports & interfaces Built-in USB hub* USB hub version USB upstream port type USB Type-C USB Type-C downstream ports quantity USB Power Delivery USB Power Delivery USB Power Delivery up to HDMI ports quantity HDMI version 2.0 DisplayPorts quantity 1 DisplayPorts quantity 1 DisplayPorts quantity 1 DisplayPort squantity 1 DisplayPort version 1.4 EasyRead mode Low Blue and the shade of the shade of the shade out the deadphone out * HDCP HDCP version Network Sustainability compliance Sustainability compliance Sustainability compliance Sustainability compliance Sustainability certificates Sustainability certified Sustaination Sustaination Sustaination Sustaination Sustaination Sustainat	Front bezel colour	Black		
Ports & interfaces Sustainability certificates ENERGY STAR, TCO, RoHS Built-in USB hub * Jopesn't contain Mercury, PVC/BFR USB Ubstream port type USB Type-C Recycling data USB Type-A downstream ports quantity 4 Dest-consumer recycled plastic 85% USB Type-C downstream ports quantity 1 Picture-by-Picture (PbP) Image: Post-consumer recycled plastic 85% USB Type-C downstream ports quantity 1 Picture befaures Textured USB Type-C DisplayPort Alternate Mode Image: Picture (PbP) Image: Picture on Picture (PbP) Image: Picture on Picture o	Feet colour	Black		
Built-in USB hub* Coesn't contain Mercury, PVC/BFR USB hub version 3.2 Gen 2 (3.1 Gen 2) Recycling data USB Type-A downstream port type USB Type-C Post-consumer recycled plastic 85% USB Type-A downstream ports quantity 4 Other features Textured USB Type-C downstream ports quantity 1 Exterior finish type Textured USB Type-C DisplayPort Alternate Mode Y Exterior finish type Textured USB Power Delivery Y Recyclable packaging material 100% USB Power Delivery up to 100 W CB; CE Mark; FCC Class B; ICES-003; CU-EAC; EAEU RoHS; SEMKO; TUV Ergo; TUV/GS; TUV Eye Comfort certified HDMI version 2.0 Delta E 2 DisplayPorts quantity 1 Light sensor ✓ HBADP Version 1.4 EasyRead mode ✓ HEAD Poversion 1.4/2.2 LowBlue mode ✓ HDCP version 1.4/2.2 Mean time between failures (MTBF) 70000 h Metwork ***Control Millips**	Ports & interfaces		· ·	
USB hub version USB upstream port type USB Type-C USB Type-A downstream ports quantity USB Type-C downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery Usc Power Delivery USB Power Delivery Usc	Built-in USB hub *	J	•	
USB Type-A downstream ports quantity USB Type-C downstream ports quantity USB Type-C downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery USB Power Delivery USB Power Delivery up to HDMI yersion Delta E DisplayPort squantity 1 Delta E Delta E Delta E DisplayPort version 1.4 EasyRead mode LowBlue mode HDCP HDCP HDCP Network Welca en I All 2 Post-consumer recycled plastic Post-consumer table Post-co				Mercury, PVC/BFR
USB Type-A downstream ports quantity USB Type-C downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery Use Delta E USB Power Delivery Use Delta E USB CE Mark; FCC Class B; ICES-003; CU-EAC; EAEU RoHS; SEMKO; TUV Ergo; TUV/GS; TUV Eye Comfort certified USB Power Delivery USB Power Delivery USB Power Delivery Use Delta E Use Delta E USB Power Delta E Use Delta E USB Power Delta E USB Power Delta E USB Power Delta E USB Power Delta E USE Delta E USB Power Delta E USB Power Delta E USB Power Delta E USB Power Delta E USE Delta E USB Power Delta E USE	USB upstream port type		Recycling data	
QuantityOther featuresUSB Type-C downstream ports quantity1Picture-by-Picture (PbP)✓USB Type-C DisplayPort Alternate ModeExterior finish typeTexturedUSB Power Delivery✓Recyclable packaging material100%USB Power Delivery up to100 WCB; CE Mark; FCC Class B; ICES-003; CU-EAC; EAEU RoHS; SEMKO; TUV Ergo; TUV/GS; TUV Eye Comfort certifiedHDMI ports quantity1CU-EAC; EAEU RoHS; SEMKO; TUV Ergo; TUV/GS; TUV Eye Comfort certifiedHDMI version2.0Delta E2DisplayPorts quantity1Light sensor✓DisplayPort version1.4EasyRead mode✓Headphone out *✓LowBlue mode✓HDCP✓Philips SmartUniformity93 - 105%HDCP version1.4/2.2Men time between failures (MTBF)70000 hNetworkWalso and All MaterialsMaterial All Materials	USB Type-A downstream ports		Post-consumer recycled plastic	85%
quantityPicture-by-Picture (PbP)Verture (PbP)USB Type-C DisplayPort Alternate ModeExterior finish typeTexturedUSB Power DeliveryVerture enhancementSmartImageUSB Power Delivery up to100 WCB; CE Mark; FCC Class B; ICES-003; CU-EAC; EAEU RoHS; SEMKO; TUV Ergo; TUV/GS; TUV Eye Comfort certifiedHDMI ports quantity1Light sensor2DisplayPorts quantity1Light sensorVDisplayPort version1.4EasyRead modeVHeadphone out *VersionVersionVHDCPVersionPhilips SmartUniformity93 - 105%HDCP version1.4/2.2Mean time between failures (MTBF)70000 hNetworkWalso an LAN.	' '	7	Other features	
USB Type-C DisplayPort Alternate Mode Mode Picture enhancement Recyclable packaging material USB Power Delivery USB Power Delivery up to HDMI * HDMI ports quantity HDMI version Delta E DisplayPort version 1.4 Headphone out * HDCP HDCP HDCP HDCP Mean time between failures (MTBF) Network Exterior finish type Textured SmartImage 100% CB; CE Mark; FCC Class B; ICES-003; CU-EAC; EAEU RoHS; SEMKO; TUV Ergo; TUV/GS; TUV Eye Comfort certified CU-EAC; EAEU RoHS; SEMKO; TUV Ergo; TUV/GS; TUV Eye Comfort certified Light sensor Light sensor LowBlue mode HLOWBlue mode HDCP Headphone out * HOCP Mean time between failures (MTBF)		1	Picture-by-Picture (PbP)	✓
Mode Wode With Picture enhancement With Power Delivery With Power Delivery With Power Delivery up to With Power Delivery With	'		Exterior finish type	Textured
USB Power Delivery up to HDMI * HDMI ports quantity HDMI version DisplayPorts quantity 1 Light sensor DisplayPort version Headphone out * HDCP HDCP HDCP HDCP Headphone Headphone Headphone HDCP Headphone Headphone Headphone HDCP HDCP HDCP HDCP HDCP HDCP Headphone Headphone Headphone HDCP HDCP HDCP HDCP HDCP HDCP HDCP HDCP		✓	Picture enhancement	SmartImage
HDMI *	USB Power Delivery	✓	Recyclable packaging material	100%
HDMI ports quantity 1 HDMI version 2.0 Delta E Light sensor DisplayPort version 1.4 Headphone out * HDCP HDCP HDCP Headphone 1.4/2.2 Regulatory Approvals Ergo; TUV/GS; TUV Eye Comfort certified 2 Light sensor FasyRead mode LowBlue mode V How Blue mode Philips SmartUniformity Philips SmartUniformity Mean time between failures (MTBF) 70000 h Retwork Walks on LAN	USB Power Delivery up to	100 W		
HDMI ports quantity HDMI version 2.0 Delta E Light sensor DisplayPort version 1.4 Headphone out * HDCP HDCP HDCP HDCP Network Certified 2 Delta E Light sensor FasyRead mode Light sensor Light sensor FasyRead mode LowBlue mode How	HDMI *	✓	Regulatory Approvals	
DisplayPorts quantity DisplayPort version 1.4 EasyRead mode Headphone out * HDCP Philips SmartUniformity Philips SmartUniformity Mean time between failures (MTBF) Network Poeta E Z Z Z Z Z Z Z Z Z Z Z Z Z	HDMI ports quantity	1		
DisplayPort version 1.4 EasyRead mode Headphone out * HDCP Philips SmartUniformity Philips SmartUniformity 93 - 105% HDCP version 1.4/2.2 Mean time between failures (MTBF) Network Welco and AN	HDMI version	2.0	Delta E	2
DisplayPort version Headphone out * HDCP HDCP version 1.4/2.2 Mean time between failures (MTBF) Network HDCP version 1.4/2.2 Mean time between failures (MTBF) Network Water and AN	DisplayPorts quantity	1	Light sensor	✓
Headphone out * HDCP HDCP version 1.4/2.2 Mean time between failures (MTBF) Network LowBlue mode Philips SmartUniformity 93 - 105% Mean time between failures (MTBF) 70000 h Ethernet LAN data rates 10,100,1000 Mbit/s	DisplayPort version	1.4	=	✓
HDCP version 1.4/2.2 Mean time between failures (MTBF) 70000 h Network Ethernet LAN data rates 10,100,1000 Mbit/s	·		LowBlue mode	✓
Network Ethernet LAN data rates 10,100,1000 Mbit/s			Philips SmartUniformity	93 - 105%
Welco on LAN	HDCP version	1.4/2.2	Mean time between failures (MTBF)	70000 h
Ethernet LAN ✓ Wake-on-LAN ✓	Network		Ethernet LAN data rates	10,100,1000 Mbit/s



8712581801304

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.