Sony SRG-A12 8.5 MP Black 3840 x 2160 pixels 60 fps CMOS 25.4 / 2.5 mm (1 / 2.5")

Brand : Sony Product code: SRG-A12BC

Product name: SRG-A12

- High speed pan/tilt
- Wide angle zoom lens
- Powerful Zoom, wide angle
- PTZ Auto Framing
- Preset camera positions
- Picture Freeze Preset
- AF, AE and AWB
- PTZ Motion Sync
- Simple, flexible setup
- Single network cable
- HDMI/SDI outputs

SRG-A12 PTZ camera with PTZ Auto Framing

Sony SRG-A12. Megapixel (approx.): 8.5 MP, Sensor type: CMOS. HD type: 4K Ultra HD, Maximum video resolution: 3840 x 2160 pixels, Maximum frame rate: 60 fps. Optical zoom: 12x. Product colour: Black





| Camera | | Design | |
|--|---|--|---|
| Camera type | Single camera | Pan speed (max) | 300 °/sec |
| Megapixel (approx.) * | 8.5 MP CMOS 25.4 / 2.5 mm (1 / 2.5") 12x 4.4 - 52.8 mm 70° 1.6 lx | Ports & interfaces | |
| Sensor type Optical sensor size Zoom capability Optical zoom Focal length range Horizontal field of view (wide) Minimum illumination Flip & mirror | | HDMI ports quantity Ethernet LAN (RJ-45) ports DC-in jack 3G-SDI output Microphone in VISCA output ports VISCA input ports | 1 1 ✓ ✓ 1 1 |
| Aperture range (F-F) | √ 2 - 3.7 | Power | |
| White balance Auto exposure | Auto, Daylight, Indoor, Manual, One push, Outdoor Auto, Manual, Shutter priority AE Auto/Manual Auto/Manual | Power source type DC input voltage Power consumption (typical) | AC, DC 19.5 V 80 W |
| Light exposure modes | | Operational conditions | |
| Focus adjustment Gain control type PTZ control | | Operating temperature (T-T) Storage temperature (T-T) | 0 - 40 °C -20 - 60 °C |
| PTZ protocols | VISCA | Packaging content | |
| Minimum working distance (wide) Maximum working distance (tele) Slowest camera shutter speed Fastest camera shutter speed | 8 cm 40 cm 1 s 1/10000 s | Power supply included Cables included Warranty card | ✓ AC, HDMI ✓ |
| Video | 1/10000 S | Screws included Mounting brackets included | 1 |
| Video HD type * | 4K Ultra HD | Mounting brackets included | * |
| | , | | Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IoT Enterprise, Windows 10 Pro, Windows 10 Pro x64, Windows 10 Pro x64, Windows 10 |
| HD type * Maximum video resolution * Maximum frame rate * Video formats supported Supported graphics resolutions Number of TV lines | 4K Ultra HD 3840 x 2160 pixels 60 fps H.264, H.265 640 x 360, 1280 x 720 (HD 720), 1920 x 1080 (HD 1080), 3840 x 2160 | Mounting brackets included System requirements Windows operating systems | Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IoT Enterprise, Windows 10 Pro, Windows 10 Pro x64, Windows 11, Windows 11 |
| HD type * Maximum video resolution * Maximum frame rate * Video formats supported Supported graphics resolutions | 4K Ultra HD 3840 x 2160 pixels 60 fps H.264, H.265 640 x 360, 1280 x 720 (HD 720), 1920 x 1080 (HD 1080), 3840 x 2160 | Mounting brackets included System requirements Windows operating systems | Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IoT Enterprise, Windows 10 Pro, Windows 10 Pro x64, Windows 10 Pro x64, Windows 10 |

| Design | | Performance | |
|---|-------------------------------------|-----------------------------|---|
| Tally light Tilt speed (min) Tilt speed (max) Pan speed (min) | 0.5 °/sec 126 °/sec 0.5 °/sec | Auto framing | 1 |
| | | Audio | |
| | | Audio channels | 2 |
| | | Audio codecs | AAC LC 256kbps/ST (IP), AAC LC 128kbps/ST(IP) |
| | | Network | |
| | | Multi-stream capability | 3 |
| | | Bit rate control | Constant Bit Rate (CBR), Variable Bit Rate (VBR) |
| | | Bit rate range | 512 - 50000 Kbit/s |
| | | Supported network protocols | IPv4, IPv6, TCP, UDP, ARP, ICMP, HTTP, HTTPS, DHCP, DNS, RTP/RTCP, RTSP, VISCA over IP, SRT |
| | | Weight & dimensions | |
| | | Width | 156.7 mm |
| | | Depth | 200 mm |
| | | Height | 184 mm |
| | | Weight | 2 kg |





5013493458642

4548736143425

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.