Viewsonic LS510W data projector Standard throw projector 3000 ANSI lumens LED WXGA (1280x800) White

Brand : Viewsonic

Product code: LS510W

Product name : LS510W

- 3rd generation LED technology for greater sustainability

- Maintenance free: 30,000-hour light source life and less power consumption

- 3,000 ANSI Lumens offering bright images in any environment

- Ease of use: instant power on/off and convenient software update

- Wide color gamut to present the best

0.65" WXGA, 1280 x 800, LED, 3000 lm, 30"~300", HDMI, 293 x 221 x 115 mm, 240 W Viewsonic LS510W. Projector brightness: 3000 ANSI lumens, Projection technology: LED, Projector native resolution: WXGA (1280x800). Light source type: LED, Service life of light source: 30000 h. Focal length range: 22 - 24.1 mm, Aperture range (F-F): 2.56 - 2.68, Throw ratio: 1.55 - 1.70. Supported graphics resolutions: 640 x 480 (VGA), 1920 x 1080 (HD 1080), Supported video modes: 480i, 480p, 576i, 576p, 720p, 1080i, 1080p. Serial interface type: RS-232, HDMI connector type: Full-size



Smart projector *XCard reader integrated *XScreen size compability *762 - 7620 mm (30 - 300*)FeaturesProjector distance1 - 10.98 mInteractive *XProjector technology *LEDNoise level (economic mode)24 dBProjector technology *LEDMXGA (1280x800)On Screen Display (0SD)/Number of colours1.07 billion colours1.07 billion colours/Number of colours1.07 billion colours1.07 billion colours/Number of colours1.07 billion colours//Natrix sizeDMDNumber of OSD languages24Matrix kypeDMDNumber of OSD languages24Matrix kypeDMDNumber of OSD languages24Light source type *LEDMultimedia/Light source type *2.56 - 2.88Z/Portuge (Fr)2.56 - 2.8Z/Zoon capability///Product colour *White/Jongo (Fr)100%Z/Supported graphics resolution640 x 480 (VGA), 1920 x 1080 (HD/Jongo (Fr)1.4Storage temperature (T-T)0.40 *CSupported graphics resolution1.4Operating relative tuning (HL)0.50 *CSupported graphics resolution1.4Operating relative tuning (HL)0.50 *CSupported graphics resolution1.4Operating relative tuning (HL)0.50 *CSupported graphics resolution1.4Operating re				
Screen size compatibility* 762 - 7620 mm (30 - 300") Petures Projector infythess* 1.0.98 m Interactive * X Projector infythess* 3000 ANSI lumens Interactive * X Projector infythess* 3000 ANSI lumens Noise level (economic mode) 28 dB Projector native resolution* WKAK (1280x800) On Screen Display (OSD) / Ourstar tardi (viprical)* 300000:1 On Screen Display (OSD) languages Traditional Chinese, Tradi	Projector		Storage	
Projection distance 1 - 10.98 m Interactive * Projection technology* BUD Noise level (economic mode) 28 dB Projection technology* LED Moise level (economic mode) 28 dB Projection technology* WXGA (1280x800) MDCP ✓ Number of colours 1.07 billine colours Arabic, Simplified Chinese, Creerh, German Display (OSD) ✓ Number of colours 1.07 billine colours Traditional Chinese, Czech, German Display (OSD) ✓ Matrix size 1.07 billine colours No Screen Display (OSD) languages ✓ Matrix size 1.05 cm (0.65°) Number of OSD languages Z4 Matrix size 0.000 h Built-in speaker(5)* ✓ ✓ Light source type* LED Built-in speaker(5)* ✓ ✓ Light source type * LED Built-in speaker(5)* ✓ ✓ Service life dright source* 30000 h Built-in speaker(5)* ✓ ✓ Com capability ✓ Morece ✓ ✓ Service life dright source* 30000 h	Smart projector *	×	Card reader integrated *	×
Projector brightness*3000 ANSI lumensInteractive **×Projector atkinology*LEDNoise level (economic mode)28 dBProjector native resolution*WCA (1280x800)On Screen Display (OSD)✓Contrast ratio (typical) *300000:1✓Arabic, Simplified Chinese, Traditional Chinese, Creeh, German Display (OSD) languagesArabic, Simplified Chinese, Traditional Chinese, Creeh, German Display (OSD) languagesArabic, Simplified Chinese, Traditional Chinese, Creeh, German Display (OSD) languagesNumber of ColoursNorece, Pindi, Hungarian, Indonesian, Italian, Japanese, Korean, Polish, Portuguese, Russian Sweish, Thai, Turkish, Vietnamese Matrix sizeAfabicStandard Hrow projector Korean, Polish, Portuguese, Russian Korean, Polish, Portuguese, Russian, R	Screen size compatibility *	762 - 7620 mm (30 - 300")	Features	
LEDMultimediaService life of light source *3000 hBuilt-in speaker(s) *✓Service life of light source *3000 hBuilt-in speaker(s) *✓Lens systemRMS rated power2 WFocal length range22 - 24.1 mmNumber of built-in speakers1Aperture range (F-F)2.56 - 2.68DesignStandard throw projectorZoom capability✓Product type *Standard throw projectorThrow ratio1.55 - 1.70Product colour *WhiteOffset000%ED indicators✓VideoCable lock slot✓Full HD *XDisplayXSupported graphics resolutions640 x 480 (VGA), 1920 x 1080 (H) 1080Power source *ACSupported video modesFull-sizePower consumption (typical) *240 WHDM connector typeFull-sizePower consumption (typical) *0.5 WHDM version1.4Operating etmperature (T-T)0.40 °CUSB 2.0 ports quantity *1Storage temperature (T-T)0.90%Audio (L/R) out1Storage relative humidity (H-H)0.90%Vadio (L/R) out1Operating altitude0.300 mVadio (L/R) out1Operating altitude0.90%Vadio (L/R) out1 </td <td>Projector brightness * Projection technology * Projector native resolution * Contrast ratio (typical) * Number of colours Horizontal scan range Vertical scan range Keystone correction, vertical Matrix size Matrix type</td> <td>3000 ANSI lumens LED WXGA (1280x800) 3000000:1 1.07 billion colours 15 - 102 kHz 23 - 120 Hz +/- 40° 1.65 cm (0.65")</td> <td>Noise level (economic mode) HDCP On Screen Display (OSD) On Screen Display (OSD) languages Number of OSD languages</td> <td>28 dB Arabic, Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Greek, Hindi, Hungarian, Indonesian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Thai, Turkish, Vietnamese 24</td>	Projector brightness * Projection technology * Projector native resolution * Contrast ratio (typical) * Number of colours Horizontal scan range Vertical scan range Keystone correction, vertical Matrix size Matrix type	3000 ANSI lumens LED WXGA (1280x800) 3000000:1 1.07 billion colours 15 - 102 kHz 23 - 120 Hz +/- 40° 1.65 cm (0.65")	Noise level (economic mode) HDCP On Screen Display (OSD) On Screen Display (OSD) languages Number of OSD languages	28 dB Arabic, Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Greek, Hindi, Hungarian, Indonesian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Thai, Turkish, Vietnamese 24
Service life of light source* 3000 h Built-in speaker(s)* / Lens system // RMS rated power 2 W Number of built-in speakers 1 Focal length range 22 - 24.1 mm Aperture range (F-F) 2.56 - 2.68 Design Zoom capability / I Colow Product type * Standard throw projector Throw ratio 1.55 - 1.70 Product colour * White Offset 1000% LED indicators / I Colow Product colour * Colow Product Colow * Colow * Colow Product Colow * Colow Product Colow * Co	-			5145
Lens systemRMS rated power2 WFocal length range22 · 24.1 mmNumber of built-in speakers1Aperture range (F-F)2.56 · 2.68DesignZoom capability✓Product type *Standard throw projectorThrow ratio1.55 · 1.70Product colour *WhiteOffset1000%LED indicators✓VideoCable lock slot✓Full HD *XDisplayX3D *XBuilt-in display *XSupported graphics resolutions480i, 480p, 576ip, 576p, 720p, 1080i 1080pPowerACSupported video modesFull-sizePower consumption (typical) *240 WPorts & interfacesFull-sizeOperating temperature (T-T)0.40 °CHDMI version1.4Operating temperature (T-T)0.40 °CUSB 2.0 ports quantity*1Storage temperature (T-T)0.40 °CVadio (L/R) out1Operating relative humidity (H-H)0.90%Audio (L/R) out1Storage relative humidity (H-H)0.90%Audio (L/R) out1Storage relative humidity (H-H)0.90%Serial interface type *RS-232Operating altitude0.3000 mVGA (D-Sub) ports quantity*1Storage relative humidity (H-H)0.90%	5 51			
Fund systemNumber of built-in speakers1Focal length range (F-F)2.56 2.68DesignZoom capabilityProduct type *Standard throw projectorThrow ratio1.55 - 1.70Product colour *WhiteOffset1000%LED indicatorsVideoCable lock slotFull HD *XDistalyaXSupported graphics resolution640 x 480 (VGA), 1920 x 1080 (HD 1080)PowerXSupported video modes640, 480, 576i, 576p, 720p, 1080 1080Power consumption (typical) *240 WPower consumption (typical) *240 WWWPower consumption (typical) *0.5 WWWHDMI connector typeFull-sizePoerating temperature (T-T)0.40 °CLDS 2.0 ports quantity *1Storage temperature (T-T)0.40 °CAudio (L/R) out1Capacity elaitive humidity (H+H)0.90%Audio (L/R) out1Storage tenperature (T-T)0.90%Audio (L/R) out1S	Service life of light source *	30000 h		
Focal length range 22 - 24.1 mm Aperture range (F-F) 2.56 - 2.68 Design Zoon capability Intow ratio Product type * 0 Standard throw projector Throw ratio 1.55 - 1.70 Product colour * 0 White Offset 1000% LED indicators ✓ Video Cable lock slot ✓ Full HD * X Display X 3D * X04 0480 (VGA), 1920 x 1080 (MD) Newer X Supported graphics resolutions 640 x 480 (VGA), 1920 x 1080 (MD) Newer consumption (typical) * 240 W Supported wideo modes 480i, 480p, 576i, 576p, 720p, 1080 (MD) Power consumption (typical) * 240 W Potts & interfaces Power consumption (typical) * 240 W HDMI connector type Full-size Power consumption (standby) * 0.5 W HDMI version 1.4 Operating temperature (T-T) -0.40 °C USB 2.0 ports quantity * 1 Storage temperature (T-T) -0.60 °C Audio (L/R) in * 1 Operating relative humidity (H-H) 0.90% Audio (L/R) out 1 Storage relative humidity (H-H) 0.	Lens system		•	
Appendic runge (i 1)2.100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 100 / 1	Focal length range		·	-
VideoCable lock slotImage: state	Zoom capability Throw ratio	✓ 1.55 - 1.70	Product type * Product colour *	White
Full HD * 3D *XDisplay3D *XBuilt-in display *XSupported graphics resolutions $640 \times 480 (VGA), 1920 \times 1080 (HD1080)$ PowerPowerSupported video modes $80i, 480p, 576i, 576p, 720p, 1080i1080pPower consumption (typical) *ACPots & interfacesPower consumption (typical) *240 WHDMI connector typeFull-sizeOperational conditions0.5 WHDMI version1.4Operating temperature (T-T)0 - 40 °CUSB 2.0 ports quantity *1Storage temperature (T-T)-20 - 60 °CAudio (L/R) out1Operating relative humidity (H-H)0 - 90%Audio (L/R) out1Storage relative humidity (H-H)0 - 90%Serial interface type *RS-232Operating altitude0 - 3000 mVGA (D-Sub) ports quantity *1Weight & dimensions$				
Summe 3D*K3D*640 x 480 (VGA), 1920 x 1080 (HD 1080)Built-in display *KSupported graphics resolutions640 x 480 (VGA), 1920 x 1080 (HD 1080)PowerSupported video modes480i, 480p, 576i, 576p, 720p, 1080i, 1080pPower source *AC Power consumption (typical) *Potts & interfacesPower consumption (typical) *240 WHDMI connector typeFull-sizeOperational conditionsHDMI version1.4Operating temperature (T-T)0 - 40 °CUSB 2.0 ports quantity *1Storage temperature (T-T)-20 - 60 °CAudio (L/R) in *1Operating relative humidity (H-H)0 - 90%Audio (L/R) out1Storage relative humidity (H-H)0 - 90%Serial interface type *RS-232Operating altitude0 - 3000 mVGA (D-Sub) ports quantity *1Weight & dimensions0		.	Display	
Supported graphics resolutions1080/ 480i, 480p, 576i, 576p, 720p, 1080i, 1080pPower source * Power consumption (typical) * 240 WACPorts & interfacesPower consumption (typical) * Power consumption (typical) * 0.5 W240 WHDMI connector typeFull-size Operational conditions HDMI version1.4Operating temperature (T-T) Storage temperature (T-T)0 - 40 °CAudio (L/R) in *1Operating relative humidity (H-H) 0 - 90%0 - 90%Audio (L/R) out1Storage relative humidity (H-H) 0 - 90%0 - 90%VGA (D-Sub) ports quantity *1Weight & dimensions	3D *			×
Number of the sector of the	Supported graphics resolutions		Power	
HDMI connector typeFull-sizeOperational conditionsHDMI version1.4Operating temperature (T-T)0 - 40 °CUSB 2.0 ports quantity *1Storage temperature (T-T)-20 - 60 °CAudio (L/R) in *1Operating relative humidity (H-H)0 - 90%Audio (L/R) out1Storage relative humidity (H-H)0 - 90%Serial interface type *RS-232Operating altitude0 - 3000 mVGA (D-Sub) ports quantity *1Weight & dimensions	Supported video modes	480i, 480p, 576i, 576p, 720p, 1080i,	Power consumption (typical) *	240 W
HDMI version1.4Operating temperature (T-T)0 - 40 °CUSB 2.0 ports quantity *1Storage temperature (T-T)-20 - 60 °CAudio (L/R) in *1Operating relative humidity (H-H)0 - 90%Audio (L/R) out1Storage relative humidity (H-H)0 - 90%Serial interface type *RS-232Operating altitude0 - 3000 mVGA (D-Sub) ports quantity *1Weight & dimensions	Ports & interfaces			VV C.U
USB 2.0 ports quantity *1Storage temperature (T-T)-20 - 60 °CAudio (L/R) in *1Operating relative humidity (H-H)0 - 90%Audio (L/R) out1Storage relative humidity (H-H)0 - 90%Serial interface type *RS-232Operating altitude0 - 3000 mVGA (D-Sub) ports quantity *1Weight & dimensions	HDMI connector type			
Audio (L/R) in *1Operating relative humidity (H-H)0 - 90%Audio (L/R) out1Storage relative humidity (H-H)0 - 90%Serial interface type *RS-232Operating altitude0 - 3000 mVGA (D-Sub) ports quantity *1Weight & dimensions				
Audio (L/R) out 1 Storage relative humidity (H-H) 0 - 90% Serial interface type * RS-232 Operating altitude 0 - 3000 m VGA (D-Sub) ports quantity * 1 Weight & dimensions				
Serial interface type * RS-232 Operating altitude 0 - 3000 m VGA (D-Sub) ports quantity * 1 Weight & dimensions				
VGA (D-Sub) ports quantity * 1 Weight & dimensions	Serial interface type *	-		
	VGA (D-Sub) ports quantity *			
	HDMI ports quantity *	1		

Ports & interfaces		Weight & dimensions		
IR input ports quantity AC (power) in	1 ✓	Width Depth	293 mm 221 mm	
Network		Height Weight *	115 mm 2.65 kg	
Smart TV * Ethernet LAN * Wi-Fi *	× × ×	Package width Package depth Package height Package weight	2.00 kg 365 mm 300 mm 188 mm 2.85 kg	
		Packaging content		
		Remote control included *	4	

Cables included

Manual

AC

∢





766907018073

0766907018073

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.