

Epson EB-L775U data projector 7000 ANSI lumens 3LCD WUXGA (1920x1200) Black

Brand : Epson **Product code:** V11HA96180

Product name: EB-L775U

4KE display solution

Epson EB-L775U. Projector brightness: 7000 ANSI lumens, Projection technology: 3LCD, Projector native resolution: WUXGA (1920x1200). Light source type: Laser, Service life of light source: 20000 h, Service life of light source (economic mode): 30000 h. Focus: Manual, Focal length range: 20 - 31.8 mm, Aperture range (F-F): 1.5 - 1.7. Video colour modes: Cinema, DICOM simulation mode, Dynamic, Multiprojection, Natural, Presentation. Serial interface type: RS-232C





Projector		Storage	
Screen size compatibility *	1270 - 12700 mm (50 - 500")	Card reader integrated *	X
Projector brightness *	7000 ANSI lumens	Features	
Projection technology * Projector native resolution *	3LCD WUXGA (1920x1200)	Interactive *	×
Contrast ratio (typical) *	2500000:1	Noise level (economic mode)	27 dB
Native aspect ratio *	16:10	Noise level *	37 dB
Number of colours	1.07 billion colours	High Dynamic Range (HDR) supported	✓
Keystone correction, horizontal	-30 - 30°	High Dynamic Range (HDR)	High Dynamic Bango 10 (HDB10)
Keystone correction, vertical	-30 - 30°	technology	High Dynamic Range 10 (HDR10)
Light source		Multimedia	
Light source type *	Laser	Built-in speaker(s) *	✓
Service life of light source *	20000 h	RMS rated power	10 W
Service life of light source (economic mode)	30000 h	Design	
,		Market positioning *	Education
Lens system	Marian	Product colour *	Black
Focus * Focal length range	Manual 20 - 31.8 mm	Placement	Ceiling, Desktop
Aperture range (F-F)	1.5 - 1.7	Cable lock slot	√
Zoom capability	1.5 - 1.7	Cable lock slot type	Kensington
Zoom type	Manual	Power	
Throw ratio	1.35 - 2.20:1	Power source *	AC
Video		Power consumption (typical) *	300 W
Analog signal format system *	Not supported	Power consumption (standby) *	0.5 W
Full HD *	✓	Power consumption (max) Power consumption (economy	366 W
3D *	×	mode)	277 W
	Cinema, DICOM simulation mode,	AC input frequency	50/60 Hz
Video colour modes	Dynamic, Multi-projection, Natural, Presentation	AC adapter output voltage	100 - 240 V
Ports & interfaces		Operational conditions	
HDBaseT port	1	Storage temperature (T-T)	-10 - 60 °C
USB 2.0 ports quantity *	2	Operating relative humidity (H-H)	20 - 80%
USB 2.0 Type-A ports quantity	1	Storage relative humidity (H-H)	10 - 90%
USB 2.0 Type-B ports quantity	1	Weight & dimensions	
Serial interface type *	RS-232C	Width	440 mm
HDMI ports quantity *	3	Depth	304 mm
DVI port *	×	Height	122 mm
Network		Weight *	8.5 kg
Ethernet LAN *	×	Packaging content	
Wi-Fi *	✓	Remote control included *	✓
		Batteries included	✓

