

## TP-Link Deco X50-5G Dual-band (2.4 GHz / 5 GHz) Wi-Fi 6 (802.11ax) White 3 Internal

Brand : TP-Link

Product code: DECO X50-5G(1-PACK)

Product name : Deco X50-5G


- Ultra-Fast Broadband Connection: Supports Sub-6 GHz 5G technology boosts download speeds up to 3.4 Gbps§

- Ultra-Low Latency: 5G brings responsive network connections with only 1 ms latency§
- AX3000 Dual-Band Wi-Fi 6 Speed: 2402 Mbps (5 GHz) + 574 Mbps (2.4 GHz)†
- 2.5 Gigabit Wired Connections: 1× 2.5 Gbps port + 2× Gigabit port\*\*
- Mesh Network: Deco mesh technology ensures strong Wi-Fi signals everywhere‡
- Flexible Network Access: 4G, 5G, Fixed-Line Internet Access
- Simplified Setup: Easily set up and manage your network with the TP-Link Deco app
- TP-Link HomeShield: Provides comprehensive network protection, robust parental controls, and real-time loT security $^{*}$
- 5G AX3000 Whole Home Mesh WiFi 6 Gateway (Availability based on regions)





Design		Wireless LAN features	
Product type Product colour * Antenna type * Antennas quantity	Mesh system White Internal 2	IGMP snooping Tagged VLAN Dynamic DNS (DDNS) Control apps supported	✓ ✓ ✓ TP-Link Deco
Maximum coverage	230 m <sup>2</sup>	Mobile network	
Storage temperature (T-T) -40	0 - 40 °C -40 - 60 °C 10 - 90%	Mobile network generation 4G standard	5G LTE-TDD & LTE-FDD
Storage relative humidity (H-H)	5 - 90%	Features	
Certification Wireless LAN features	RoHS, CE, RCM	Quality of Service (QoS) support MU-MIMO technology MIMO	
Wi-Fi band *	Dual-band (2.4 GHz / 5 GHz)	Protocols	•
Top Wi-Fi standard * Wi-Fi standards WLAN data transfer rate (first band) WLAN data transfer rate (second		DHCP client DHCP server Supported network protocols (IPv6) Universal Plug and Play (UPnP)	✓ ✓ IPv4/IPv6 ✓
band)	574 Mbit/s	Ports & interfaces	
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n	Ethernet LAN (RJ-45) ports * Ethernet WAN	3 ✓
Security algorithms	WPA, WPA2, WPA3	Weight & dimensions	
Point-to-point protocol over Ethernet (PPPoE) Dynamic IP Static IP	4	Width Depth Height	130 mm 123 mm 210.5 mm
Wireless Distribution System (WDS)	*	Packaging content	
lGMP proxy	4	AC adapter included Ethernet cable	4





4897098687949

4897098687826

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.