

iiyama LE5041UHS-B1 Signage Display Digital signage flat panel 125.7 cm (49.5") LCD 350 cd/m² 4K Ultra HD Black 18/7

Brand : iiyama

Product code: LE5041UHS-B1

Product name : LE5041UHS-B1

iiyama LE5041UHS-B1. Product design: Digital signage flat panel. Display diagonal: 125.7 cm (49.5"), Display technology: LCD, Display resolution: 3840 x 2160 pixels, Display brightness: 350 cd/m², HD type: 4K Ultra HD. Operating hours (hours/days): 18/7. Product colour: Black



Display		Design	
Panel type	VA	Screen shape	Flat
Display diagonal *	125.7 cm (49.5")	VESA mounting *	✓
Display technology *	LCD	Panel mounting interface	400 x 400 mm
Display resolution *	3840 x 2160 pixels	Performance	
Display brightness *	350 cd/m ²	Purpose *	Universal
HD type *	4K Ultra HD	On Screen Display (OSD)	✓
Touchscreen *	✗	Number of OSD languages	11
Native aspect ratio	16:9	Operating hours (hours/days)	18/7
Response time	9 ms	Mean time between failures (MTBF)	50000 h
Contrast ratio (typical)	5000:1	Power	
Viewing angle, horizontal	178°	Power consumption (typical) *	112 W
Viewing angle, vertical	178°	Power consumption (standby) *	0.5 W
Display number of colours	1.07 billion colours	Power consumption (off)	0.3 W
Pixel pitch	0.285 x 0.285 mm	Energy efficiency class (SDR)	G
Active display area (W x H)	1096 x 616.4 mm	Energy consumption (SDR) per 1000 hours	112 kWh
Display diagonal (metric)	125.7 cm	AC input voltage	100 - 250 V
Horizontal scan range	30 - 83 kHz	AC input frequency	50/60 Hz
Ports & interfaces		Computer system	
HDMI ports quantity *	3	Computer system *	✗
DVI port *	✗	Built-in processor *	✗
VGA (D-Sub) input ports	1	Weight & dimensions	
USB port *	✓	Display width	1127.6 mm
USB ports quantity	2	Display depth	72.5 mm
Ethernet LAN *	✓	Display height	648.2 mm
Ethernet LAN (RJ-45) ports	1	Display weight	13.2 kg
Wi-Fi *	✗	Packaging data	
Audio (L/R) out	1	Package width	1245 mm
RS-232C	✓	Package depth	148 mm
Remote (IR) input	1	Package height	790 mm
Remote (IR) output	1	Package weight	17.9 kg
Audio		Packaging content	
Built-in speaker(s) *	✓	Remote control included	✓
Number of built-in speakers	2		
RMS rated power	20 W		

Design		Packaging content	
Product design *	Digital signage flat panel	Batteries included	✓
Placement supported *	Indoor	Cables included	AC, HDMI, RS-232
Orientation	Horizontal	Operational conditions	
Product colour *	Black	Operating temperature (T-T)	0 - 40 °C



4948570120949

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.