PHILIPS

Philips 6000 series 40B1U6903CH LED display 100.8 cm (39.7") 5120 x 2160 pixels 5K Ultra HD LCD Black

Brand : Philips Product family: 6000 series Product code: 40B1U6903CH

Product name: 40B1U6903CH

6000 series 5K2K UltraWide Thunderbolt™ monitor

Philips 6000 series 40B1U6903CH LED display 100.8 cm (39.7") 5120 \times 2160 pixels 5K Ultra HD LCD Black:

The Philips Thunderbolt™ 4 monitor delivers a secure, reliable one-cable docking solution, delivering sharp images, with a noise cancelling mic that lets people hear you properly. Windows Hello Webcam for quick access and strong security.

Philips 6000 series 40B1U6903CH. Display diagonal: 100.8 cm (39.7"), Display resolution: 5120 x 2160 pixels, HD type: 5K Ultra HD, Display technology: LCD, Response time: 4 ms, Native aspect ratio: 21:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub, USB hub version: 3.2 Gen 2 (3.1 Gen 2). VESA mounting, Height adjustment. Product colour: Black





Display		Ports & interfaces	
Display diagonal *	100.8 cm (39.7")	HDMI *	✓
Display resolution *	5120 x 2160 pixels	HDMI ports quantity	2
HD type *	5K Ultra HD	HDMI version	2.0
Native aspect ratio *	21:9	DisplayPorts quantity	1
Display technology *	LCD	DisplayPort version	1.4
Panel type *	IPS	Thunderbolt 4 ports quantity	1
Backlight type	W-LED	Audio output	✓
Touchscreen *	×	Microphone in	✓
Display brightness (typical)	300 cd/m ²	Built-in KVM switch	✓
Response time	4 ms	HDCP	✓
Anti-glare screen	✓	HDCP version	1.4/2.2
Screen shape *	Curved	Network	
Screen curvature rating	2500R	Ethernet LAN	1
Contrast ratio (typical) *	1000:1		•
Contrast ratio (dynamic)	80000000:1	Ergonomics	
Dynamic contrast ratio marketing name	SmartContrast	VESA mounting * Panel mounting interface	✓ 100 x 100 mm
Maximum refresh rate *	75 Hz	Cable lock slot *	✓
Viewing angle, horizontal	178°	Cable lock slot type	Kensington
Viewing angle, vertical	178°	Height adjustment *	√
Display number of colours *	1.07 billion colours	Height adjustment	15 cm
Pixel pitch	0.1815 x 0.1815 mm	Swivelling	✓
Pixel density	140 ppi	Swivel angle range	-45 - 45°
Horizontal scan range	30 - 140 kHz	Tilt angle range	-5 - 15°
Vertical scan range	30 - 60 Hz	Picture-in-Picture	1
Viewable size, horizontal	92.9 cm	On Screen Display (OSD)	✓
Viewable size, vertical	39.2 cm	, , ,	Simplified Chinese, Traditional
Digital horizontal frequency	30 - 170 kHz		Chinese, Czech, German, Dutch,
Digital vertical frequency	48 - 75 Hz	On Screen Display (OSD) languages	English, Spanish, Finnish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian,
Display diagonal (metric)	100.9 cm		
High Dynamic Range (HDR) supported	✓	Number of OSD languages	Swedish, Turkish, Ukrainian 21
High Dynamic Range (HDR)	High Dynamic Range 10 (HDR10)	Plug and Play	✓
technology	riigii byriainiic Range 10 (HbR10)	LED indicators	Operation, Stand-by
DDC/CI	✓		
Haze rate	25%	Power	
Surface hardness	3H	Power consumption (typical) *	58.3 W
RGB colour space	DCI-P3	Power consumption (standby) *	0.44 W
Colour gamut	98%	Power consumption (PowerSave)	44.6 W
sRGB coverage (typical)	134%	AC input voltage	100 - 240 V

Display		Power	
NTSC coverage (typical)	113%	AC input frequency	50/60 Hz
Display sRGB	113% ✓	Power supply type	Internal
Performance		Operational conditions	
NVIDIA G-SYNC * AMD FreeSync * Fast charging Fast charging technology VESA Adaptive Sync support Component video sync Flicker-free technology	X Y Power Delivery Separate sync	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Operating altitude Non-operating altitude Packaging content Bundled software	0 - 40 °C -20 - 60 °C 20 - 80% 0 - 3658 m 3658 - 12192 m
Low Blue Light technology	1		SiliarControl
HBR3 support	Mar OC V Windows 11 / 10 / 0 1 / 0	Weight & dimensions	0.40
Compatible operating systems Multimedia Built-in speaker(s) * Built-in camera * Number of speakers RMS rated power Megapixel (approx.) Built-in microphone	Mac OS X Windows 11 / 10 / 8.1 / 8	Width (with stand) Depth (with stand) Height (with stand) Weight (with stand) Width (without stand) Depth (without stand) Height (without stand) Weight (without stand)	948 mm 236 mm 605 mm 13.5 kg 948 mm 109 mm 426 mm 10.3 kg
Design		Packaging data	
Market positioning * Product colour * Front bezel colour Feet colour Heavy metals free	Business Black Black Black Hg (mercury)	Package width Package depth Package height Package weight Sustainability	1150 mm 211 mm 565 mm 17.2 kg
Ports & interfaces		Sustainability compliance	1
USB upstream port type	3.2 Gen 2 (3.1 Gen 2) USB Type-B 2	Sustainability certificates Doesn't contain	CB, CE, ENERGY STAR, Federal Communications Commission (FCC), RoHS, TCO, TUV Mercury, PVC/BFR
		Recycling data	
Number of USB Type-B upstream ports quantity	1	Post-consumer recycled plastic	85%
USB Type-A downstream ports	4	Other features	
JSB Type-C downstream ports 1 JSB Type-C DisplayPort Alternate Mode JSB Power Delivery JSB Power Delivery up to 90 W	Picture-by-Picture (PbP) Exterior finish type Picture enhancement Recyclable packaging material Delta E SoftBlue EasyRead mode Philips SmartUniformity Mean time between failures (MTBF) Ethernet LAN data rates Wake-on-LAN	Textured SmartImage 100% 2 93 - 105% 70000 h 10,100,1000 Mbit/s	

