

**PHILIPS**

# Philips 275S9JML/00 computer monitor 68.6 cm (27") 2560 x 1440 pixels Quad HD LCD Black

**Brand :** Philips

**Product code:** 275S9JML/00

**Product name :** 275S9JML/00

S Line 27" (68.5 cm), 2560 x 1440 (QHD), VA, 4 ms, 75 Hz, 613 x 525 x 205 mm, 5.6 kg

Philips 275S9JML/00 computer monitor 68.6 cm (27") 2560 x 1440 pixels Quad HD LCD Black:

Our S Line monitor delivers business efficiency. Features like Flicker-free and LowBlue mode make work easy on the eyes and increase your productivity.

Philips 275S9JML/00. Display diagonal: 68.6 cm (27"), Display resolution: 2560 x 1440 pixels, HD type: Quad HD, Display technology: LCD, Response time: 4 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub. VESA mounting, Height adjustment. Product colour: Black



Display		Ergonomics		
Display diagonal *	68.6 cm (27")	On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish, Ukrainian	
Display resolution *	2560 x 1440 pixels			
HD type *	Quad HD	Plug and Play	✓	
Native aspect ratio *	16:9		LED indicators	Operation, Stand-by
Display technology *	LCD		Tilt adjustment	✓
Panel type *	VA	Power		
LED backlight	✓	Energy efficiency class (SDR) *	F	
Backlight type	W-LED	Energy efficiency class (HDR) *	Not available	
Display brightness (typical)	300 cd/m <sup>2</sup>	Energy consumption (SDR) per 1000 hours *	26 kWh	
Response time	4 ms	Power consumption (typical) *	19.6 W	
Anti-glare screen	✓	Power consumption (standby) *	0.3 W	
Screen shape *	Flat	Power consumption (off)	0.3 W	
Contrast ratio (typical) *	4000:1	Power consumption (PowerSave)	15 W	
Maximum refresh rate *	75 Hz	AC input voltage	100 - 240 V	
Viewing angle, horizontal	178°	AC input frequency	50 - 60 Hz	
Viewing angle, vertical	178°	Power supply type	Internal	
Display number of colours *	16.7 million colours	Energy efficiency scale	A to G	
Pixel pitch	0.2331 x 0.2331 mm	Operational conditions		
Pixel density	108.79 ppi	Operating temperature (T-T)	0 - 40 °C	
Horizontal scan range	30 - 114 kHz	Storage temperature (T-T)	-20 - 60 °C	
Vertical scan range	48 - 75 Hz	Operating relative humidity (H-H)	20 - 80%	
Viewable size, horizontal	59.7 cm	Operating altitude	0 - 3658 m	
Viewable size, vertical	33.6 cm	Non-operating altitude	0 - 12192 m	
Display diagonal (metric)	68.5 cm			
DDC/CI	✓			
Haze rate	25%			
Surface hardness	3H			
Colour depth	8 bit			
sRGB coverage (typical)	119%			

<b>Display</b>		<b>Packaging content</b>	
NTSC coverage (typical)	97%	Stand included	✓
Display sRGB	✓	Manual	✓
<b>Performance</b>		Bundled software	SmartControl
VESA Adaptive Sync support	✓	<b>Weight &amp; dimensions</b>	
Component video sync	Separate sync	Width (with stand)	613 mm
Flicker-free technology	✓	Depth (with stand)	205 mm
<b>Multimedia</b>		Height (with stand)	525 mm
Built-in speaker(s) *	✓	Weight (with stand)	5.6 kg
Built-in camera *	✗	Width (without stand)	613 mm
Number of speakers	2	Depth (without stand)	56 mm
<b>Design</b>		Height (without stand)	367 mm
Market positioning *	Business	Weight (without stand)	3.84 kg
Product colour *	Black	<b>Packaging data</b>	
Front bezel colour	Black	Package width	780 mm
Feet colour	Black	Package depth	161 mm
<b>Ports &amp; interfaces</b>		Package height	445 mm
Built-in USB hub *	✓	Package weight	8.2 kg
USB upstream port type	USB Type-B	<b>Sustainability</b>	
Audio output	✓	Doesn't contain	Mercury, PVC/BFR
HDCP	✓	European Product Registry for Energy Labelling (EPREL) code	1468978
HDCP version	1.4	<b>Recycling data</b>	
Charging port type	USB Type-A	Post-consumer recycled plastic	85%
<b>Ergonomics</b>		<b>Other features</b>	
VESA mounting *	✓	Exterior finish type	Textured
Panel mounting interface	100 x 100 mm	Picture enhancement	SmartImage
Cable lock slot *	✓	Recyclable packaging material	100%
Cable lock slot type	Kensington	Regulatory Approvals	CB; CE Mark; CU-EAC; EAEU RoHS; FCC Class B; ICES-003; TUV Ergo; TUV/GS
Height adjustment *	✓	EasyRead mode	✓
Height adjustment	13 cm	LowBlue mode	✓
Pivot angle	-90 - 90°	Mean time between failures (MTBF)	70000 h
Swivel angle range	-180 - 180°		
Tilt angle range	-5 - 25°		



8712581801168

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 03-APR-2024. Prints or copies of Information are only valid on the printed Publication date