

## Fujitsu PRIMERGY RX2540 M7 server Rack (2U) Intel Xeon Silver 4410Y 2 GHz 32 GB DDR5-SDRAM 900 W

**Brand :** Fujitsu **Product family:** PRIMERGY **Product code:** VFY:R2547SC020IN



Product name: RX2540 M7

- No OS
- Intel Xeon Silver 4410Y (30MB Cache, 2GHz)
- 32GB (4800MHz) DDR5-SDRAM (1 x 32)

Intel Xeon Silver 4410Y (30MB Cache, 2GHz), 32GB DDR5-SDRAM (4800MHz), LAN, 900W, No OS Fujitsu PRIMERGY RX2540 M7. Processor family: Intel Xeon Silver, Processor frequency: 2 GHz, Processor model: 4410Y. Internal memory: 32 GB, Internal memory type: DDR5-SDRAM. HDD size: 2.5". Ethernet LAN. Power supply: 900 W, Redundant power supply (RPS) support. Chassis type: Rack (2U)



Processor		Design	
Processor manufacturer *	Intel	Redundant fans support	✓
Processor family *	Intel Xeon Silver	Performance	
Processor frequency * 2	or frequency * 2 GHz or boost frequency 3.9 GHz or cores 12	Trusted Platform Module (TPM)	✓
		Trusted Platform Module (TPM)	2.0
Processor cores		version	2.0
Processor cache		Software	
Motherboard chipset	Intel C741	Operating system installed *	×
Configurable TDP-down	4.5 W		Windows Server 2022 Datacenter Windows Server 2022 Standard Windows Server 2019 Datacenter Windows Server 2019 Standard Windows Server 2019 Essentials SUSE® Linux Enterprise Server 15
Bus type	OPI		
Memory		Compatible operating systems *	
Internal memory *	32 GB		
Internal memory type *	DDR5-SDRAM		Red Hat® Enterprise Linux 8
Memory clock speed	4800 MHz	Processor special features	
Maximum internal memory *	8 TB	CPU configuration (max)	1
Storage		Intel Smart Response Technology version	1.00
HDD size	2.5"	Intel Stable Image Platform Program	0.00
Number of HDDs supported	16 ✓	(SIPP) version	0.00
RAID support *	*	Intel Secure Key Technology version	
Network		Intel TSX-NI version	0.00
Ethernet LAN	✓	Power	
Ports & interfaces		Redundant power supply (RPS) support *	✓
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	4	Power supply *	900 W
VGA (D-Sub) ports quantity	1	Power supply input voltage	100 - 240 V
Expansion slots		Power supply input frequency	50/60 Hz
PCI Express x16 (Gen 4.x) slots	1	Weight & dimensions	
Design		Width	482.2 mm
Chassis type *	Rack (2U)	Depth Height	800 mm 86.9 mm
Product colour	Black	Weight	32 kg
		Weight	32 Ng

