

Samsung LH75QBCEBGCXEN Signage Display Digital signage flat panel 190.5 cm (75") Wi-Fi 350 cd/m² 4K Ultra HD Black Tizen 16/7



Brand : Samsung

Product code: LH75QBCEBGCXEN

Product name : LH75QBCEBGCXEN

- Ultra Slim Depth
- Even bezel
- Centered VESA Holes

Crystal UHD Signage QBC, 75", 3840 x 2160, VA, 0.429x0.429mm, 16/7, 214.5 W, 1682.3 x 960.4 x 28.5 mm, 33.4 kg

Samsung LH75QBCEBGCXEN. Product design: Digital signage flat panel. Display diagonal: 190.5 cm (75"), Display resolution: 3840 x 2160 pixels, Display brightness: 350 cd/m², HD type: 4K Ultra HD. Wi-Fi. Operating hours (hours/days): 16/7. Operating system installed: Tizen. Product colour: Black

Display		Design	
Panel type	VA	VESA mounting *	✓
Display diagonal *	190.5 cm (75")	Panel mounting interface	400 x 400 mm
Display resolution *	3840 x 2160 pixels	Performance	
Display brightness *	350 cd/m ²	Purpose *	Universal
HD type *	4K Ultra HD	Operating hours (hours/days)	16/7
Response time	8 ms	HDCP	✓
Contrast ratio (typical)	4000:1	HDCP version	2.2
Dynamic contrast ratio marketing name	Mega Contrast	Power	
Viewing angle, horizontal	178°	Power consumption (typical) *	214.5 W
Viewing angle, vertical	178°	Power consumption (standby) *	0.5 W
Pixel pitch	0.429 x 0.429 mm	AC input voltage	100-240 V
Colour saturation	72%	AC input frequency	50-60 Hz
Horizontal scan range	30 - 81 kHz	Computer system	
Vertical scan range	48 - 75 Hz	Operating system installed	Tizen
Haze rate	2%	Operating system version	Tizen 7.0
RGB colour space	NTSC	Weight & dimensions	
Ports & interfaces		Display width	1682.3 mm
HDMI ports quantity *	3	Display depth	28.5 mm
HDMI version	2.0	Display height	960.4 mm
HDMI input ports quantity	3	Display weight	33.4 kg
DVI port *	✗	Packaging data	
USB port *	✓	Package width	1839 mm
USB ports quantity	2	Package depth	180 mm
Ethernet LAN *	✓	Package height	1113 mm
Ethernet LAN (RJ-45) ports	1	Package weight	43.5 kg
Wi-Fi *	✓	Packaging content	
RS-232 interface	✓	Stand included	✓
Design		Operational conditions	
Product design *	Digital signage flat panel	Operating temperature (T-T)	0 - 40 °C
Product colour *	Black	Operating relative humidity (H-H)	10 - 80%



8806094973952

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 21-NOV-2023. Prints or copies of Information are only valid on the printed Publication date