



ASUS ROG RYUJIN III 240 Processor All-in-one liquid cooler 12 cm Black 1 pc(s)

Brand : ASUS

Product code: 90RC00K0-M0UAY0

Product name : ROG RYUJIN III 240

3,5" LCD, 2x Noctua 2000 PWM 120mm

[ASUS ROG RYUJIN III 240 Processor All-in-one liquid cooler 12 cm Black 1 pc\(s\):](#)



COOLER THAN COOL

Go cooler than cool with the ROG Ryujin III. Its roomy 3.5-inch LCD screen displays live system stats or your custom artwork and animated GIFs. Underneath, an embedded fan upgraded with Axial-tech improves motherboard VRM thermals by up to 35 Celsius, and an 8th Gen Asetek pump and coldplate combine to deliver even lower CPU temperatures. Liquid is piped in through generously long braided tubing and chilled by a higher capacity radiator and two famously quiet 120 mm Noctua fans.

ASUS ROG RYUJIN III 240. Type: All-in-one liquid cooler, Fan diameter: 12 cm, Maximum airflow: 71.6 cfm, Airflow: 121.8 m³/h, Maximum air pressure: 5.53 mmH2O. Product colour: Black

Performance		Design	
Suitable location *	Processor	Number of fans	2 fan(s)
Type *	All-in-one liquid cooler	Water block material	Copper
Fan diameter	12 cm	Display type	LCD
Supported processor sockets	LGA 1150 (Socket H3), LGA 1151 (Socket H4), LGA 1155 (Socket H2), LGA 1156 (Socket H), LGA 1200 (Socket H5), LGA 1700, Socket AM4, Socket AM5	Weight & dimensions	
Minimum airflow (imperial)	21.8 cfm	Radiator width	27.9 cm
Maximum airflow	71.6 cfm	Radiator depth	12 cm
Airflow	121.8 m ³ /h	Radiator height	13 cm
Maximum air pressure	5.53 mmH2O	Tube length	40 cm
Pulse-width modulation (PWM) support	✓	Waterblock width	8.9 cm
Fan noise level (max)	29.7 dB	Waterblock depth	9.1 cm
Quantity per pack	1 pc(s)	Waterblock height	10.1 cm
Pump motor speed (min)	800 RPM	Weight	1.5 kg
Pump motor speed (max)	3600 RPM	Fan dimensions (W x D x H)	120 x 120 x 25 mm
Fan speed (min)	450 RPM	Package width	307 mm
Fan speed (max)	2000 RPM	Package depth	241 mm
Fan static pressure	3.94 mmH2O	Package height	135 mm
		Package weight	2.66 kg
Design		Packaging content	
Product colour *	Black	Mounting kit	✓
Radiator material	Aluminum	Installation instruction	✓



4711387048153

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 25-MAY-2023. Prints or copies of Information are only valid on the printed Publication date