

DELL Latitude 5440 i5-1335U Notebook 35.6 cm (14") Full HD Intel® Core™ i5 8 GB DDR4-SDRAM 256 GB SSD Wi-Fi 6E (802.11ax) Windows 11 Pro Grey

Brand : DELL

Product family: Latitude

Product code: TRVMJ

Product name : 5440

- Windows 11 Pro 64-bit

- Intel Core i5-1335U (12MB Cache)

- 35.6 cm (14") Full HD 1920 x 1080 IPS

- 8GB (3200MHz) DDR4-SDRAM (1 x 8) & 256GB SSD

Intel Core i5-1335U (12MB Cache), 8GB DDR4-SDRAM, 256GB SSD, 35.6 cm (14") Full HD 1920 x 1080 IPS, Intel Iris Xe Graphics, LAN, WLAN, Webcam, Windows 11 Pro 64-bit

DELL Latitude 5440 i5-1335U Notebook 35.6 cm (14") Full HD Intel® Core™ i5 8 GB DDR4-SDRAM 256 GB SSD Wi-Fi 6E (802.11ax) Windows 11 Pro Grey:

Work from anywhere with the world's most intelligent and secure business laptops sustainably designed for productivity on the go.

DELL Latitude 5440. Product type: Notebook, Form factor: Clamshell. Processor family: Intel® Core™ i5, Processor model: i5-1335U. Display diagonal: 35.6 cm (14"), HD type: Full HD, Display resolution: 1920 x 1080 pixels. Internal memory: 8 GB, Internal memory type: DDR4-SDRAM. Total storage capacity: 256 GB, Storage media: SSD. On-board graphics card model: Intel Iris Xe Graphics. Operating system installed: Windows 11 Pro. Product colour: Grey. Weight: 1.39 kg








Design		Network	
Product type * Product colour * Form factor * Market positioning	Notebook Grey Clamshell Business	Mobile network connection * Antenna type WLAN controller model WLAN controller manufacturer	X 2x2 Intel Wi-Fi 6E AX211 Intel
Display Display diagonal * Display resolution * Touchscreen *	35.6 cm (14") 1920 x 1080 pixels	Ethernet LAN Ethernet LAN data rates Bluetooth WWAN	✓ 10,100,1000 Mbit/s ✓ Upgradable
HD type	X Full HD	Ports & interfaces	
Panel type LED backlight Native aspect ratio Anti-glare screen Display brightness Pixel density RGB colour space Colour gamut Maximum refresh rate Contrast ratio (typical) Processor	IPS ✓ 16:9 ✓ 250 cd/m ² 157 ppi NTSC 45% 60 Hz 600:1	USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity * Ethernet LAN (RJ-45) ports HDMI ports quantity * HDMI version Thunderbolt 4 ports quantity Intel® Thunderbolt 4 Combo headphone/mic port Charging port type USB Type-C DisplayPort Alternate Mode USB Power Delivery	2 1 1 2.0 2 ✓ USB Type-C ✓
Processor manufacturer * Processor generation Processor model *	Intel 13th gen Intel® Core™ i5 i5-1335U	PowerShare Number of USB ports with PowerShare support	✓ 1
Processor family *	Intel® Core™ i5	Performance	
Efficient-core base frequency Performance-core boost frequency Processor boost frequency Processor cores	3.4 GHz 4.6 GHz 4.6 GHz 10	Ambient light sensor Keyboard Pointing device	✔ Touchpad

Processor cache typeX #8Keyboard languageFinglis Processor cache typeSmart CacheSmart CacheFinglis Processor cache typeProcessor cache typeSmart CacheSoftwareKannenic Keypad *Kannenic Keypad *Kannenic Keypad *MemoryRemory8 GBOperating system and the curseG4-bitInternal memory *18 GBOperating system languageMultilingual Information of the License includedMemory look types3200 MK2Operating system installed *Microsoft Office License includedMemory look types2.8 GBProcessor special featuresMicrosoft Office License includedMemory look types2.8 GBProcessor special featuresMicrosoft Office License includedMemory look types2.8 GGProcessor special features1.4 VMemory look types2.5 GGBattery voltage3Non-Ber CSDs installed2.5 GGBattery voltage4 Processor special featuresStorageneria5.5 GGBattery voltage4 Processor special featuresStorageneria5.5 GGBattery voltage2.0 go CallStorageneria5.5 GGBattery voltage4 Processor special featuresStorageneria5.6 GGSWSWStorageneria4.2 Adapter from voltage2.0 go CallStorageneria4.2 Adapter from voltage6.5 WStorageneria4.2 Adapter from voltage2.0 SoftwareStorageneriaMace special specia				
Process cache byeSmart CacheNumeric keynal a"XConfiguratio TDP-down12 WGortung system Architecture6 d-bitInternal memory type8 G.BOperating system languageMultingualInternal memory typeDDAR SDRAMTrial software30 day Trial offer OnlyMemory dout Speed3200 MizzDoresting system installed30 day Trial offer OnlyMemory dout Stok size1.8 G.BProcessor special featuresWindow 11 ProMemory dout Stok size1.8 G.BProcessor special featuresNumer of battery cells3Mammer Indemony4 G.BBattery copacity3 Advance1Nan-ECCVNumber of battery cells31Storage dout Stok size25 G.BBattery copacity3 Advance1Stola storage capacity25 G.BFact Arging20 advanceStola storage capacity25 G.BFact Arging20 advanceStola torage capacity25 G.BFact Arging20 advanceStola torage capacity25 G.BSoctareSoctareStola torage capacity25 G.BSoctareSoctareStola torage capacity26 G.BSoctareSoctareStola torage capacity25 G.BSoctareSoctareStola torage capacity26 G.BSoctareSoctareStola torage capacityAdvalater frequency50 SoftareNome of battery cells stokMacdity SoctareSoctareStola torage capacityAdvalater frequency30 Softare<	Processor		Keyboard	
Configurable TDP-down12 WSoftwareGeneting system architecture64-bitMemory6.8 BOperating system anchitecture64-bitInternal memory typeDDRA SDRAMTrial software30 day Trial Offer Onfice License IncludedMemory clock system3.00 MirzOperating system installed *Windows 11 ProMemory typeSD-DMMOperating system installed *Windows 11 ProMemory slock size1.x 8 GBProcessor special featuresMemory slock size3.x SO-DMMCV configuration (max)1Maximum internal memory64 GBBattery colls (max)3Mastram internal memory64 GBBattery colls (max)3Storage endarch*55 GBBattery voltage1.4 VStorage endarch*256 GBProcessor special features54 WinTotal storage endarch*256 GBPower-Storage endarch*256 GBPower-Sto InterfacePol ExpressAc dapter frapmeny65 WinSto InterfaceMirage100 - 240 V20 0Sto InterfaceMirage100 - 240 V20 0Sto InterfaceMirage20 020 0Sto InterfaceWindow20 020 0Sto InterfaceMirage20 020 0Storage<	Processor cache	12 MB	, , ,	5
Memory 6.6B Operating system anchitecture 6.4 bit Internal memory Vace 8.6B Operating system language Multingual Internal memory Vace 300 MHz 30 day Trai 0 Offer License included Memory loyou (loks speed 300 MHz 30 day Trai 0 Offer Choy Memory loyou (loks size) 1 x 8 GB Percessor special features 30 day Trai 0 Offer Choy Memory loyou (loks size) 1 x 8 GB Percessor special features 30 day Trai 0 Offer Choy Memory loyou (loks size) 1 x 8 GB Percessor special features 30 day Trai 0 Offer Choy Non-ECC 4 Number of battery cells 3 Non-ECC 5 GB Battery versige 1 1.4 V Storage media 550 Ga Battery versige 1 1.4 V Storage fracting 256 GB Percer 220 ga SSD capacity 256 GB Percer 200 of 12 SSD form factor M2 A dadpter fraquency 50/60 Hz SSD form factor M2 A dadpter fraquency 50/60 Hz SSD form factor M2 <td></td> <td></td> <td>Numeric keypad *</td> <td>×</td>			Numeric keypad *	×
Interal memory * 8 8 GB Openal system language Multilingual Interal memory type DDR-SDRAM Tails of tware and the source of the laces included ad day Trial Offer Laces included ad day Trial Software 3 200 MHz OPenaling system instale * Windows 11 Pro Memory look sizes 1 x 8 GB Processor special features * * * * * * * * * * * * * * * * * * *	Configurable TDP-down	12 W	Software	
Internal memory typeDD4. DVA Memory Circk speedDD4. SUD0 MHzTrial softwareNo. Mocostol Office License Included Memory MicroMemory form CarcoSOD0 MHzOperating system installed **Windows 11 ProMemory More Carco1 x 8 G BProcessor special features************************************	Memory		Operating system architecture	64-bit
Memory clock speed3200 MHzOperating system installedMindows 11 ProMemory layot (bits x size)1 × 8 GBProcessor special featuresMemory layot (bits x size)1 × 8 GBProcessor special featuresMemory layot (bits x size)2 × 50 DIMMCPU configuration (max)1 × 10 × 10 × 10 × 10 × 10 × 10 × 10 ×	Internal memory *	8 GB	Operating system language	Multilingual
Memory clack speed300 MHzOperating system installedWindows 11 ProMemory layout (slots x size)50-DIMMOperating system installedWindows 11 ProMemory layout (slots x size)1 × 8 GBProcessor special featuresMemory layout (slots x size)2 × 50-DIMMCPU configuration (max)1 Memory layout (slots x size)64 GBBattery colls (max)3 Non-ECC64 GBBattery colls (max)3 Non-ECC55 GBBattery colls (max)3 Storage capacity256 GBBattery voltage1 Vomber of S50s installed1Battery woltage20 goS50 capacity256 GBPower200 goS50 capacity256 GBPower200 goS50 form factorM2A Cadapter input voltage20 / 60 / 70 / 70 / 70 / 70 / 70 / 70 / 7	Internal memory type	DDR4-SDRAM	Trial software	
memory joint (sides size)J × 8 GBProcessor special featuresMemory joint (sides size)1 × 8 GBProcessor special featuresMemory joint (sides size)2 × 00000000000000000000000000000000000	Memory clock speed	3200 MHz		
Memory plotsSO-DMMCPL configuration (max)1 A displayMaximum internal memory64 GBHettrySoNon-ECCAHettrySoStorage capalty55 GBBattery voltage1.4 VTotal storage capaltySo GBBattery voltage1.4 VTotal storage capaltySo GBBattery voltage1.4 VTotal Storage capalty25 GBBattery veltage timeVSo Capacity25 GBActa dapter power (max)So GBSo Capacity25 GBActa dapter frequency50 GBSo Totar factorNAActa dapter frequency100 ACMSo Capacity3.5 CapacitySo GBSo CapacitySo CapacityActa dapter frequency100 ACMSo CapacityActa dapter frequency100 ACMOptical dari typesActa dapter frequency100 ACM <td></td> <td>SO-DIMM</td> <td>1 0)</td> <td>Windows II Pro</td>		SO-DIMM	1 0)	Windows II Pro
Maximum internal memory* Non-ECC64 GBConsummer of Nature Consumer of NaturePercent of Nature Percent of NatureNon-ECC46 GBBattery capacity (Mater)3Storage256 GBBattery voltage14 MStorage media*SDBattery voltage14 MStorage media*SDBattery voltage14 MNumber of SSDs installed1Battery voltage4 MSD interfaceFast charging20 gSSD capacity256 GBPoreSDSSD interfaceNCL SpressAC adapter frequency50 GeN H7SSD form factorM.2AC adapter frequency50 GeN H7SSD form factorM.2AC adapter frequency50 GeN H7SSD form factorM.2AC adapter frequency50 GeN H7SSD form factorM.2Cable lock slot typeVedgeCard reader integratedXSam card reader4Optical drive type*Not availableCable lock slot typeVedgeOn-baard graphics card*XSam card reader4On-baard graphics card*XSam card reader4Number of builtin speakers2Generating temperature (TT)40 65 °CSpeakers manufacturerYawesSam card reader45Speakers manufacturerYawesSam card reader45Speakers manufacturerVedgeSam card reader45Speakers manufacturerVedgeSam card reader45Speakers m			Processor special features	
Non-ECCI alteryStorageI altery capacity *54 WhStorage capacity *256 GBBattery voltage will *1.1 A VTotal storage capacity *550 GBBattery verbarge time4 hTotal SDS capacity256 GBBattery verbarge time4 hSD capacity *256 GBPeretarge time220 gSD capacity256 GBPeretarge time220 gSD capacity256 GBPeretarge time50 GBSD capacity256 GBPeretarge time50 GBSD capacityAC adapter prover voltage50 GB VSSD form factorM.2AC adapter findur voltage0.0 240 VSSD form factorM.2Cadapter findur voltage0.0 240 VSD form factorM.2Cadapter findur voltage0.0 240 VOptical drive graphics card model *NotavaliableCable lock slot typeWedgeOn-baard graphics card *4Cable lock slot typeWedgeOn-baard graphics card *4Samat card reader4On-baard graphics card *4Sorage tanger time full with Module (TPM)4Vadio systemNawsAudioOperating relative humidity (H+1)0.0 5%Speaker panalyter for minorphone2Sorage tanger tard with Module (TPM)40.6 5%Speaker panalyter for minorphone2Operating relative humidity (H+1)0.0 5%Speaker panalyter for minorphone2Operating relative humidity (H+1)0.0 5%Speaker panalyter for minorphone100 for for for for for for			CPU configuration (max)	1
StorageNumber of battery cells of Battery voltage3Total storage capacity*256 GBBattery voltage11.4 VStorage media*SDOBattery voltage time4 hStorage media*SDGBattery voltage time4 hNumber of SSDs installed1Battery voltage20 gSSD capacity256 GBPowerSSDSSD form for SSDs installedNumber of SSD form for SSDs installedAC adapter requery of SSD form for SSD form for SSD65 WSSD form for SSD form for SSDMACAC adapter frequery of SSD form for SSD50 GPA50 GPASSD form for forM2AC adapter frequery of SSD store for SSD form for ACAC adapter frequery of SSD store for SSD form for AC50 GPASSD form for for SSD form for ACM2Construct for SSD form for AC50 GPASSD form for for SSD form for ACM2Construct for SSD form for AC50 GPASSD form for ACM2Construct for SSD form for AC70 GPASSD form for ACXSamat card reader4On-board graphics card mode!Net with SSD form for AC70 GPASonader graphics card mode!*Net with SSD form for AC70 GPAAudio systemM2Poetring toreform Module (TPM)4Number of built-in speakers2Operating for Module (TPM)40 - 65 °CSpeaker power2M2Poetring toreform for Construct (T-1)9.5 SPSpeaker power2M2Poetring relative hunnikity (H+1)0.9 SPSpeaker pow			Battery	
Storage Storage capacity 256 GB Battery valage 11.4 V Total storage capacity S5D Battery vacharge time 11.4 V Total Storage media S5D Battery vacharge time 11.4 V Total Storage media S5D GB 4 Total Storage time 220 GB 220 GB SSD capacity 256 GB Power SSD tomafactor M.2 AC adapter frequency 505 (0) 7.2 SSD form factor M.2 AC adapter frequency 505 (0) 7.2 SSD form factor M.2 AC adapter input voltage 100 - 240 V Optical direk types X Cadapter frequency 505 (0) 7.2 SSD terperformance class 35 0 cons (1) 80 darging voltage 20,9,15 V Card reader integrated X Cadapter frequency Wedge Optical direk types X So adapter frequency So adapter frequency So adapter frequency Y Optical direk types X Cadapter frequency Wedge Y Optical direk types X Cadapter f		v	Number of battery cells	3
Storage mediaSSDBattery vecharge time4 hTotal SSDs capacity256 GBFast charging4Storage media1Battery vecharge time4 hSSD capacity256 GBFast charging220 gSSD capacity256 GBPower	Storage			54 Wh
Total SDs capacity256 GBFast charging/ ANumber of SDs instaled1Battery weight220 gSDs capacity256 GBPover220 gSDs instarcePCI ExpressPover50 (50 Hz)SDs form factorM.2A Cadapter requency50 (50 Hz)SDs form factorM.2A Cadapter input voltage100 - 240 VSDs performance class35Cadapter input voltage100 - 240 VCard reader integratedXSuff Calapter input voltage20,5,9,15 VCard reader integratedXCable lock slot typeVedgeDiscrete graphics card model *Not availableCable lock slot typeVedgeOn-board graphics card *XSuff Calapter readerVedgeDiscrete graphics card *XStorage tenperature (T-M)VedgeNumber of built-in speakers2Operating temperature (T-M)0 - 35 °CSpeaker spower2 WavesStorage temperature (T-M)0 - 65 °CSpeaker spower2 WavesStorage temperature (T-M)0 - 65 °CSpeaker spower2 WavesStorage temperature (T-M)0 - 55 °C <tr< td=""><td></td><td></td><td>Battery voltage</td><td>11.4 V</td></tr<>			Battery voltage	11.4 V
Number of SDs installed1Pack Larguing eight220 gSD capacity256 GBPower220 gSD interfacePCI ExpressPower65 WSD form factorM.2AC adapter frequency50/60 HzSD performance class35Cadapter input voltage20.5.9.15 VSD performance class35Cadapter input voltage20.5.9.15 VCard reader integratedXSecurityVergenceCard reader integratedNot availableCable lock slot typeWedgeOn-boad graphics card model *Not availableFingerprint readerOn-boad graphics card *XSmart card readerOn-boad graphics card *XSmart card readerAudio systemNaxxAudioTrusted Platform Module (TPM)2.0Audio systemVersion2.0Number of built-in speakers2Operating temperature (1-T)-40.65 °CSpeakers manufacturerWavesStorage temperature (1-T)-40.65 °CSpeakers power2Operating relative humidity (H+H)10.90%Built-in microphones2Operating relative humidity (H+H)10.90%Ront carrer aresolution (numeric)2.07 NPNon-operating shock110 GFront camera resolution (numeric)2.07 NPOperating shock10.66 GFront camera resolution (numeric)2.07 NPNon-operating shock10.61 GFront camera resolution (numeric)2.07 NPNon-operating shock10.61 GFront c			Battery recharge time	4 h
SD capacity256 GBDescription219 (a participation)SD interfacePCI ExpressA cadapter power65 WWMe〈 A cadapter frequency50/60 HzSD form factorM.2A Cadapter input voltage100 - 240 VSD performance class35A Cadapter input voltage100 - 240 VOptical drive type *XSecurity205,9,15 VCard reader integratedXSecurityVCard reader integratedNot availableCable lock slot typeWedgeOn-board graphics card model *Not availableCable lock slot typeVedgeOn-board graphics card model *Not availableTrusted Platform Module (TPM)VedgeOn-board graphics card model *Not availablePertineraderVedgeAudioXTrusted Platform Module (TPM)VedgeAudio systemMaxxAudioOperating temperature (T-T)0.35 °CSpeaker smanufacturerYOperating relative humidity (H+H)0.90%Built-in microphone2Operating relative humidity (H+H)0.95%Number of microphones2Operating altitude15.2 : 10668 mFront camera/Non-operating neitrity humidity (H+H)0.95%Cont camera resolution (numeric)207 MPNon-operating shock10 GFront camera resolution (numeric)207 MPNon-operating shock10 GFront camera resolution (numeric)207 MPNon-operating shock10 GFront camera resolution (numeric)207 MPOpera	1,		Fast charging	4
SD interface NMePCI ExpressPowerNMe✓ AC adapter power55% (%)SSD form factorM.2AC adapter frequency50% (%)SSD performance class35AC adapter input voltage100 - 240 VOptical drive type*✓VStoraging voltage20,5,9,15 VCard erader integrated✓Storaging voltage20,5,9,15 VCarder integrated✓Cable lock slot typeWedgeDiscrete graphics card model*Not availableCable lock slot typeWedgeOn-board graphics card*✓Cable lock slot type✓On-board graphics card*✓Tusted Platform Module (TPM)On-board graphics card*✓Tusted Platform Module (TPM)2,0AutioMaxXudioOperating temperature (T-T)0.35 °CSpeakers manufacturerZOperating temperature (T-T)40-65 °CSpeakers manufacturerZOperating temperature (T-T)0.95%Number of microphones2Operating relative humidity (H+H)0.90%Number of microphones2Operating speakers10.0 GFront camera resolution (numeric)2,07 MPNon-operating shock10.0 GFront camera resolution (numeric)2,07 MPNon-operating shock10.0 GFront camera resolution (numeric)2,07 MPNon-operating vibration3.6 GFront camera resolution (numeric)3,05 N10.0 G10.0 GFront camera resolution (numeric)3,05 N10.0 GFront c			Battery weight	220 g
NMeAC adapter power65 WSD form factorM.2AC adapter frequency100 - 240 VSD performance class3AC adapter input voltage100 - 240 VSD performance classSACadapter input voltage100 - 240 VCarl reader integratedXSecurity205,915 VGraphicsNot availableCable lock slot typeVDiscrete graphics cardNot availableFingerprint reader4On-board graphics cardMaxAudioFingerprint reader4Discrete graphics card modelItel Iris Xe GraphicsTrusted Platform Module (TPM)4AudioMaxAudioTrusted Platform Module (TPM)2Audio systemMaxAudioOperating temperature (T-T)0.3 S °CSpeaker power2Operating temperature (T-T)0.4 S °CSpeaker power2Operating temperature (T-T)0.4 S °CSpeaker power2Operating temperature (T-T)0.9 S °CSumber of microphone2Operating temperature (T-T)0.9 S °CNumber of microphone2Operating tento humidity (H+1)0.90%Speaker power2Operating tento humidity (H-1)0.9 S °CSpeaker power2Operating shock10.6 G °CSpeaker power2Operating shock10.6 G °CSpeaker power200perating shock10.6 G °CSpeaker power200.9 S °C0.6 G °CSpeaker power20.0 S °C0.0 S °C0.6 G °CSpeaker po	1 3		Power	
SSD form factorM.2AC adapter frequency50/60 HzSSD performance class35AC adapter input voltage100 - 240 VOptical drive type *XUSB charging voltage100 - 240 VCard reader integratedXSecurityVelocityGraphicsXSecurityXDiscrete graphics card model *Not availableCable lock slot typeVedgeOn-board graphics card *XSmart card readerVedgeOn-board graphics card *XTrusted Platform Module (TPM)XNo-board graphics card *XTrusted Platform Module (TPM)AcalAduidMaxAudioPertainet module (TPM)0.35 °CAudio systemMaxAudioStorage relative humidity (H+I)0.90%Speaker power2WOperating relative humidity (H+I)0.90%Number of huirin speakers2Operating relative humidity (H+I)0.90%Speaker power2WOperating relative humidity (H+I)0.90%Number of microphones2Operating altitude15.2 · 3048 mNumber of microphones2.01% IBO pixelsOperating shock10.6Front camera resolution (numeric)2.07 NPNon-operating shock10.6Front camera resolution (numeric)2.01% IBO pixelsOperating vibration0.66 GFront camera resolution (numeric)2.01% IBO pixelsOperating vibration10.6Front camera resolution (numeric)2.01% IBO pixelsOperating vibration10.6Front camera resolutio		I	AC adapter power	65 W
SD performance class35AC adapter input voltage100 - 240 VOptical drive type *XYES charging voltage20,5,9,15 VCardede rintegratedXCarding voltageVoltageGraphicsXCalle lock slot typeWedgeDiscrete graphics card model *NotavailableCable lock slot typeWedgeOn-board graphics card *XCable lock slot typeVoltageDiscrete graphics card *XTrusted Platform Module (TPM)QOn-board graphics card *XTrusted Platform Module (TPM)QAudio systemMaxxAudioTrusted Platform Module (TPM)QNumber of built-in speakers2Poerting temperature (T-T)40 - 65 °CSpeaker power2 WOperating relative humidity (H-H)10 - 90%Built-in microphone2Operating relative humidity (H-H)10 - 90%Number of incrophones2Operating relative humidity (H-H)10 - 90%Front camera resolution (nume)120 × 1080 pixelsOperating relative humidity (H-H)10 - 60Front camera resolution (nume)120 × 1080 pixelsOperating vibration13 - 60Video capturing speed30 × 1080 pixels <t< td=""><td></td><td></td><td>AC adapter frequency</td><td>50/60 Hz</td></t<>			AC adapter frequency	50/60 Hz
Optical drive type *KUSB charging voltage20.5.9.15 VCard reader integratedKSecurityGraphicsNot availableCable lock slot typeWedgeDiscrete graphics card model *Not availableCable lock slot typeWedgeOn-board graphics card *✓Smart card reader✓Discrete graphics card model *KSmart card reader✓On-board graphics card model *Intel Iris Xe GraphicsTrusted Platform Module (TPM)✓On-board graphics card model *MaxxAudio Operational conditions Operating temperature (T-T)0.35 °CAudio systemMaxxAudioOperating relative humidity (H-H)0.95 °COperating relative humidity (H-H)0.95 °CSpeaker power2WOperating relative humidity (H-H)10.90 °CStorage relative humidity (H-H)0.95 °CNumber of microphones2VOperating altitude15.2 · 3048 mStorage relative humidity (H-H)10.90 °CBuilt-in microphones2Operating shock110 GStorage relative humidity (H-H)0.95 %Number of microphones2Non-operating shock150 CStorage relative humidity (H-H)0.95 %Front camera✓Non-operating shock110 GStorage relative humidity (H-H)0.95 %Front camera✓Non-operating shock160 GStorage relative humidity (H-H)0.95 %Front camera resolution (numeric)1.90 Non-operating shock160 GStorage relative humidity (H-H)0.92 N<			AC adapter input voltage	100 - 240 V
Card reader integratedKSecurityGraphicsNot availableCable lock slot typeVedgeDiscrete graphics card model *Not availableCable lock slot typeVedgeDiscrete graphics card *XSmart card readerZOn-board graphics card model *Intel Iris Xe GraphicsTusted Platform Module (TPM)ZOn-board graphics card *XTusted Platform Module (TPM)ZAutioMaxXudioOperating temperature (T-T)0.35 °CSpeaker power2Operating relative humidity (H+H)10.90%Speaker power2Operating relative humidity (H+H)10.90%Number of built-in speakers2Operating relative humidity (H+H)10.90%Speaker power2Operating relative humidity (H+H)10.90%Number of microphones2Operating relative humidity (H+H)10.90%Number of microphones2Non-operating altitude15.2 · 3048 mFront camera2.01Non-operating shock110 GFront camera resolution1.902 × 1080 pixelsOperating ubration0.66 GFront camera resolution (numerities)1.902 × 1080 pixelsOperating vibration0.66 GFront camera resolution (speakers3.016 × 1000	•		USB charging voltage	20,5,9,15 V
Discrete graphics card model * Not available Addite fingerprint reader 4 (Addite fingerprint reader) 4 (Addite fingerprint module (TPM) 4 (Addite fingerprint mod			Security	
Discrete graphics card model * Not available Addite fingerprint reader 4 (Addite fingerprint reader) 4 (Addite fingerprint module (TPM) 4 (Addite fingerprint mod	Graphics		Cable lock slot	1
Discrete graphics card */ ConvolutionFingerprint reader/ ConvolutionDiscrete graphics card *XSmart card reader/Discrete graphics card *XSmart card reader/AudioTrusted Platform Module (TPM)/Audio systemMaxxAudioTrusted Platform Module (TPM)/Audio systemMaxxAudioOperating temperature (T-T)0 - 35 °CSpeaker power2 WOperating temperature (T-T)-40 - 65 °CSpeaker power2 WOperating relative humidity (H-H)10 - 90%Built-in microphone2Storage temperature (T-T)-95%Number of microphones2Operating altitude-15.2 - 3048 mNumber of microphones2Non-operating altitude-15.2 - 10668 mFront camera/Operating shock110 GFront camera resolution (numeric)2.07 MPNon-operating vibration0.66 GFront camera resolution (numeric)1.920 x 1080 pixelsOperating vibration0.66 GFront camera resolution (numeric)3 of psWeight & dimension3 clu 4 mmInfared (IR) camera/Wieli & dimension21.1 mmPrivacy camera/Privacy shutterHeight (front)1.91 cmPrivacy typeWi-Fi 6 (802.11ax)Weight *1.3 of Wieli Kaing (S02.11b)Wi-Fi standard *Wi-Fi 6 (802.11ax)Weight *3.9 kg		Notavailable		
Discrete graphics card model*XSmart card readerXOn-board graphics card model*Intel Iris Xe GraphicsTrusted Platform Module (TPM)XAudioTrusted Platform Module (TPM)X.0Audio systemMaxxAudioDerating temperature (T-T)0.35 °CNumber of built-in speakers2Operating temperature (T-T)40 · 65 °CSpeakers manufacturerWavesStorage temperature (T-T)40 · 65 °CSpeaker power2Operating relative humidity (H-H)10 · 90%Built-in microphone2Operating altitude0 · 95%Number of microphones2Operating altitude0.52. · 2048 mCamera✓Operating altitude0.52. · 20668 mFront camera resolution (numeric)2.07 MPOperating shock110 GFront camera resolution (numeric)1920 x 1080 pixelsOperating vibration0.66 GFront camera HD typeFull HDNon-operating vibration3.6 GVideo capturing speed30 fpsWith32.14 mmPrivacy tamera✓With1.91 cmPrivacy tamera✓Pethic & dimensionsPrivacy tamera✓Pethic & dimensionsPrivacy tamera✓With (Field (IC) (In) (With)3.14 cmPrivacy tamera✓Piter (Field (IC) (In) (With)1.91 cmPrivacy tamera✓Piter (Field (IC) (In) (With)1.91 cmPrivacy tamera✓Piter (Field (IC) (In) (With)1.91 cmPrivacy tamera✓Piter (Field				1
On-board graphics card model* Intel Iris Xe Graphics Trusted Platform Module (TPM) version Image Platform (T) version Image Platform (T) version<			Smart card reader	1
AudioTrusted Platform Module (TPM) version2.0Audio systemMaxxAudio Operational conditions Number of built-in speakers2Operating temperature (T-T)0 - 35 °CSpeakers manufacturerWavesStorage temperature (T-T)-40 - 65 °CSpeaker power2 WOperating relative humidity (H-H)10 - 90%Built-in microphoneImage temperature (T-T)-95%Number of microphones2Operating relative humidity (H-H)0 - 95%Number of microphones2Operating altitude-5.2 - 3048 mCameraImage relative humidity (H-H)15.2 - 10668 m-15.2 - 10668 mFront cameraImage relative humidity (H-H)10.90%-15.2 - 10668 mFront cameraImage relative humidity (H-H)10.90%-15.2 - 10668 mFront camera resolution (numeric)2.07 MPNon-operating altitude-15.2 - 10668 mFront camera resolution (numeric)1.02 nto 1080 pixelsOperating vibration1.60 GFront camera resolution (numeric)1.92 nto 1080 pixelsOperating vibration1.3 GVideo capturing speed30 fpsImage relative humidity and the site of the			Trusted Platform Module (TPM)	4
Audio system MaxxAudio Operation conditions Number of built-in speakers 2 Operating temperature (T-T) 0 - 35 °C Speaker smanufacturer Waves Storage temperature (T-T) -40 - 65 °C Speaker power 2 W Operating temperature (T-T) -0 - 90% Built-in microphone ✓ Operating relative humidity (H-H) 0 - 90% Number of microphones 2 Operating altitude 0 - 95% Number of microphones 2 Non-operating altitude -15.2 - 3048 m Camera ✓ Operating shock 110 G Front camera ✓ Operating shock 10.0 G Front camera resolution (numeric) 2.07 MP Non-operating shock 160 G Front camera resolution (numeric) 2.07 MP Non-operating vibration 1.3 G Video capturing speed 30 fps Meight & dimensions 1.3 G Video capturing speed 30 fps Peth 212 mm Privacy shutter Pilki (front) 1.91 cm 1.91 cm Privacy type Privacy shutter <t< td=""><td></td><td></td><td></td><td>2.0</td></t<>				2.0
Number of built-in speakers2Operational contitionsSpeakers manufacturerWavesOperating temperature (T-T)0 - 35 °CSpeaker power2 WStorage temperature (T-T)-40 - 65 °CBuilt-in microphone✓Operating relative humidity (H-H)10 - 90%Number of microphones2Operating relative humidity (H-H)0 - 95%Number of microphones2Operating relative humidity (H-H)0 - 95%Number of microphones2Operating altitude-15.2 - 3048 mNumber of microphones2Operating altitude-15.2 - 10668 mFront camera✓Operating shock110 GFront camera resolution (numeric)2.07 MPNon-operating shock110 GFront camera resolution1920 x 1080 pixelsOperating vibration0.66 GFront camera resolution1920 x 1080 pixelsOperating vibration1.3 GVideo capturing speed30 fpsWeight & dimensions110 GInfrared (IR) camera✓Width321.4 mmPrivacy camera✓Peth1.91 cmPrivacy camera✓Peth1.91 cmPrivacy typePrivacy shutterHeight (front)1.91 cmNerifi 5 (802.11ac), 802.11b, 802.11ac), 802.11b, 802.11ac), Wi-Fi 6 (802.11ac), 802.11b, 802.11ac), Wi-Fi 6 (802.11ac), 802.11b, 802.11ac), Wi-Fi 6 (802.11ac), 802.11b, 802.11ac), 802.11b, 802.11ac), 802.11b, 802.11ac), 802.11b, 802.11ac), 802.11b, 802.11ac), 802.11b, 802.11ac), 802.11b, 802.11ac), 802.11b, 802.11ac), 802.11b, 802.11ac), 802.11b, <b< td=""><td></td><td>Maxwaudia</td><td>version</td><td></td></b<>		Maxwaudia	version	
Speakers manufacturerWavesOperating temperature (T-T)0 - 35 °CSpeaker power2 WStorage temperature (T-T)-40 - 65 °CBuilt-in microphone✓Operating relative humidity (H-H)10 - 90%Number of microphones2Operating altivule humidity (H-H)0 - 95%Number of microphones2Operating altivule-15.2 - 3048 mCamera✓Operating altivule-15.2 - 10668 mFront camera✓Operating shock110 GFront camera resolution (numeric)2.07 MPNon-operating shock160 GFront camera resolution1920 x 1080 pixelsOperating vibration0.66 GFront camera HD typeFull HDNon-operating vibration1.3 GVideo capturing speed30 fpsWeight & dimensions21.4 mmPrivacy camera✓Privacy shutter1.91 cmPrivacy typePrivacy shutterHeight (front)1.91 cmNetworkVi-Fi 5 (802.11ac), 802.11b,Weight *1.39 kgWi-Fi standard's802.11n, Wi-Fi 4 (802.11n), Wi-Fi 6Packaging content	-		Operational conditions	
Speaker power2 WStorage temperature (1-1)40 - 65 °CBuilt-in microphoneVOperating relative humidity (H-H)10 - 90%Number of microphones2Operating altive humidity (H-H)0 - 95%CameraVNon-operating altivude-15.2 - 3048 mFront camera✓Operating shock110 GFront camera resolution (numeric)2.07 MPNon-operating shock160 GFront camera resolution (numeric)1920 x 1080 pixelsOperating vibration0.66 GFront camera HD typeFull HDNon-operating vibration1.3 GVideo capturing speed30 fpsWeight & dimensions21.4 mmPrivacy camera✓Width321.4 mmPrivacy camera✓Depth212 mmPrivacy typePrivacy shutterHeight (front)1.91 cmRetworkWi-Fi 5 (802.11ac), 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 68Packaging contentWi-Fi standardsS02.11g, Wi-Fi 4 (802.11n), Wi-Fi 68Packaging content	•		Operating temperature (T-T)	0 - 35 °C
Built-in microphone✓Operating relative humidity (H-H)10 - 90%Built-in microphones2Storage relative humidity (H-H)0 - 95%Number of microphones2Operating altitude-15.2 - 3048 mCamera✓Non-operating altitude-15.2 - 10668 mFront camera✓Operating shock110 GFront camera resolution (numeric)2.07 MPNon-operating shock160 GFront camera resolution (numeric)1920 x 1080 pixelsOperating vibration0.66 GFront camera HD typeFull HDNon-operating vibration1.3 GVideo capturing speed30 fpsWeight & dimensionsVidhhInfrared (IR) camera✓Video spituterVidhh321.4 mmPrivacy camera✓Privacy shutterHeight (front)1.91 cmPrivacy typePrivacy shutterHeight (rear)2.1 cmTop Wi-Fi standard *Wi-Fi 5 (802.11ac), 802.11b, Wi-Fi 6 (802.11n), Wi-Fi 6 (802	•		Storage temperature (T-T)	-40 - 65 °C
Number of microphones2Storage relative humidity (H-H)0 - 95%CameraCameraOperating altitude-15.2 - 3048 mFront cameraImage: Compariting altitude-15.2 - 10668 mFront cameraImage: Compariting altitude-15.2 - 10668 mFront camera resolution (numeric)2.07 MPOperating shock100 GFront camera resolution (numeric)1.920 x 1080 pixelsOperating vibration0.66 GFront camera HD typeFull HDNon-operating vibration0.66 GVideo capturing speed30 fpsMeight & dimensions321.4 mmInfrared (IR) cameraImage: Comparities and the store and t				
CameraOperating altitude-15.2 - 3048 mCameraNon-operating altitude-15.2 - 10668 mFront cameraImage: Compariting altitude-15.2 - 10668 mFront camera resolution (numeric)2.07 MPNon-operating shock100 GFront camera resolution1920 x 1080 pixelsOperating vibration0.66 GFront camera resolution1920 x 1080 pixelsOperating vibration0.66 GFront camera HD typeFull HDNon-operating vibration1.3 GVideo capturing speed30 fpsWeight & dimensions21.4 mmPrivacy cameraImage: Comparition with the standards21.4 mmPrivacy typePrivacy shutterDepth21.2 mmHeight (rear)1.91 cm2.1 cmTop Wi-Fi standard *Wi-Fi 5 (802.11ac), 802.11b, 802.11b, 802.11b, 802.11b, 802.11b, 802.11b, 802.11p, Wi-Fi 4 (802.11n), Wi-Fi 6Packaging content	•		5 , , , ,	
Front cameraImplementation10.0 cmFront camera resolution (numeric)2.07 MPNon-operating shock160 GFront camera resolution1920 x 1080 pixelsOperating vibration0.66 GFront camera HD typeFull HDNon-operating vibration1.3 GVideo capturing speed30 fpsWeight & dimensions1.3 GInfrared (IR) cameraImplementationVideo capturing speed30 fpsVideo capturing vibration321.4 mmPrivacy cameraImplementationPrivacy shutterDepth212 mm120 mmPrivacy typePrivacy shutterHeight (front)1.91 cm1.91 cmHeight (rear)2.1 cm2.1 cm1.39 kgWi-Fi standard *Wi-Fi 5 (802.11ac), 802.111b, 802.111b, Wi-Fi 6EPackaging contentPackaging content	·			
Front camera resolution (numeric)2.07 MPNon-operating shock160 GFront camera resolution1920 x 1080 pixelsOperating vibration0.66 GFront camera HD typeFull HDNon-operating vibration1.3 GVideo capturing speed30 fpsWeight & dimensionsInfrared (IR) cameraImprove function321.4 mmPrivacy cameraImprove functionDepth321.4 mmPrivacy typePrivacy shutterDepth1.91 cmNetworkImprove functionHeight (rear)Top Wi-Fi standard *Wi-Fi 5 (802.11ac), 802.11b, 802.11b, 802.11b, 802.11b, 802.11b, 802.11b, Wi-Fi 4 (802.11n), Wi-Fi 6Packaging content				
Front camera resolution1920 x 1080 pixelsOperating vibration0.66 GFront camera HD typeFull HDNon-operating vibration1.3 GVideo capturing speed30 fpsWeight & dimensions1.3 GInfrared (IR) cameraVideo capturing speed321.4 mmPrivacy cameraDepth321.4 mmPrivacy typePrivacy shutterDepth212 mmNetwork1.91 cmHeight (front)1.91 cmTop Wi-Fi standard *Wi-Fi 6E (802.11ac), 802.11b, 802				
Front camera HD typeFull HDNon-operating vibration1.3 GVideo capturing speed30 fpsWeight & dimensionsInfrared (IR) camera✓Width321.4 mmPrivacy camera✓Depth212 mmPrivacy typePrivacy shutterHeight (front)1.91 cmNetworkVi-Fi 6E (802.11ax)Weight *2.1 cmYui-Fi standard *Wi-Fi 5 (802.11ac), 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 6EPackaging content				
Video capturing speed30 fpsWeight & dimensionsInfrared (IR) camera✓Width321.4 mmPrivacy camera✓Depth212 mmPrivacy typePrivacy shutterHeight (front)1.91 cmNetworkVi-Fi 6E (802.11ax)Weight *2.1 cmTop Wi-Fi standard *Wi-Fi 5 (802.11ac), 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 6EPackaging content		•	1 5	
Infrared (IR) cameraWeight & uniensionsPrivacy cameraWidth321.4 mmPrivacy typePrivacy shutterDepth212 mmNetworkHeight (front)1.91 cmTop Wi-Fi standard *Wi-Fi 6E (802.11ax)Weight *2.1 cmWi-Fi 5 (802.11ac), 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 6EPackaging contentPackaging content				1.5 0
Privacy cameraVWidth321.4 mmPrivacy typePrivacy shutterDepth212 mmNetworkLeight (front)1.91 cmTop Wi-Fi standard *Wi-Fi 6E (802.11ax)Weight *2.1 cmWi-Fi 5 (802.11ac), 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 6EPackaging contentPackaging content			-	
Privacy typePrivacy shutterDepth212 mmNetworkLeight (front)1.91 cmTop Wi-Fi standard *Wi-Fi 6E (802.11ax)Weight *2.1 cmWi-Fi 5 (802.11ac), 802.11b, Wi-Fi standardsB02.11g, Wi-Fi 4 (802.11n), Wi-Fi 6EPackaging contentPackaging content		1		
Network Height (front) 1.91 cm Top Wi-Fi standard * Wi-Fi 6E (802.11ax) Weight * 2.1 cm Wi-Fi 5 (802.11ac), 802.11b, Weight * 1.39 kg Wi-Fi standards 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 6E Packaging content		Privacy shutter		
Top Wi-Fi standard * Wi-Fi 6E (802.11ax) Weight * 1.39 kg Wi-Fi 5 (802.11ac), 802.11b, Wi-Fi 5 (802.11ac), 802.11b, Packaging content		-	-	
Wi-Fi 5 (802.11ac), 802.11b, Packaging content Wi-Fi standards 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 6E Packaging content		Wi-Fi 6F (802 11ax)	u	
Wi-Fi standards 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 6E			-	1.55 NY
(802.11ax) Cables included AC	Wi-Fi standards	802.11g, Wi-Fi 4 (802.11n), Wi-Fi 6E		
			Cables included	AC



5397184801444

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.