

Epson EB-L570U data projector 5200 ANSI lumens 3LCD WUXGA (1920x1200) Black, White

Brand : Epson **Product code:** V11HA98080

Product name: EB-L570U

3LCD, 0.67", WUXGA, 5200 lumens, 16:10, speaker 10 W, 8.3 kg

Epson EB-L570U. Projector brightness: 5200 ANSI lumens, Projection technology: 3LCD, Projector native resolution: WUXGA (1920x1200). Light source type: Laser, Service life of light source: 20000 h, Service life of light source (economic mode): 30000 h. Focus: Manual, Focal length range: 20 - 31.8 mm, Aperture range (F-F): 1.5 - 1.7. Serial interface type: RS-232C. Noise level: 31 dB, Noise level (economic mode): 23 dB, High Dynamic Range (HDR) technology: High Dynamic Range 10 (HDR10)



iiin	~55	-	-	
OW	ENSO			
_				1
				-

Projector		Network	
Screen size compatibility *	1270 - 12700 mm (50 - 500")	Ethernet LAN *	×
Projection distance 1.44 - 23.84 m Projection distance (wide) 1.4 - 14.8 m Projection distance (tele) 2.4 - 23.8 m Projector brightness * 5200 ANSI lumens Projection technology * 3LCD Projector native resolution * WUXGA (1920x1200)	1.44 - 23.84 m	Wi-Fi *	✓
	Storage		
		Card reader integrated *	×
		Features	
	WUXGA (1920x1200)	Interactive *	×
Contrast ratio (typical) *	2500000:1	Noise level (economic mode)	23 dB
Native aspect ratio *	16:10	Noise level *	31 dB
Number of colours Keystone correction, horizontal	1.07 billion colours -30 - 30°	High Dynamic Range (HDR) supported	✓
Keystone correction, vertical	-30 - 30°	High Dynamic Range (HDR) technology	High Dynamic Range 10 (HDR10)
Matrix size	1.7 cm (0.67")	Multimedia	
Light source		Built-in speaker(s) *	√
Light source type *	Laser	RMS rated power	10 W
Service life of light source * Service life of light source	20000 h	Design	
(economic mode)	30000 h	Market positioning *	Business
Lens system		Product colour *	Black, White
Focus *	Manual	Power	
. 0000		. •	
Focal length range	20 - 31.8 mm	Power source *	AC
Focal length range Aperture range (F-F)	20 - 31.8 mm 1.5 - 1.7		AC 201 W
Focal length range Aperture range (F-F) Zoom capability	20 - 31.8 mm 1.5 - 1.7	Power source * Power consumption (typical) * Power consumption (standby) *	201 W 2 W
Focal length range Aperture range (F-F) Zoom capability Zoom type	20 - 31.8 mm 1.5 - 1.7 ✓ Manual	Power source * Power consumption (typical) * Power consumption (standby) * Power consumption (max)	201 W
Focal length range Aperture range (F-F) Zoom capability	20 - 31.8 mm 1.5 - 1.7	Power source * Power consumption (typical) * Power consumption (standby) *	201 W 2 W
Focal length range Aperture range (F-F) Zoom capability Zoom type Throw ratio	20 - 31.8 mm 1.5 - 1.7 ✓ Manual 1.35 - 2.20:1	Power source * Power consumption (typical) * Power consumption (standby) * Power consumption (max) Power consumption (economy	201 W 2 W 260 W
Focal length range Aperture range (F-F) Zoom capability Zoom type Throw ratio Horizontal lens shift range	20 - 31.8 mm 1.5 - 1.7 ✓ Manual 1.35 - 2.20:1 -20 - 20%	Power source * Power consumption (typical) * Power consumption (standby) * Power consumption (max) Power consumption (economy mode)	201 W 2 W 260 W 199 W
Focal length range Aperture range (F-F) Zoom capability Zoom type Throw ratio Horizontal lens shift range Vertical lens shift range	20 - 31.8 mm 1.5 - 1.7 ✓ Manual 1.35 - 2.20:1 -20 - 20%	Power source * Power consumption (typical) * Power consumption (standby) * Power consumption (max) Power consumption (economy mode) AC input frequency	201 W 2 W 260 W 199 W 50/60 Hz
Focal length range Aperture range (F-F) Zoom capability Zoom type Throw ratio Horizontal lens shift range Vertical lens shift range	20 - 31.8 mm 1.5 - 1.7 Manual 1.35 - 2.20:1 -20 - 20% -50 - 50%	Power source * Power consumption (typical) * Power consumption (standby) * Power consumption (max) Power consumption (economy mode) AC input frequency AC adapter output voltage	201 W 2 W 260 W 199 W 50/60 Hz
Focal length range Aperture range (F-F) Zoom capability Zoom type Throw ratio Horizontal lens shift range Vertical lens shift range Video Analog signal format system *	20 - 31.8 mm 1.5 - 1.7 ✓ Manual 1.35 - 2.20:1 -20 - 20% -50 - 50% Not supported	Power source * Power consumption (typical) * Power consumption (standby) * Power consumption (max) Power consumption (economy mode) AC input frequency AC adapter output voltage Operational conditions	201 W 2 W 260 W 199 W 50/60 Hz 100 - 240 V
Focal length range Aperture range (F-F) Zoom capability Zoom type Throw ratio Horizontal lens shift range Vertical lens shift range Video Analog signal format system * Full HD *	20 - 31.8 mm 1.5 - 1.7 Manual 1.35 - 2.20:1 -20 - 20% -50 - 50% Not supported	Power source * Power consumption (typical) * Power consumption (standby) * Power consumption (max) Power consumption (economy mode) AC input frequency AC adapter output voltage Operational conditions Storage temperature (T-T)	201 W 2 W 260 W 199 W 50/60 Hz 100 - 240 V
Focal length range Aperture range (F-F) Zoom capability Zoom type Throw ratio Horizontal lens shift range Vertical lens shift range Video Analog signal format system * Full HD * 3D *	20 - 31.8 mm 1.5 - 1.7 Manual 1.35 - 2.20:1 -20 - 20% -50 - 50% Not supported	Power source * Power consumption (typical) * Power consumption (standby) * Power consumption (max) Power consumption (economy mode) AC input frequency AC adapter output voltage Operational conditions Storage temperature (T-T) Operating relative humidity (H-H)	201 W 2 W 260 W 199 W 50/60 Hz 100 - 240 V -10 - 60 °C 20 - 80%
Focal length range Aperture range (F-F) Zoom capability Zoom type Throw ratio Horizontal lens shift range Vertical lens shift range Video Analog signal format system * Full HD * 3D * Ports & interfaces	20 - 31.8 mm 1.5 - 1.7 Manual 1.35 - 2.20:1 -20 - 20% -50 - 50% Not supported X	Power source * Power consumption (typical) * Power consumption (standby) * Power consumption (max) Power consumption (economy mode) AC input frequency AC adapter output voltage Operational conditions Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	201 W 2 W 260 W 199 W 50/60 Hz 100 - 240 V -10 - 60 °C 20 - 80%
Focal length range Aperture range (F-F) Zoom capability Zoom type Throw ratio Horizontal lens shift range Vertical lens shift range Video Analog signal format system * Full HD * 3D * Ports & interfaces HDBaseT port USB 2.0 ports quantity * USB 2.0 Type-A ports quantity	20 - 31.8 mm 1.5 - 1.7 Manual 1.35 - 2.20:1 -20 - 20% -50 - 50% Not supported	Power source * Power consumption (typical) * Power consumption (standby) * Power consumption (max) Power consumption (economy mode) AC input frequency AC adapter output voltage Operational conditions Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Weight & dimensions Width Depth	201 W 2 W 260 W 199 W 50/60 Hz 100 - 240 V -10 - 60 °C 20 - 80% 10 - 90% 440 mm 304 mm
Focal length range Aperture range (F-F) Zoom capability Zoom type Throw ratio Horizontal lens shift range Vertical lens shift range Video Analog signal format system * Full HD * 3D * Ports & interfaces HDBaseT port USB 2.0 ports quantity * USB 2.0 Type-A ports quantity USB 2.0 Type-B ports quantity	20 - 31.8 mm 1.5 - 1.7 Manual 1.35 - 2.20:1 -20 - 20% -50 - 50% Not supported X 2 1 1	Power source * Power consumption (typical) * Power consumption (standby) * Power consumption (max) Power consumption (economy mode) AC input frequency AC adapter output voltage Operational conditions Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Weight & dimensions Width Depth Height	201 W 2 W 260 W 199 W 50/60 Hz 100 - 240 V -10 - 60 °C 20 - 80% 10 - 90% 440 mm 304 mm 122 mm
Focal length range Aperture range (F-F) Zoom capability Zoom type Throw ratio Horizontal lens shift range Vertical lens shift range Video Analog signal format system * Full HD * 3D * Ports & interfaces HDBaseT port USB 2.0 ports quantity * USB 2.0 Type-A ports quantity USB 2.0 Type-B ports quantity Serial interface type *	20 - 31.8 mm 1.5 - 1.7 Manual 1.35 - 2.20:1 -20 - 20% -50 - 50% Not supported X 2 1 1 RS-232C	Power source * Power consumption (typical) * Power consumption (standby) * Power consumption (max) Power consumption (economy mode) AC input frequency AC adapter output voltage Operational conditions Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Weight & dimensions Width Depth Height Weight *	201 W 2 W 260 W 199 W 50/60 Hz 100 - 240 V -10 - 60 °C 20 - 80% 10 - 90% 440 mm 304 mm
Focal length range Aperture range (F-F) Zoom capability Zoom type Throw ratio Horizontal lens shift range Vertical lens shift range Video Analog signal format system * Full HD * 3D * Ports & interfaces HDBaseT port USB 2.0 ports quantity * USB 2.0 Type-A ports quantity USB 2.0 Type-B ports quantity	20 - 31.8 mm 1.5 - 1.7 Manual 1.35 - 2.20:1 -20 - 20% -50 - 50% Not supported X 2 1 1	Power source * Power consumption (typical) * Power consumption (standby) * Power consumption (max) Power consumption (economy mode) AC input frequency AC adapter output voltage Operational conditions Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Weight & dimensions Width Depth Height	201 W 2 W 260 W 199 W 50/60 Hz 100 - 240 V -10 - 60 °C 20 - 80% 10 - 90% 440 mm 304 mm 122 mm

Packaging content

Batteries included ✓
Cables included AC

