

## Samsung LH37SHCEBGBXEN Signage Display Panorama design 94 cm (37") LCD Wi-Fi 700 cd/m<sup>2</sup> Black Tizen 7.0 24/7

**Brand :** Samsung

**Product code:** LH37SHCEBGBXEN

**Product name :** LH37SHCEBGBXEN



Samsung LH37SHCEBGBXEN. Product design: Panorama design. Display diagonal: 94 cm (37"), Display technology: LCD, Display resolution: 1920 x 540 pixels, Display brightness: 700 cd/m<sup>2</sup>. Wi-Fi. Operating hours (hours/days): 24/7. Operating system installed: Tizen 7.0. Product colour: Black



Display		Design	
Panel type	VA	Bezel width (bottom)	9.8 mm
Display diagonal *	94 cm (37")	Bezel width (side)	7.9 mm
Display technology *	LCD	Bezel width (top)	9.8 mm
Display resolution *	1920 x 540 pixels	Anti-glare screen	✓
Display brightness *	700 cd/m <sup>2</sup>	Mounting type	Wall
Touchscreen *	✗	<b>Performance</b>	
Native aspect ratio	16:4.5	Purpose *	Universal
Response time	8 ms	Operating hours (hours/days)	24/7
Contrast ratio (typical)	4000:1	HDCP	✓
Dynamic contrast ratio marketing name	Mega Contrast	HDCP version	2.2
Viewing angle, horizontal	178°	<b>Power</b>	
Viewing angle, vertical	178°	Power consumption (typical) *	77 W
Pixel pitch	0.47 x 0.47 mm	Power consumption (sleep)	0.5 W
Display diagonal (metric)	94 cm	AC input voltage	100 - 240 V
Horizontal scan range	33.6 - 36.6 kHz	AC input frequency	50 - 60 Hz
Vertical scan range	47 - 63 Hz	Energy efficiency scale	A to G
Haze rate	28%	<b>Computer system</b>	
Colour gamut	72%	Internal storage capacity	8 GB
<b>Ports &amp; interfaces</b>		Operating system installed	Tizen 7.0
HDMI ports quantity *	3	<b>Weight &amp; dimensions</b>	
HDMI version	1.4	Width	923.3 mm
DVI port *	✗	Depth	44.8 mm
USB port *	✓	Height	277.1 mm
USB ports quantity	2	Weight	6.3 kg
Ethernet LAN *	✓	<b>Packaging data</b>	
Ethernet LAN (RJ-45) ports	1	Package width	363 mm
Wi-Fi *	✓	Package depth	122 mm
RS-232 interface	✓	Package height	1112 mm
Remote (IR) input	1	Package weight	8.4 kg
<b>Design</b>			
Product design *	Panorama design		

**Design**

Placement supported *	Indoor
Product colour *	Black
VESA mounting *	✓
Panel mounting interface	400 x 200 mm

**Operational conditions**

Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	10 - 80%

**Technical details**

Sustainability certificates	ENERGY STAR, EPEAT Bronze, Electromagnetic Compatibility (EMC)
-----------------------------	--

**Other features**

Bluetooth	✓
-----------	---



8806095208848

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 07-MAY-2024. Prints or copies of Information are only valid on the printed Publication date