

SONY

Sony α α6700 MILC 27 MP Exmor R CMOS 6192 x 4128 pixels Black

Brand : Sony

Product family: α

Product code: ILCE6700LB.CEC

Product name : α6700

Sony α α6700. Camera type: MILC, Megapixel (approx.): 27 MP, Sensor type: Exmor R CMOS, Maximum image resolution: 6192 x 4128 pixels. ISO sensitivity (max): 32000. Focal length range: 16 - 50 mm. Fastest camera shutter speed: 1/4000 s. Wi-Fi. HD type: 4K Ultra HD, Maximum video resolution: 3840 x 2160 pixels. Display diagonal: 7.62 cm (3"), Touchscreen. Viewfinder type: Electronic. Weight: 410 g. Product colour: Black



| Picture quality | | Viewfinder | |
|----------------------------------|---------------------------------------|----------------------------------|--|
| Camera type * | MILC | Viewfinder type | Electronic |
| Megapixel (approx.) * | 27 MP | Magnification | 1.07x |
| Sensor type * | Exmor R CMOS | Viewfinder screen size | 0.39" |
| Maximum image resolution * | 6192 x 4128 pixels | Viewfinder eyepoint (approx.) | 2.2 cm |
| Still image resolution(s) * | 6192 x 4128, 4384 x 2920, 3104 x 2064 | Viewfinder technology | OLED |
| Image stabilizer * | ✓ | Viewfinder resolution (approx.) | 2359296 pixels |
| Supported aspect ratios | 3:2 | Ports & interfaces | |
| Image sensor size (W x H) | 23.3 x 15.5 mm | PictBridge * | ✗ |
| Sensor format | Advanced Photo System type-C (APS-C) | USB version * | 3.2 Gen 1 (3.1 Gen 1) |
| Simultaneous recording | ✓ | USB connector | USB Type-C |
| Image formats supported * | HEIF, JPEG, RAW | HDMI * | ✓ |
| Lens system | | HDMI connector type | Micro |
| Focal length range | 16 - 50 mm | Microphone in | ✓ |
| Lens mount interface | E mount | Headphone outputs | 1 |
| Focusing | | Headphone connectivity | 3.5 mm |
| Focus * | TTL | Network | |
| Focus adjustment * | Auto | Bluetooth * | ✓ |
| Auto focusing (AF) modes * | Tracking Auto Focus | Bluetooth version | 4.2 |
| Auto Focus (AF) object detection | Aircraft, Animal, Bird, People, Train | Wi-Fi * | ✓ |
| Auto Focus (AF) points | 759 | Wi-Fi standards | 802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac) |
| Exposure | | Near Field Communication (NFC) * | ✗ |
| ISO sensitivity (min) * | 100 | Camera | |
| ISO sensitivity (max) * | 32000 | Subject recognition | ✓ |
| Light exposure correction * | ± 5EV (1/2EV; 1/3EV step) | Dioptre correction | ✓ |
| Number of measurement zones | 1200 | Diopter adjustment (D-D) | -4 - 3 |
| Anti-flicker shooting | ✓ | Anti-dust function | ✓ |
| Shutter | | Smartphone remote support | ✓ |
| Fastest camera shutter speed * | 1/4000 s | View on smartphone | ✓ |
| Camera shutter type | Electronic, Mechanical | Metadata supported | ✓ |
| | | Tripod mounting supported * | ✓ |
| | | Built-in processor | ✓ |

| | | | |
|------------------------------|--|--------------------------------|-----------|
| Video | | Design | |
| Video recording * | ✓ | Product colour * | Black |
| Maximum video resolution * | 3840 x 2160 pixels | Battery | |
| HD type * | 4K Ultra HD | Battery life (CIPA standard) | 570 shots |
| Video resolutions | 1920 x 1080, 3840 x 2160 pixels | Battery life (viewfinder) | 550 shots |
| | 1920x1080@100fps, 1920x1080@120fps, 1920x1080@23.98fps, 1920x1080@25fps, 1920x1080@29.97fps, 1920x1080@50fps, 1920x1080@59.94fps, 3840x2160@120fps, 3840x2160@23.98fps, 3840x2160@60fps | Operational conditions | |
| Resolution at capture speed | | Operating temperature (T-T) | 0 - 40 °C |
| Video formats supported | H.264, H.265, HEVC, MPEG4 | Weight & dimensions | |
| Audio | | Width | 122 mm |
| Built-in microphone * | ✓ | Depth | 75.1 mm |
| Built-in speaker(s) | ✓ | Height | 69 mm |
| Audio system | stereo | Weight | 410 g |
| Audio formats supported | LPCM | Weight (including battery) | 493 g |
| Memory | | Packaging data | |
| Compatible memory cards * | SD | Quantity per pack | 1 pc(s) |
| Memory slots | 1 | Packaging content | |
| Memory card read mechanism | UHS-I | Shoulder strap | ✓ |
| Display | | Batteries included | ✓ |
| Display * | TFT | Lens cap included | ✓ |
| Touchscreen * | ✓ | | |
| Display diagonal * | 7.62 cm (3") | | |
| Display diagonal (metric) | 7.5 cm | | |
| Display resolution (numeric) | 1036800 pixels | | |



4548736146976

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 25-OCT-2023. Prints or copies of Information are only valid on the printed Publication date