

POLY VVX 250 IP phone Black 4 lines LED

Brand: POLY Product code: 89B58AA

Product name: VVX 250

Poly OBi VVX 250 4-Line IP Phone and PoE-enabled

POLY VVX 250 IP phone Black 4 lines LED:

Conversations stay on track

Quality sound is standard on the Poly VVX 250 IP desk phone. You'll appreciate all the smart features on non-stop call days, but equally love the color display. It's a win-win for today's office environments. POLY VVX 250. Product type: IP Phone, Product colour: Black, Handset type: Wired handset. Lines quantity: 4 lines. Display: LED, Display diagonal: 7.11 cm (2.8"), Display resolution: 320 x 240 pixels. Voice codecs: G.711, G.722, G.722.1, G.729ab, OPUS, iLBC. Ethernet LAN interface type: Gigabit Ethernet, Ethernet LAN data rates: 10,100,1000 Mbit/s, Security algorithms: 802.1x RADIUS, HTTPS





Design		Network	
Product type * Handset type Product colour *	IP Phone Wired handset Black	Ethernet LAN data rates Security algorithms Syslog	10,100,1000 Mbit/s 802.1x RADIUS, HTTPS ✓
Phone features		Technical details	
Lines quantity *	4 lines	Warranty period	1 year(s)
Call waiting	√	Ports & interfaces	
Distinctive ring Speed dialling Call hold	1	USB 2.0 ports quantity Ethernet LAN (RJ-45) ports	1 2
Call forwarding	4	Certificates	
Conference call	✓	Sustainability certificates	ENERGY STAR
Redialing Do not disturb function Call transfer	1	Safety	UL 60950-1/62368-1, CE Mark, CAN/CSA C22.2 No 60950-1/62368-1-1, EN 60950-1/62368-1, IEC 60950-1/62368-1, AS/NZS 60950-1
Display			FCC Part 15 (CFR 47) Class B
Display Display diagonal Display resolution Touchscreen *	LED 7.11 cm (2.8") 320 x 240 pixels	Certification	ICES-003 Class B EN55032 Class B CISPR32 Class B VCCI Class B EN55024 EN61000-3-2; EN61000-3-3 NZ Telepermit Korea KCC3 UAE TRA Russia CU3 Brazil
Audio			ANATEL3 Australia RCM South Africa ICASA3 Saudi Arabia CITC China
Speakerphone *	✓		CCC3 RoHS Complian TAA
Voice codecs	G.711, G.722, G.722.1, G.729ab, OPUS, iLBC	Power	
Voice activity detection Comfort noise generation (CNG)	4	Power over Ethernet (PoE) * AC adapter output voltage AC adapter output current	√ 5 V 3 A
Network			3 A
Ethernet LAN * Ethernet LAN interface type	√ Gigabit Ethernet	Operational conditions	0. 40.00
		Operating temperature (T-T) Operating relative humidity (H-H) Storage temperature (T-T)	0 - 40 °C 5 - 95% -40 - 70 °C
		Packaging content	
		Number of handles included * AC adapter included	1 pc(s) ✓

