



iiyama ProLite T1634MC-B1S computer monitor 39.6 cm (15.6") 1920 x 1080 pixels Full HD LED Touchscreen Black

Brand : iiyama

Product family: ProLite

Product code: T1634MC-B1S

Product name : T1634MC-B1S

15.6", 39.5cm, IPS, LED, 1920 x 1080, 16:9, 450 cd/m², 90%, 25ms, 381 x 285.5 x 200mm, 445 x 355 x 150mm, 3.4kg, 5.18kg

iiyama ProLite T1634MC-B1S. Display diagonal: 39.6 cm (15.6"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Display technology: LED, Display surface: Matt, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. VESA mounting. Product colour: Black



Display		Ports & interfaces	
Display diagonal *	39.6 cm (15.6")	VGA (D-Sub) ports quantity	1
Display resolution *	1920 x 1080 pixels	HDMI *	✓
HD type *	Full HD	HDMI ports quantity	1
Native aspect ratio *	16:9	DisplayPorts quantity	1
Display technology *	LED	HDCP	✓
Panel type *	IPS	Ergonomics	
Touchscreen *	✓	VESA mounting *	✓
Touchscreen technology	Projected capacitive system	Panel mounting interface	100 x 100 mm
Number of simultaneous touchpoints	10	Tilt angle range	90 - 5°
Display brightness (peak)	450 cd/m ²	On Screen Display (OSD)	✓
Display brightness (typical)	405 cd/m ²	Tilt adjustment	✓
Display surface	Matt	Power	
Screen shape *	Flat	Energy efficiency class (SDR) *	E
Contrast ratio (typical) *	700:1	Energy efficiency class (HDR) *	Not available
Maximum refresh rate *	60 Hz	Energy consumption (SDR) per 1000 hours *	10 kWh
Viewing angle, horizontal	178°	Power consumption (typical) *	18 W
Viewing angle, vertical	178°	Power consumption (standby) *	1.5 W
Display number of colours *	16.2 million colours	Power consumption (off)	0.3 W
Response time (fast)	25 ms	Power supply type	External
Pixel pitch	0.179 x 0.179 mm	Energy efficiency scale	A to G
Digital horizontal frequency	30 - 84 kHz	Packaging content	
Display diagonal (metric)	39.5 cm	Cables included	AC, DisplayPort, HDMI, USB
Colour depth	6 bit	Weight & dimensions	
Colour gamut	90%	Width (with stand)	381 mm
Second display effective viewing area	344.2 x 193.6 mm	Depth (with stand)	200 mm
Design		Height (with stand)	285.5 mm
Market positioning *	Office	Weight (with stand)	3.4 kg
Product colour *	Black	Packaging data	
International Protection (IP) code	IP65	Package width	445 mm
Glass thickness	2.4 mm	Package depth	150 mm
		Package height	355 mm
		Package weight	5.18 kg



4948570122110

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 24-NOV-2023. Prints or copies of Information are only valid on the printed Publication date