

NETGEAR PR60X wired router 2.5 Gigabit Ethernet, Gigabit Ethernet Black

Brand : NETGEAR

Product code: PR60X-100EUS



Product name : PR60X



- 10G/Multi-Gigabit and 2.5G Dual WAN ports with failover
 - High performance hardware with one 10G/Multi-Gigabit Ethernet port, four 2.5G Ethernet ports and one 10G SFP+ port for long-distance backhaul or connection to ISP fiber modem
 - Seamless integration with NETGEAR Pro WiFi Access Points and select Smart switches through NETGEAR Insight Cloud Management
 - Control, manage and monitor through NETGEAR Insight
 - Rack-mountable for placement in industry-standard enclosures
 - Firewall protection
 - IPSec configuration to create secure site-to-site VPN connections
- 0G/Multi-Gigabit Dual WAN Pro Router with Insight Cloud Management

[NETGEAR PR60X wired router 2.5 Gigabit Ethernet, Gigabit Ethernet Black:](#)

Total Network Solution helps you get the most out of your network

Easily deploy, manage, and monitor NETGEAR Insight managed routers, switches, and access points all from a single pane-of-glass.

NETGEAR INSIGHT REMOTE MANAGEMENT

Manage locally or remotely through the Cloud for simple yet powerful control of your network anytime, anywhere. A 1-year subscription is included.

WAN connection		Security	
Ethernet WAN *	✓	Network address translation (NAT)	✓
Network		Features	
Ethernet interface type *	2.5 Gigabit Ethernet, Gigabit Ethernet	Built-in processor	✓
Switching capacity	9.4 Gbit/s	Processor manufacturer	ARM
Throughput	2.4 Gbit/s	Flash memory	2000 MB
Static route	✓	Internal memory	4000 MB
VLAN support	✓	Internal memory type	DDR4
Port forwarding	✓	Design	
Management features		Product colour *	Black
Web-based management *	✓	LED indicators	✓
Quality of Service (QoS) support	✓	Power	
Reset button	✓	AC input voltage	100 - 240 V
Ports & interfaces		AC input frequency	50/60 Hz
Ethernet LAN (RJ-45) ports *	3	Input current	1.3 A
Installed SFP+ modules quantity	1	Operational conditions	
Protocols		Operating temperature (T-T)	0 - 40 °C
DHCP client *	✓	Storage temperature (T-T)	-20 - 70 °C
DHCP server *	✓	Operating relative humidity (H-H)	0 - 90%
Security		Storage relative humidity (H-H)	0 - 95%
Security algorithms *	128-bit AES, 192-bit AES, 256-bit AES, SHA-1, SHA-2, SHA-256	Weight & dimensions	
Firewall	✓	Width	440 mm
Access Control List (ACL)	✓	Depth	100 mm
		Height	43.2 mm
		Weight	1.51 kg



0606449166200



606449166200

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 25-MAR-2024. Prints or copies of Information are only valid on the printed Publication date