



DELL P Series P2424HT computer monitor 60.5 cm (23.8") 1920 x 1080 pixels Full HD LCD Touchscreen Black, Silver

Brand : DELL

Product family: P Series

Product code: DELL-P2424HT

Product name : P2424HT

- 60.5cm (23.8") Full HD 1920 x 1080 LED IPS

- 8ms, 16:9, 300cd/m², 1000:1

- USB, HDMI, DisplayPort

60.5cm (23.8") Full HD 1920 x 1080 LED IPS, 16:9, 300cd/m², 16.78M, 8ms, 178°/178°, 1000:1

DELL P Series P2424HT computer monitor 60.5 cm (23.8") 1920 x 1080 pixels Full HD LCD Touchscreen Black, Silver:

23.8-inch monitor puts productivity in reach with its touch screen, superior connectivity and articulating stand.

DELL P Series P2424HT. Display diagonal: 60.5 cm (23.8"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Display technology: LCD, Response time: 8 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub. VESA mounting, Height adjustment. Product colour: Black, Silver



Display		Network	
Display diagonal *	60.5 cm (23.8")	Wi-Fi	✗
Display resolution *	1920 x 1080 pixels	Ergonomics	
HD type *	Full HD	VESA mounting *	✓
Native aspect ratio *	16:9	Panel mounting interface	100 x 100 mm
Display technology *	LCD	Cable management	✓
Panel type *	IPS	Cable lock slot *	✓
Backlight type	LED	Cable lock slot type	Kensington
Touchscreen *	✓	Height adjustment *	✓
Display brightness (typical)	300 cd/m ²	Height adjustment	11.1 cm
Response time	8 ms	Pivot	✗
Anti-glare screen	✓	Swivelling	✓
Screen shape *	Flat	Swivel angle range	-30 - 30°
Supported video modes	480p, 576p, 720p, 1080i, 1080p	Tilt angle range	-5 - 60°
Contrast ratio (typical) *	1000:1	On Screen Display (OSD)	✓
Maximum refresh rate *	60 Hz	Plug and Play	✓
Viewing angle, horizontal	178°	LED indicators	✓
Viewing angle, vertical	178°	Tilt adjustment	✓
Display number of colours *	16.78 million colours	Power	
Response time (fast)	5 ms	Energy efficiency class (SDR) *	E
Pixel pitch	0.2745 x 0.2745 mm	Energy efficiency class (HDR) *	Not available
Pixel density	93 ppi	Energy consumption (SDR) per 1000 hours *	18 kWh
Horizontal scan range	30 - 88 kHz	Power consumption (typical) *	18 W
Vertical scan range	48 - 75 Hz	Power consumption (standby) *	0.5 W
Viewable size, horizontal	52.7 cm	Power consumption (max)	190 W
Viewable size, vertical	29.6 cm	Power consumption (off)	0.3 W
Viewable size diagonal	60.5 cm	AC input voltage	100 - 240 V
Display diagonal (metric)	60.47 cm	AC input frequency	50/60 Hz
High Dynamic Range (HDR) supported	✗		

Display		Power	
Surface hardness	3H	Power supply type	Internal
Colour depth	6 bit	Energy efficiency scale	A to G
sRGB coverage (typical)	99%	Operational conditions	
Performance		Operating temperature (T-T)	0 - 40 °C
Low Blue Light technology	✓	Storage temperature (T-T)	-20 - 60 °C
Multimedia		Operating relative humidity (H-H)	10 - 80%
Built-in speaker(s) *	✓	Storage relative humidity (H-H)	5 - 90%
Built-in camera *	✗	Operating altitude	0 - 5000 m
RMS rated power	3 W	Non-operating altitude	5000 - 12192 m
Design		Packaging content	
Market positioning *	Business	Stand included	✓
Product colour *	Black, Silver	Cables included	AC, DisplayPort, USB Type-A to USB Type-C, USB Type-C to USB Type-C
Front bezel colour	Black	Power adapter included	✓
Feet colour	Silver	Remote control included	✗
Heavy metals free	Hg (mercury)	Stylus included	✗
Ports & interfaces		Quick start guide	✓
Built-in USB hub *	✓	DisplayPort cable length	1.8 m
USB upstream port type	USB Type-C	Weight & dimensions	
Number of USB Type-C upstream ports quantity	1	Width (with stand)	538.8 mm
USB Type-A downstream ports quantity	2	Depth (with stand)	248.9 mm
USB Type-C downstream ports quantity	1	Height (with stand)	431.5 mm
USB Type-C DisplayPort Alternate Mode	✓	Weight (with stand)	7.86 kg
USB Power Delivery	✓	Width (without stand)	538.8 mm
USB Power Delivery up to	90 W	Depth (without stand)	54.1 mm
HDMI *	✓	Height (without stand)	321 mm
HDMI ports quantity	1	Weight (without stand)	3.86 kg
HDMI version	1.4	Bezel width (side)	5.88 mm
DisplayPorts quantity	1	Bezel width (top)	5.87 mm
DisplayPort version	1.2	Bezel width (bottom)	1.86 cm
Headphone out *	✓	Packaging data	
Headphone connectivity	3.5 mm	Package weight	10.8 kg
Microphone in	✗	Sustainability	
PC Audio in	✗	Sustainability compliance	✓
HDCP	✓	Sustainability certificates	ENERGY STAR, RoHS
HDCP version	1.4	Doesn't contain	PVC/BFR
AC (power) in	✓	Other features	
		RJ-45 ports quantity	1



5397184821367

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 05-OCT-2023. Prints or copies of Information are only valid on the printed Publication date