



AVer CAM520 Pro2 2 MP Black 1920 x 1080 pixels 60 fps

Brand : AVer

Product code: 61U3410000AF

Product name : CAM520 Pro2

CAM520 Pro2 - 2M, Zoom: 24X, WDR

AVer CAM520 Pro2. Megapixel (approx.): 2 MP. HD type: Full HD, Maximum video resolution: 1920 x 1080 pixels, Supported video modes: 240p, 360p, 480p, 720p, 900p, 1080p, Maximum frame rate: 60 fps. Optical zoom: 12x. Mounting type: Stand, Product colour: Black



Camera		Operational conditions	
Megapixel (approx.) *	2 MP	Storage relative humidity (H-H)	20 - 80%
Optical zoom	12x	Packaging content	
Combined zoom	24x	Power supply included	✓
Focal length range	3.9 - 47.3 mm	Remote control included	✓
Horizontal field of view	76°	Cables included	AC, USB
Vertical field of view	48°	Warranty card	✓
Flip & mirror	✓	Screws included	✓
Aperture range (F-F)	1.8 - 2.8	Quick start guide	✓
White balance	Auto, Manual	Mounting kit	✓
Closest focusing distance	1.5 m	Cable ties included	✓
Wide Dynamic Range (WDR)	✓	System requirements	
Number of camera presets	10	Windows operating systems supported	✓
PTZ control	✓	Mac operating systems supported	✓
Video		Other operating systems supported	ChromeOS
HD type *	Full HD	Minimum processor family	Core i5
Maximum video resolution *	1920 x 1080 pixels	Minimum processor speed	3.2 GHz
Maximum frame rate *	60 fps	Minimum processor	Intel Core i5-4460
Supported video modes	240p, 360p, 480p, 720p, 900p, 1080p	Minimum RAM	4096 MB
Video formats supported	M-JPEG, NV12, YUV, YUY2	Performance	
Design		Remote control function	✓
Product colour *	Black	Remote control type	IR
Mounting type	Stand	Plug and Play	✓
Tilt angle range	-30 - 90°	Audio	
Pan range	-170 - 170°	Built-in microphone	✓
LED indicators	Status	Built-in speaker(s)	✓
Web-based management	✓	Network	
Ports & interfaces		Ethernet LAN data rates	10,100,1000 Mbit/s
USB 3.2 Gen 1 (3.1 Gen 1) Type-B ports quantity	1	Supported network protocols	RTSP, RTMP
RS-232 ports	1	Weight & dimensions	
Ethernet LAN (RJ-45) ports	1	Remote control dimensions (W x H x D)	200 x 50 x 21 mm
DC-in jack	✓	Width	182 mm
Power		Depth	142.7 mm
Power source type	AC	Height	153 mm
AC input frequency	50/60 Hz	Weight	1.47 kg
AC input voltage	100 - 240 V		

Power		Packaging data	
DC input voltage	12 V	Package width	256 mm
Input current	2 A	Package depth	256 mm
Operational conditions		Package height	274 mm
Operating temperature (T-T)	0 - 40 °C	Package weight	3.33 kg
Storage temperature (T-T)	-20 - 60 °C	Package type	Box
Operating relative humidity (H-H)	20 - 80%		

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 15-DEC-2023. Prints or copies of Information are only valid on the printed Publication date