ASUS PRIME B760-PLUS Intel B760 LGA 1700 ATX

Brand: ASUS Product code: 90MB1EF0-M1EAY0

Product name: PRIME B760-PLUS

- Intel® LGA 1700 Socket: Ready for 13th and 12th Gen Intel® processors
- Ultrafast Connectivity: PCle 5.0, three PCle 4.0 M.2, Realtek 2.5Gb Ethernet, USB 3.2 Gen 2x2 Type-C®, front USB 3.2 Gen 1 Type-C® and Thunderbolt $^{\text{TM}}$ (USB4®) header support
- Comprehensive Cooling: VRM heatsinks, M.2 heatsink, PCH heatsink, hybrid fan headers and Fan Xpert 2+
- Exclusive Memory Technology: ASUS Enhanced Memory Profile II and ASUS OptiMem II
- Aura Sync RGB Lighting: Onboard Addressable Gen 2 headers and Aura RGB header for RGB LED strips, easily synced with Aura Sync-capable hardware

Prime B760-PLUS, an Intel B760 LGA 1700 ATX motherboard with PCle 5.0, three PCle 4.0 M.2 slots, DDR5, Realtek 2.5Gb Ethernet, DisplayPort, VGA, HDMI™, SATA 6 Gbps, USB 3.2 Gen 2x2 Type-C, front USB 3.2 Gen 1 Type-C, Thunderbolt (USB4) support, Aura Sync





| Processor | | | Rear panel I/O ports | |
|---|------------------------|--|--|---|
| Processor manufacturer Processor socket * | * | Intel LGA 1700 | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity * | 1 |
| | | Intel® Celeron®, Intel® Core™ i3, Intel® Core™ i5, Intel® Core™ i7, | USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity * | 2 |
| Compatible processor s | eries * | Intel® Core™ i9, Intel® Pentium® Gold | USB 3.2 Gen 2x2 Type-C ports quantity | 1 |
| Maximum number of SM | 1P | 1 | Ethernet LAN (RJ-45) ports * | 1 |
| processors | alcata | LCA 1700 | VGA (D-Sub) ports quantity * | 1 |
| Supported processor so | ckets | LGA 1700 | HDMI ports quantity * | 1 |
| Memory | DDR5-SDRAM | | HDMI version | 2.1 |
| Supported memory types * Number of memory slots * | 4 | | DisplayPorts quantity | 1 |
| Memory slots type | DIMM | | DisplayPort version | 1.4 |
| Memory channels Non-ECC | Dual-channel ✓ | | Headphone outputs | 1 |
| Supported memory clock speeds | 4800,5000,5200, MHz | 5400,5600,5800,6000,6200,6400,6600,6800,7000,7200 | Line-in | ✓ |
| Maximum internal memory * Unbuffered memory | 192 GB ✓ | | Network | |
| Storage controllers | | | Ethernet LAN | ✓ |
| Supported storage drive types | | HDD & SSD | Ethernet interface type | 2.5 Gigabit Ethernet, Fast Ethernet,Gigabit Ethernet |
| Supported storage drive interfaces * | | M.2, SATA III | Wi-Fi * | × |
| Number of HDDs suppo | | 4 | Features | |
| Number of storage drives supported | | 7 | Motherboard chipset * | Intel B760 |
| RAID support | | 1 | • | 7.1 channels |
| RAID levels | | 0, 1, 5, 10 | Audio output channels * Component for * | PC |
| Graphics | | | Motherboard form factor * | ATX |
| Parallel processing tech | nology | Not supported | Motherboard chipset family * Intel | |
| support * | | not supported | Cooling type | Passive |
| Internal I/O | | | Power source type | ATX |
| USB 2.0 connectors * | | 2 | Windows operating systems supported | Windows 10 x64, Windows 11 |
| USB 3.2 Gen 1 (3.1 Gen connectors * | 1) | 2 | Expansion slots | |
| Number of SATA III conr | nectors * | 4 | • | 2 |
| S/PDIF out connector | | √ | PCI Express x16 (Gen 3.x) slots | 2 |
| Front panel audio conne | ector | ✓ | PCI Express x16 (Gen 4.x) slots PCI Express x16 (Gen 5.x) slots | 1 |

| ternal I/O | | Expansion slots | |
|---|------------|---|--|
| ont panel connector | ✓ | Number of M.2 (M) slots | 3 |
| X Power connector (24-pin) | ✓ | BIOS | |
| CPU fan connector Number of chassis fan connectors Peripheral (Molex) power | 3 | BIOS type * BIOS memory size | UEFI AMI 128 Mbit |
| nnectors (4-pin) | 1 | Packaging data | |
| 2S power connector (8-pin) umber of COM connectors 2M connector nunderbolt headers 2V power connector GB LED pin header ear panel I/O ports SB 2.0 ports quantity * | 1 1 1 2 | Package width Package depth Package height Package weight Weight & dimensions Width Depth | 328 mm 266 mm 53 mm 1.2 kg 305 mm 244 mm 36 mm |
| | | Packaging content Cables included Other features Weight | SATA 760 q |



4711387102985

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.