




DELL P5524QT Interactive flat panel 139.7 cm (55") LCD 350 cd/m² 4K Ultra HD Black Touchscreen

Brand : DELL

Product code: DELL-P5524QT

Product name : P5524QT



- 54.64" 4K UHD 3840 x 2160, IPS
- 8ms, 16:9, 350cd/m², 1200:1
- USB, HDMI, DisplayPort"
- 54.64" 4K UHD 3840 x 2160, IPS, 16:9, 350 cd/m² 1.07 Billion, 8 ms, 178°/178°, 1200:1

DELL P5524QT Interactive flat panel 139.7 cm (55") LCD 350 cd/m² 4K Ultra HD Black Touchscreen:

Bring the team together, whether they are in the room or remote, with this brilliant 55" 4K UHD large format monitor with 20-point touch, palm-rejection, USB-C connectivity and built-in dual 10W speakers. DELL P5524QT. Product design: Interactive flat panel. Display diagonal: 139.7 cm (55"), Display technology: LCD, Display resolution: 3840 x 2160 pixels, Display brightness: 350 cd/m², HD type: 4K Ultra HD, Touchscreen. Product colour: Black




Display		Design	
Panel type	IPS	Bezel width (side)	4.47 cm
LED backlight	✓	Bezel width (top)	4.47 cm
Display diagonal *	139.7 cm (55")	Anti-glare screen	✓
Display technology *	LCD	Performance	
Display resolution *	3840 x 2160 pixels	Purpose *	Corporate
Display brightness *	350 cd/m ²	On Screen Display (OSD)	✓
HD type *	4K Ultra HD	Power	
Touchscreen *	✓	Power consumption (typical) *	77.1 W
Number of simultaneous touchpoints	20	Power consumption (standby) *	0.5 W
Multi-touch	✓	Power consumption (off)	0.3 W
Native aspect ratio	16:9	Power consumption (max)	320 W
Contrast ratio (typical)	1300:1	Energy efficiency class (SDR)	F
Viewing angle, horizontal	178°	Energy efficiency class (HDR)	Not available
Viewing angle, vertical	178°	Energy consumption (SDR) per 1000 hours	77 kWh
Display number of colours	1.07 billion colours	AC input voltage	100 - 240 V
Pixel pitch	0.315 x 0.315 mm	AC input frequency	50/60 Hz
Display diagonal (metric)	138.787 cm	Heat dissipation	263.08 BTU/h
Horizontal scan range	30 - 140 kHz	Energy efficiency scale	A to G
Vertical scan range	24 - 75 Hz	Computer system	
Supported graphics resolutions	640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 1024 x 768 (XGA), 1152 x 864 (XGA+), 1280 x 1024 (SXGA), 1280 x 800, 1600 x 1200, 1920 x 1080 (HD 1080), 2048 x 1152, 2560 x 1440, 3840 x 2160	Windows operating systems supported	Windows 7 Professional, Windows 7 Ultimate, Windows 8, Windows 8.1
Supported video modes	480p, 576p, 720p, 1080i, 1080p, 2160p	Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan
Hardness	3H	Linux operating systems supported	✓
Native refresh rate	60 Hz	Weight & dimensions	
RGB colour space	NTSC	Display width	1299 mm
Colour gamut	72%	Display depth	78.7 mm
Ports & interfaces		Display height	769.8 mm
HDMI ports quantity *	3	Display weight	34.3 kg
HDMI version	2.0	Packaging data	
DVI port *	✗	Package weight	41.9 kg
DisplayPorts quantity *	1	Packaging content	
USB port *	✓	Remote control included	✓
USB ports quantity	8	Stylus pen	✓
USB version	2.0/3.2 Gen 1 (3.1 Gen 1)	Number of stylus pens	2
		Cables included	DisplayPort, HDMI, USB, USB Type-C

Ports & interfaces		Operational conditions	
USB connector type	USB Type-A	Operating temperature (T-T)	0 - 40 °C
USB 2.0 Type-B ports quantity	3	Operating relative humidity (H-H)	10 - 80%
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	4	Storage temperature (T-T)	-20 - 60 °C
USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity	1	Storage relative humidity (H-H)	5 - 90%
USB Power Delivery	✓	Operating altitude	0 - 5000 m
USB Power Delivery up to	90 W	Non-operating altitude	0 - 12192 m
USB Type-C DisplayPort Alternate Mode	✓	Features	
Ethernet LAN *	✓	Heat dissipation (max)	1091.89 BTU/h
Ethernet LAN (RJ-45) ports	1	Technical details	
Wi-Fi *	✗	Sustainability compliance	✓
Audio (L/R) in	1	Sustainability certificates	ENERGY STAR, RoHS
RS-232 interface	✓	Doesn't contain	Arsenic, Mercury, PVC/BFR
Audio		Other features	
Built-in speaker(s) *	✓	Quick start guide	✓
Number of built-in speakers	2	Cable lock slot	✓
RMS rated power	20 W	LED indicators	✓
Speaker impedance	8 Ω	On/off switch	✓
Speaker frequency range	120 - 20000 Hz	Viewable size, horizontal	121 cm
Design		Viewable size, vertical	68 cm
Product design *	Interactive flat panel	Power supply type	Internal
Placement supported *	Indoor	Cable management	✓
Product colour *	Black	Response time	9 s
Screen shape	Flat	Plug and Play	✓
VESA mounting *	✓		
Panel mounting interface	300 x 400 mm		
Bezel width (bottom)	4.47 cm		



5397184821534



0884116452089



884116452089

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.