



## DELL P7524QT Interactive flat panel 189.3 cm (74.5") LCD 350 cd/m<sup>2</sup> 4K Ultra HD Black Touchscreen

**Brand :** DELL

**Product code:** DELL-P7524QT

**Product name :** P7524QT

- 75" 4K UHD 3840 x 2160, IPS
- 8ms, 16:9, 350cd/m<sup>2</sup>, 1200:1
- USB, HDMI, VGA , DisplayPort"
- 75" 4K UHD 3840 x 2160, IPS, 16:9, 350 cd/m<sup>2</sup> 1.07 Billion, 8 ms, 178°/178°, 1200:1

DELL P7524QT Interactive flat panel 189.3 cm (74.5") LCD 350 cd/m<sup>2</sup> 4K Ultra HD Black Touchscreen:

Bring the team together, whether they are in the room or remote, with this brilliant 75" 4K UHD large format monitor with 20-point touch, palm-rejection and built-in dual 20W speakers.  
DELL P7524QT. Product design: Interactive flat panel. Display diagonal: 189.3 cm (74.5"), Display technology: LCD, Display resolution: 3840 x 2160 pixels, Display brightness: 350 cd/m<sup>2</sup>, HD type: 4K Ultra HD, Touchscreen. Product colour: Black



| Display                            |  | Performance                             |  |
|------------------------------------|--|---|--|
| Panel type                         | IPS  | Purpose *                               | Corporate  |
| LED backlight                      | ✓  | On Screen Display (OSD)                 | ✓  |
| Display diagonal *                 | 189.3 cm (74.5")   | HID support                             | ✓  |
| Display technology *               | LCD  | <b>Power</b>                            |  |
| Display resolution *               | 3840 x 2160 pixels   | Power consumption (typical) *           | 140 W  |
| Display brightness *               | 350 cd/m <sup>2</sup>  | Power consumption (standby) *           | 0.5 W  |
| HD type *                          | 4K Ultra HD  | Power consumption (off)                 | 0.3 W  |
| Touchscreen *                      | ✓  | Power consumption (max)                 | 290 W  |
| Number of simultaneous touchpoints | 20   | Energy efficiency class (SDR)           | G  |
| Multi-touch                        | ✓  | Energy efficiency class (HDR)           | Not available  |
| Native aspect ratio                | 16:9   | Energy consumption (SDR) per 1000 hours | 140 kWh  |
| Response time                      | 8 ms   | AC input voltage                        | 100 - 240 V  |
| Contrast ratio (typical)           | 1200:1   | AC input frequency                      | 50/60 Hz   |
| Viewing angle, horizontal          | 178°   | Heat dissipation                        | 477.7 BTU/h  |
| Viewing angle, vertical            | 178°   | Energy efficiency scale                 | A to G   |
| Display number of colours          | 1.07 billion colours   | <b>Computer system</b>                  |  |
| Pixel pitch                        | 0.429 x 0.429 mm   | Windows operating systems supported     | Windows 7 Professional, Windows 7 Ultimate, Windows 8, Windows 8.1 |
| Display diagonal (metric)          | 189.273 cm   | Mac operating systems supported         | Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan                 |
| Horizontal scan range              | 30 - 140 kHz   | Linux operating systems supported       | ✓  |
| Vertical scan range                | 24 - 75 Hz   | <b>Weight &amp; dimensions</b>          |  |
| Supported graphics resolutions     | 640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 1024 x 768 (XGA), 1152 x 864 (XGA+), 1280 x 1024 (SXGA), 1280 x 800, 1600 x 1200, 1920 x 1080 (HD 1080), 2048 x 1152, 2560 x 1440, 3840 x 2160 | Display width                           | 1735 mm  |
| Supported video modes              | 480p, 576p, 720p, 1080i, 1080p, 2160p  | Display depth                           | 79.1 mm  |
| Hardness                           | 9H   | Display height                          | 1017.4 mm  |
| Native refresh rate                | 60 Hz  | Display weight                          | 64 kg  |

| Display   |                           | Packaging data                    |                                 |
|---|---------------------------|-----------------------------------|---------------------------------|
| RGB colour space                                | NTSC                      | Package weight                    | 76.6 kg                         |
| Colour gamut                                    | 72%                       | Packaging content                 |                                 |
| Ports & interfaces                              |                           | Remote control included           | ✓                               |
| HDMI ports quantity *                           | 3                         | Stylus pen                        | ✓                               |
| HDMI version                                    | 2.0                       | Number of stylus pens             | 2                               |
| DVI port *                                      | ✗                         | Cables included                   | AC, DisplayPort, HDMI, USB, VGA |
| VGA (D-Sub) input ports                         | 1                         | Operational conditions            |                                 |
| DisplayPorts quantity *                         | 1                         | Operating temperature (T-T)       | 0 - 40 °C                       |
| USB port *                                      | ✓                         | Operating relative humidity (H-H) | 10 - 80%                        |
| USB ports quantity                              | 7                         | Storage temperature (T-T)         | -20 - 60 °C                     |
| USB version                                     | 2.0/3.2 Gen 1 (3.1 Gen 1) | Storage relative humidity (H-H)   | 5 - 90%                         |
| USB connector type                              | Mini-USB A                | Operating altitude                | 0 - 5000 m                      |
| USB 2.0 Type-B ports quantity                   | 3                         | Non-operating altitude            | 0 - 12192 m                     |
| USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity | 4                         | Features                          |                                 |
| USB Type-C DisplayPort Alternate Mode           | ✓                         | Heat dissipation (max)            | 989.52 BTU/h                    |
| Ethernet LAN *                                  | ✓                         | Technical details                 |                                 |
| Ethernet LAN (RJ-45) ports                      | 1                         | Sustainability compliance         | ✓                               |
| Wi-Fi *   | ✗                         | Sustainability certificates       | ENERGY STAR, RoHS               |
| Audio (L/R) in                                  | 1                         | Doesn't contain                   | Arsenic, Mercury, PVC/BFR       |
| Audio (L/R) out                                 | 1                         | Other features                    |                                 |
| RS-232 interface                                | ✓                         | Quick start guide                 | ✓                               |
| Audio   |                           | Cable lock slot                   | ✓                               |
| Built-in speaker(s) *                           | ✓                         | LED indicators                    | ✓                               |
| Number of built-in speakers                     | 2                         | On/off switch                     | ✓                               |
| RMS rated power                                 | 40 W                      | Viewable size diagonal            | 18.9 cm                         |
| Design  |                           | Viewable size, horizontal         | 165 cm                          |
| Product design *                                | Interactive flat panel    | Viewable size, vertical           | 92.8 cm                         |
| Placement supported *                           | Indoor                    | Power supply type                 | Internal                        |
| Product colour *                                | Black                     | Cable management                  | ✓                               |
| Screen shape                                    | Flat                      | Response time                     | 8 s                             |
| VESA mounting *                                 | ✓                         | Plug and Play                     | ✓                               |
| Panel mounting interface                        | 400 x 400 mm              |                                   |                                 |
| Bezel width (bottom)                            | 4.67 cm                   |                                   |                                 |
| Bezel width (side)                              | 4.27 cm                   |                                   |                                 |
| Bezel width (top)                               | 4.28 cm                   |                                   |                                 |
| Anti-glare screen                               | ✓                         |                                   |                                 |



5397184821558

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 07-MAY-2024. Prints or copies of Information are only valid on the printed Publication date