PHILIPS

Philips 5000 series 49B2U5900CH/00 LED display 124 cm (48.8") 5120 x 1440 pixels Dual QHD LCD Black

Brand : Philips

Product family: 5000 series

Product code:
49B2U5900CH/00

Product name :
49B2U5900CH/00

32:9 SuperWide curved monitor with USB-C

Philips 5000 series 49B2U5900CH/00 LED display 124 cm (48.8") 5120 x 1440 pixels Dual QHD LCD Black:

Welcome to a more efficient workspace. To facilitate everyday workflow, this monitor's large 32:9 SuperWide screen is equipped with a new busy light and tilting webcam feature that helps you flow between tasks with ease.
Philips 5000 series 49B2U5900CH/00. Display diagonal: 124 cm (48.8"), Display resolution: 5120 x 1440 pixels, HD type: Dual QHD, Display technology: LCD, Response time: 4 ms, Native aspect ratio: 32:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub, USB hub version: 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: Black

Display

Display diagonal *	124 cm (48.8")
Display resolution *	5120 x 1440 pixels
HD type *	Dual QHD
Native aspect ratio *	32:9
Display technology *	LCD
Panel type *	VA
Backlight type	W-LED
Touchscreen *	✖
Display brightness (typical)	450 cd/m²
Response time	4 ms
Anti-glare screen	✔
Screen shape *	Curved
Screen curvature rating	1800R
Contrast ratio (typical) *	3000:1
Contrast ratio (dynamic)	80000000:1
Dynamic contrast ratio marketing name	SmartContrast
Maximum refresh rate *	75 Hz
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours *	1.07 billion colours
Pixel pitch	0.2328 x 0.2328 mm
Pixel density	109 ppi
Horizontal scan range	30 - 140 kHz
Vertical scan range	48 - 75 Hz
Viewable size, horizontal	119.2 cm
Viewable size, vertical	33.5 cm
Display diagonal (metric)	124 cm
High Dynamic Range (HDR) supported	✔

Ports & interfaces

DisplayPorts quantity	1
DisplayPort version	1.4
Audio output	✔
Microphone in	✔
Built-in KVM switch	✔
HDCP	✔
HDCP version	1.4/2.2

Network

Ethernet LAN	✔

Ergonomics

VESA mounting *	✔
Panel mounting interface	100 x 100 mm
Cable lock slot *	✔
Cable lock slot type	Kensington
Height adjustment *	✔
Height adjustment	15 cm
Swivelling	✔
Swivel angle range	-30 - 30°
Tilt angle range	-5 - 15°
Picture-in-Picture	✔
On Screen Display (OSD)	✔
On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish, Ukrainian
Number of OSD languages	21
Plug and Play	✔

Display

High Dynamic Range (HDR) technology	DisplayHDR 400
DDC/CI	✔
Haze rate	25%
Surface hardness	3H
Colour depth	8 bit
RGB colour space	sRGB
sRGB coverage (typical)	119%
NTSC coverage (typical)	97%
Display sRGB	✔

Performance

NVIDIA G-SYNC *	✘
AMD FreeSync *	✘
Fast charging	✔
Fast charging technology	Power Delivery
VESA Adaptive Sync support	✔
Component video sync	Separate sync
Flicker-free technology	✔
Low Blue Light technology	✔
HBR3 support	✔
Compatible operating systems	Mac OS X Windows 11/10/8.1/8

Multimedia

Built-in speaker(s) *	✔
Built-in camera *	✔
Number of speakers	2
RMS rated power	6 W
Megapixel (approx.)	5 MP
Built-in microphone	✔

Design

Market positioning *	Business
Product colour *	Black
Front bezel colour	Black
Feet colour	Black
Heavy metals free	Hg (mercury)

Ports & interfaces

Built-in USB hub *	✔
USB hub version	3.2 Gen 1 (3.1 Gen 1)
USB upstream port type	USB Type-B, USB Type-C
Number of upstream ports	2
Number of USB Type-B upstream ports quantity	1
Number of USB Type-C upstream ports quantity	1
USB Type-A downstream ports quantity	2
USB Type-C downstream ports quantity	1
USB Type-C DisplayPort Alternate Mode	✔
USB Power Delivery	✔
USB Power Delivery up to	100 W
HDMI *	✔
HDMI ports quantity	2
HDMI version	2.0

Ergonomics

LED indicators	Operation, Stand-by
Tilt adjustment	✔

Power

Energy efficiency class (SDR) *	F
Power consumption (typical) *	46.1 W
Power consumption (standby) *	0.8 W
Power consumption (PowerSave)	39 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power supply type	Internal

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	20 - 80%
Operating altitude	0 - 3658 m
Non-operating altitude	3658 - 12192 m

Packaging content

Stand included	✔
Cables included	AC, DisplayPort, HDMI, USB Type-C to USB Type-A, USB Type-C to USB Type-C
Manual	✔
Bundled software	SmartControl

Weight & dimensions

Width (with stand)	1193 mm
Depth (with stand)	268 mm
Height (with stand)	586 mm
Weight (with stand)	15.2 kg
Width (without stand)	1193 mm
Depth (without stand)	164 mm
Height (without stand)	373 mm
Weight (without stand)	11.6 kg

Packaging data

Package width	1290 mm
Package depth	475 mm
Package height	300 mm
Package weight	19.4 kg

Sustainability

Sustainability compliance	✔
Sustainability certificates	CB, CE, ENERGY STAR, EPEAT, Federal Communications Commission (FCC), RoHS, TCO, TUV
Doesn't contain	Mercury, PVC/BFR

Recycling data

Post-consumer recycled plastic	85%

Other features

Picture-by-Picture (PbP)	✔
Exterior finish type	Textured
Picture enhancement	SmartImage
Recyclable packaging material	100%
Regulatory Approvals	CB; CE Mark; FCC Class B; ICES-003; CU-EAC; EAEU RoHS; TUV Ergo; TUV/GS; TUV Eyesafe certified; cETLus
Delta E	2
EasyRead mode	✔
LowBlue mode	✔
Philips SmartUniformity	93 - 105%

Other features

Mean time between failures (MTBF)	70000 h
Ethernet LAN data rates	10,100,1000 Mbit/s
Wake-on-LAN	✔

8712581802578