Viewsonic Display VG2408A computer monitor 61 cm (24") 1920 x 1080 pixels Full HD LED Black

Brand : Viewsonic

Product name : Display VG2408A

Product code: VG2408A

- SuperClear® IPS panel
- 100Hz Refresh rate delivers fluid visuals
- USB hub with 1 upstream, 2 downstream ports, and HDMI, Display Port, VGA inputs for easy connectivity
- Height-adjustable swivel stand with pivot and tilt function
- Eye ProTech+ for always-on eye protection

24" IPS Full HD Ergonomic Monitor with USB Hub, IPS, 1920 x 1080, FHD, 18W, 16W, 542 x 386.2~516.2 x 223mm, 3.2 kg

Viewsonic Display VG2408A. Display diagonal: 61 cm (24"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Display technology: LED, Response time: 5 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). VESA mounting, Height adjustment. Product colour: Black

Display

Display diagonal *	61 cm (24")
Display resolution *	1920 x 1080 pixels
HD type *	Full HD
Native aspect ratio *	16:9
Display technology *	LED
Panel type *	IPS
Display brightness (typical)	250 cd/m²
Response time	5 ms
Anti-glare screen	✓
Screen shape *	Flat
Contrast ratio (typical) *	1300:1
Contrast ratio (dynamic)	50000000:1
Maximum refresh rate *	100 Hz
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours *	16.7 million colours
Pixel pitch	0.275 x 0.275 mm
Surface hardness	3H
Colour depth	8 bit
RGB colour space	sRGB
sRGB coverage (typical)	99%
NTSC coverage (typical)	77%

Performance

Flicker-free technology	✓
Low Blue Light technology	✗

Multimedia

Built-in speaker(s) *	✓
Number of speakers	2
RMS rated power	2 W

Design

Market positioning *	Gaming
Product colour *	Black

Ports & interfaces

DisplayPort version	1.2

Ergonomics

VESA mounting *	✓
Panel mounting interface	100 x 100 mm
Cable management	✓
Cable lock slot *	✓
Cable lock slot type	Kensington
Height adjustment *	✓
Height adjustment	13 cm
Pivot	✓
Pivot angle	90 - 90°
Swivelling	✓
Swivel angle range	0 - 360°
Tilt angle range	-4 - 28°
Tilt adjustment	✓

Power

Power consumption (typical) *	16 W
Power consumption (standby) *	0.3 W
Power consumption (max)	18 W
AC input voltage	100 - 240 V
Power supply type	Internal

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	20 - 90%

Weight & dimensions

Width (with stand)	542 mm
Depth (with stand)	223 mm
Height (with stand)	516.2 mm
Weight (with stand)	5.2 kg
Width (without stand)	542 mm
Depth (without stand)	44 mm
Height (without stand)	323 mm
Weight (without stand)	3.2 kg

Ports & interfaces		Packaging data	
VGA (D-Sub) ports quantity	1	Package width	609 mm
HDMI *	✔	Package depth	172 mm
HDMI ports quantity	1	Package height	398 mm
HDMI version	1.4	Package weight	6.8 kg
DisplayPorts quantity	1		

Ports & interfaces		Packaging data	
VGA (D-Sub) ports quantity	1	Package width	609 mm
HDMI *	✔	Package depth	172 mm
HDMI ports quantity	1	Package height	398 mm
HDMI version	1.4	Package weight	6.8 kg
DisplayPorts quantity	1		

0766907024104

766907024104