

## Lindy 47607 networking cable Grey 10 m Cat6a S/FTP (S-STP)

Brand: Lindy Product code: 47607

Product name: 47607

- Connector A: RJ45 Male - Connector B: RJ45 Male

- Housing Material: Polycarbonate

Connector Plating: NickelPin Construction: BrassPin Plating: Gold plated

- Dimensions (approx.) WxDxH: 11.6x21.5x8.3mm (0.46x0.85x0.33in)

- Length: 10m (32.81ft) - Colour: Grey

- Type: Cat.6A

- Jacket Diameter: 6.0mm (0.24in)

- Jacket Material: LSZH
- Conductor Material: Copper
- Conductor Gauge: 26AWG
- Shielding: Aluminium Braid
- Supported Bandwidth: 500MHz

- Nominal Attenuation: 49.3dB/100m @ 500MHz

- Minimum Bend Radius: 72mm (2.84in)

- Operating Temperature: -10°C - 60°C (14F - 140°F) - Storage Temperature: -10°C - 60°C (14F - 140°F)

- Packaging Type: Polybag- Warranty (Years): 10

- Product Compliance: RoHS, REACH, UL

10m Cat.6A S/FTP LSZH Network Security Cable, Grey

Lindy 47607. Cable length: 10 m, Cable standard: Cat6a, Cable shielding: S/FTP (S-STP), Connector 1:

RJ-45, Connector 2: RJ-45, Connector contacts plating: Nickel





Features		Features	
Product colour * Grey Cable length * 10 m Cable standard * Cat6a Cable shielding * S/FTP (S-STP)	AWG wire size Frequency Bend radius (min) Nominal attenuation	26 500 MHz 7.2 cm 49.3dB/100m @ 500MHz	
Connector 1 * Connector 2 *	RJ-45 RJ-45 Male Male Straight Straight	Certification  Operational conditions	RoHS, REACH, UL
Connector 1 gender * Connector 2 gender * Connector 1 form factor		Operating temperature (T-T) Storage temperature (T-T)	-10 - 60 °C -10 - 60 °C
Connector 2 form factor		Weight & dimensions	
Connector contacts plating  Connector shielding  ✓  Connector shielding	Connector 1 dimensions (WxDxH) Connector 2 dimensions (WxDxH)	11.6 x 21.5 x 8.3 mm 11.6 x 21.5 x 8.5 mm	
Jacket material Conductor material	Low smoke zero halogen (LSZH)	Packaging data Package type	Polybag
Connector 2 gender * Male  Connector 1 form factor Straight  Connector 2 form factor Straight  Connector contacts plating Nickel  Connector shielding  Connector shield material Aluminium  Jacket material Low smoke zero halogen (LSZH)	Storage temperature (T-T)  Weight & dimensions  Connector 1 dimensions (WxDxH)  Connector 2 dimensions (WxDxH)  Packaging data	-10 - 60 °C 11.6 x 21.5 x 8.3 mm 11.6 x 21.5 x 8.5 mm	

