

iivama TW2223AS-B1 touch control panel 54.6 cm (21.5") 1920 x 1080 pixels

Brand : iivama


Product code: TW2223AS-B1

Product name : TW2223AS-B1

21.5", 54.6cm, VA, 1920 x 1080, 16:9, 400 cd/m², 3000:1, 504.5 x 302 x 32mm, 640 x 410 x 121mm, 3.61kg, 5.98kg

iivama TW2223AS-B1 touch control panel 54.6 cm (21.5") 1920 x 1080 pixels:

21.5" Full HD PCAP 10pt interactive Touch Panel PC with Android OS and edge-to-edge glass design
The ProLite TW2223AS-B1 interactive Touchpanel-PC with an elegant edge-to-edge glass design is a perfect choice for high-use environments. This monitor can operate in landscape, portrait and face-up orientation in 24/7 operating time. Thanks to the pre-installed Android 12 operating system, it is possible to easily customize the monitor by installing applications directly to it. In combination with the 16GB storage, Wi-Fi connection, LAN (RJ45) and Bluetooth connectors, it makes the monitor especially suited for POS systems or information points in retail shops to educate customers about your products, as well as virtually limitless smart home applications.



Display		Performance	
Display diagonal *	54.6 cm (21.5")	Operating system installed	Android
Display resolution *	1920 x 1080 pixels	Ports & interfaces	
Display brightness	400 cd/m²	HDMI ports quantity	1
Touchscreen technology	Projected capacitive system	RJ-45 ports quantity	1
Number of simultaneous touchpoints	10	Bluetooth	✓
Aspect ratio	16:9	Bluetooth version	5.2
Contrast ratio	3000:1	Power	
Viewing angle, horizontal	178°	Power source type	AC
Viewing angle, vertical	178°	Power supply location	External
Audio		Power consumption (typical)	23 W
Built-in speaker(s) *	✓	Weight & dimensions	
Number of speakers	2	Width	504.5 mm
Speaker power	2 W	Depth	32 mm
Performance		Height	302 mm
Mounting type *	In wall	Weight	3.61 kg
Ethernet LAN	✓	Package weight	5.98 kg
Wi-Fi *	✓	Package depth	640 mm
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)	Package width	121 mm
Product colour *	Black	Package height	410 mm
Mean time between failures (MTBF)	50000 h	Package type	Box
VESA mounting	✓	Packaging content	
		Quantity	1
		Cables included	AC
		Quick start guide	✓



4948570122936

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 24-NOV-2023. Prints or copies of Information are only valid on the printed Publication date