

BenQ MW632ST data projector Standard throw projector 3200 ANSI lumens DLP WXGA (1280x800) 3D White

Brand : BenQ Product code: 9H.JE277.13H

Product name: MW632ST

1920 x 1200, 3200 ANSI, DLP, 4000h, 196W, HDMI, USB

BenQ MW632ST. Projector brightness: 3200 ANSI lumens, Projection technology: DLP, Projector native resolution: WXGA (1280x800). Light source type: Lamp, Service life of light source: 4500 h, Service life of light source (economic mode): 6000 h. Focal length range: 10.2 - 12.24 mm, Aperture range (F-F): 2.6 - 2.78, Zoom ratio: 1.2:1. Analog signal format system: SECAM, NTSC, PAL, Supported 3D formats: Frame Sequential, Top and bottom, Supported graphics resolutions: 640 x 480 (VGA), 1600 x 1200 (UXGA). Serial interface type: RS-232, HDMI version: 1.4a, USB connector type: USB Type-A, Mini-USB B





Projector		Ports & interfaces	
Screen size compatibility *	762 - 7620 mm (30 - 300") 13000:1 3200 ANSI lumens	Mobile High-Definition Link (MHL)	✓
Contrast ratio (dynamic)		Network	
Projector brightness *		Ethernet LAN *	×
Projection technology *	DLP	Wi-Fi *	×
Projector native resolution *	WXGA (1280x800)	Bluetooth	×
Native aspect ratio * Number of colours Horizontal scan range Vertical scan range	16:10 1.073 billion colours 15 - 102 kHz 24 - 120 Hz	Storage	
		Card reader integrated *	1
		Features	•
Keystone correction, horizontal	-30 - 30°	Noise level (economic mode)	28 dB
Horizontal synchronization (min)	15 kHz	HDCP	X
Horizontal synchronization (max)	102 kHz	On Screen Display (OSD)	7
Vertical synchronization (min)	0.024 kHz	on screen bisplay (03b)	Arabic, Dutch, Norwegian,
Vertical synchronization (max)	0.12 kHz		Bulgarian, English, Indonesian,
Light source		On Screen Display (OSD) languages	Italian, Polish, Swedish, Japanese,
Light source type *	Lamp	Oil Screen Display (OSD) languages	Romanian, Turkish, Croatian,
Service life of light source *	4500 h		French, Korean, Russian, Czech,
Service life of light source	6000 h	Number of OSD languages	Greek, Danish, Hungarian 28
(economic mode)	196 W	Noise level *	33 dB
Lamp power	190 W	Multimedia	
Lens system			,
Focal length range	10.2 - 12.24 mm	Built-in speaker(s) *	√ 10 W
Aperture range (F-F)	2.6 - 2.78	RMS rated power Number of built-in speakers	10 W
Zoom ratio	1.2:1	·	1
Throw ratio	0.72 - 0.87:1	Design	
Vertical lens shift range	-30 - 30%	Market positioning *	Business
Offset	105%	Product type *	Standard throw projector
Video		Product colour *	White
Analog signal format system *	SECAM, NTSC, PAL	Placement	Desktop
Full HD *	×	Cable lock slot	✓
3D *	✓	Display	
Supported 3D formats	Frame Sequential, Top and bottom	Built-in display *	1
Supported graphics resolutions	640 x 480 (VGA), 1600 x 1200 (UXGA)	Display number of colours	1.073 billion colours
Supported video modes	576i, 480i, 576p, 1080i, 480p, 1080p, 720p	Power source *	AC
Video processing	30 bit	Power consumption (typical) *	305 W
Ports & interfaces		Power consumption (standby) *	0.5 W
HDMI version	1.4a	1 , , , , , , ,	220 W
TIDIMI VCISIOII	1.70	• • •	

Ports & interfaces		Power	
S-Video inputs quantity USB 2.0 ports quantity * Mini-USB 2.0 ports quantity Audio (L/R) in * Microphone in Serial interface type * PC Audio in PC Audio out PC in (D-Sub) VGA (D-Sub) ports quantity * HDMI ports quantity * USB connector type DVI port *	1 1 1 X RS-232	AC input voltage AC input frequency	100 - 240 V 50 - 60 Hz
		Operational conditions Operating temperature (T-T)	0 - 40 °C
		Weight & dimensions	
		Width Depth Height Weight *	287.3 mm 232.6 mm 114.4 mm 2.6 kg
		Packaging content	5
		Remote control included * Remote control type Batteries included Cables included Quick start guide Manual Warranty card	√ IR √ AC, VGA √ √
		Technical details	
		Operating time	4000 h
		Other features	
		RS-232 ports	1

