TP-Link Tapo Pan/Tilt Home Security Wi-Fi Camera

Brand : TP-Link

Product family: Tapo

Product code: TAPO C200P2

Product name : Pan/Tilt Home Security Wi-Fi Camera

- High-Definition Video: Records every image in crystal-clear 1080p definition
- Pan and Tilt: 360º horizontal and 114º vertical range
- Advanced Night Vision: Provides a visual distance of up to 30 ft
- Motion Detection and Notifications: Notifies you when the camera detects movement
- Sound and Light Alarm: Trigger light and sound effects to frighten away unwanted visitors
- Two-Way Audio: Enables communication through a built-in microphone and speaker
- Safe Storage: Locally stores up to 512 GB on a microSD card, equal to 384 hours (16 days) of footage. (Based on laboratory conditions)
- Voice Control: Free Up Your Hands with Voice Control: Works with the Google Assistant and Amazon Alexa. (Google Assistant and Amazon Alexa are not available in all languages and countries)
1/3", 1080p Full HD (1920 ×1080 px), F 2.0, 4 mm, WLAN 802.11 b/g/n, 85.4 x 86.8 x 117.7 mm

Performance	
Type *	IP security camera
Placement supported *	Indoor
Connectivity technology *	Wireless
Operating frequency	2400 MHz

Design	
Form factor *	Spherical
Mounting type *	Desk
Product colour *	Black, White
LED indicators	✔

Camera	
Camera pan control	✔
Camera tilt control	✔
Angle of rotation	360°

Image sensor	
Sensor type *	CMOS

Lens system	
Maximum aperture number	2
Fixed focal length	4 mm

Night vision	
Night vision *	✔
Night vision distance	9 m

Video	
Maximum resolution *	1920 x 1080 pixels
Video formats supported	H.264
Frame rate	15 fps

Audio	
Built-in speaker(s)	✔
Built-in microphone	✔

Network	
Wi-Fi *	✔
Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)
Bluetooth *	✘

Storage	
Built-in HDD *	✘
Card reader integrated	✔
Compatible memory cards	MicroSD (TransFlash)
Maximum memory card size	512 GB

Ports & interfaces	
DC-in jack	✔

Security	
Video motion detection	✔

Power	
Power source type *	DC
AC input voltage	100 - 240 V
AC input frequency	50 / 60 Hz
DC output voltage	9
DC output current	0.6 A

Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%

Weight & dimensions	
Width	85.4 mm
Depth	86.8 mm
Height	117.7 mm

Packaging content	
Number of cameras *	2

Network

Ethernet LAN *	✘
Networking standards	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n

4895252501735

4895252501742